

### جدول کارکرد با نازل‌های با زاویه تراجکتوری کمتر

NOZZLE	Bar	m	l/min
1 LA	2.0	6.7	4.5
	3.0	7.3	6.4
	3.5	7.9	6.8
	4.0	8.5	7.6
3 LA	2.0	8.8	11.4
	3.0	9.8	11.7
	3.5	10.7	13.2
	4.0	11.3	14.4
4 LA	2.0	9.4	12.9
	3.0	10.4	14.8
	3.5	11.3	16.7
	4.0	11.6	17.8
6 LA	3.0	11.6	24.6
	3.5	12.2	27.6
	4.0	12.8	30.3
	5.0	13.4	32.6



### جدول کارکرد با نازل استاندارد

NOZZLE	Bar	m	l/min
3 Pre- installed	2.1	11.0	7.6
	2.8	11.6	9.1
	3.4	12.2	10.2
	4.1	12.2	11.0
0.5	2.1	8.5	1.9
	2.8	8.8	2.3
	3.4	8.8	2.7
	4.1	9.1	3.0
0.75	2.1	8.8	2.6
	2.8	9.1	3.0
	3.4	9.1	3.4
	4.1	9.4	3.8
1	2.1	9.1	3.4
	2.8	9.4	3.8
	3.4	9.4	4.5
	4.1	9.8	4.9
2	2.1	9.8	4.5
	2.8	10.1	5.3
	3.4	10.4	6.1
	4.1	10.4	6.8
4	2.1	11.0	9.8
	2.8	12.2	11.4
	3.4	12.8	12.9
	4.1	12.8	14.0
6	2.1	11.6	15.9
	2.8	13.1	18.5
	3.4	14.0	20.8
	4.1	14.3	22.7
8	2.8	13.7	22.7
	3.4	14.6	25.7
	4.1	14.9	28.8
	4.8	15.5	31.0