



SPECS

FRAME	
SIZES	XS, S, M
COLOURS	Starry Gray / Metallic Purple
FRAME	ALUXX aluminum, Overdrive 1½ - 1⅝" head tube, 141mm Boost QR, integrated KS18 kickstand mount
FORK	SR Suntour XCM34 Boost Coil NLO 27,5+ 120mm travel, Tapered 1½ - 1⅝" steerer, lockout
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect TR Riser
STEM	Giant Contact
SEATPOST	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADDLE	Liv Sport
PEDALS	Aluminum Platform
DRIVETRAIN	
SHIFTERS	Shimano SL-M2000
FRONT DERAILLEUR	-
REAR DERAILLEUR	Shimano Deore, 9-Speed, Shadow design
BRAKES	Tektro HD-M286, hydraulic disc, 180mm
BRAKE LEVERS	Tektro HD-M285
CASSETTE	Shimano CS-HG200, 11-36T, 9-Speed
CHAIN	KMC e.9 Sport, e-bike optimized
CRANKSET	Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring
WHEELS	
BOTTOM BRACKET	N/A
RIMS	Giant AM 27.5, Tubeless ready, 30mm inner width, e-bike optimized
HUBS	Giant eTracker Boost, [F] 15mm Thru-Axle [R] 148x12mm Thru-axle, e-bike optimized
SPOKES	Stainless steel
TIRES	Maxxis Forekaster 27.5x2.6, foldable, 60 TPI, EXO, Tubeless ready
EXTRAS	Giant EnergyPak 4A fast charger
HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport, 70Nm, 350% tuneable support with automatic smart support
SENSORS	Giant PedalPlus 6-sensor technology
DISPLAY	Giant RideControl ONE, remote button
BATTERY	Giant EnergyPak500, 36V 13.8Ah Rechargeable Lithium-Ion

FEATURES

- Frame: ALUXX aluminum, Overdrive 1½ - 1⅝" head tube, 141mm Boost QR, integrated KS18 kickstand mount
- Fork: SR Suntour XCM34 Boost Coil NLO 27,5+ 120mm travel, Tapered 1½ - 1⅝" steerer, lockout
- Shifters: Shimano SL-M2000
- Crankset: Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring
- Colours: Starry Gray / Metallic Purple

Suggested Retail Price (CDN): \$2,999

FRAME GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	365	405	460
Seat Tube Angle	74.0°	73.5°	73.0°
Top Tube Length (mm)	550	565	585
Head Tube Length (mm)	110	115	135
Head Tube Angle	68.0°	68.0°	68.0°
Fork Rake (mm)	42	42	42
Trail (mm)	100.2	100.2	100.2
Wheelbase (mm)	1116	1126	1142
Chain Stay Length (mm)	475	475	475
Bottom Bracket Drop (mm)	50	50	50
Stack (mm)	612	617	635
Reach (mm)	374	382	390
Stand Over Height (mm)	674	696	742
Handlebar Width (mm)	690	690	750
Stem Length (mm)	50	50	60
Crank Length (mm)	170	170	170
Wheel Size	27.5+	27.5+	27.5+

All prices and specifications are subject to change without notice.