

Mosaic™ Programme mechanisms

international standards socket outlets



0 775 02



0 775 04



0 775 05



0 775 06



0 787 00

Selection chart for boxes, supports and plates **p. 900-901**

| Pack | Cat.Nos | Other standard socket outlets |
|------|-----------------------|--|
| 10 | 0 775 01 | Euro-US standard - white 1 module |
| 10 | 0 775 02 ¹ | 2 modules |
| 10 | 0 775 03 | US standard - white 1 module |
| 10 | 0 775 04 | 2 modules - 15 A |
| 10 | 0 775 05 | British standard - white 2 modules - 13 A |
| 10 | 0 775 10 | Italian type - white 1 module - 10 A - screw terminals |
| 10 | 0 775 11 | 1 module - 10/16 A - screw terminals |
| 10 | 0 775 12 | German-Italian standard 2 modules - 16 A - screw terminals Not compatible with a 2-module support |
| 10 | 0 775 06 ¹ | Swiss type - white 2 modules - type 13 |
| 10 | 0 775 08 ¹ | Danish standard - white 2 modules - with shutters for child protection |
| 10 | 0 775 09 ¹ | 2 modules - for UPS - with shutters for child protection |

| Pack | Cat.Nos | 2P ELV socket outlet |
|------|----------|---|
| 10 | 0 771 50 | With shutters for child protection For installation in flush-mounting box, surface-mounting box, floor box, column module, desktop multi-outlet extension, office module and trunking 1 module - white antimicrobial ⁽¹⁾ |
| 1 | 0 787 00 | Equipotential socket Equalises the voltages of all the conductive elements and all the exposed conductive parts, as well as limiting the contact voltage to a value that is not dangerous for people. For use in hospital environments to prevent disturbance of sensitive equipment Conforms to standards DIN 42801 and IEC 60364-7-710 1 module White antimicrobial ⁽²⁾ |
| 10 | 7 759 93 | Equipotential plug Equipotential connection plug |

1: Can be installed in receptacles for floor sockets (p. 479)

2: Contains a silver compound to prevent the growth of bacteria on the surface of the plate