



Product data sheet

HDW332M323FH5556M

Characteristics

Air circuit breaker, HDW3, 3200AF, 3200 A, 3P, fixed horizontal, 6 NO + 6 NC



Product Image Coming Soon

Main

Range of product	HDW3
Product or component type	Air circuit breaker
Frame size	3200AF
[Icu] ultimate breaking capacity	80 kA at 400 V load 65 kA at 690 V load
[Ics] rated service breaking capacity	65 kA at 400 V 50 kA at 690 V
[Icw] rated short-time withstand current	65 kA at 400 V duration: 1 s 50 kA at 690 V duration: 1 s

Complementary

[In] rated current	3200 A
Poles description	3P
Mounting mode	Fixed
Mounting position	Horizontal
Voltage release type	Without motor mechanism, closing release, shunt release and undervoltage release
Maximum tripping time	25 ms
Maximum closing response time	70 ms
Auxiliary contact composition	6 NO + 6 NC
Product compatibility	Series intelligent controller iTR326A standard protection
Height	397 mm
Width	428 mm
Depth	327 mm
Net weight	53.4 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	39.7 cm
Package 1 Width	42.8 cm
Package 1 Length	32.7 cm
Package 1 Weight	53.4 kg