

LKX XP (three phase)

Accessory holder
Power cable holder



BX4 15-200

Ergonomic handle

Panel with analogic controls

Heavy frame



Standard equipment:

- Gun with rotating coupling.
- Lance with nozzle-holder.
- Power cable 5 m
- High pressure hose 10 m



- Vertical burner with high thermal efficiency steel coil.
- Temperature regulation gauge.
- Safety valve.
- Low fuel lamp.



- Auxiliary motor for burner.

Optional:

- Hose-reel with brake (hose not included) cod.3.697.0044
- On request models with header tank and/or antiscaling device.
- Antiscaling LC-PRECAL (pcs. 4 x 5 lt.) cod. 3.697.0044



	LKX 1515 XP	LKX 2015 XP
Code	8.621.0902	8.621.0903
operat. pressure/max	30+150 bar	30+200 bar
operat. pressure/max	435+2175 psi	435+2900 psi
delivery rate	450+900 l/h	450+900 l/h
delivery rate	1.98+3.96 GPM	1.98+3.96 GPM
abs. power/voltage	5500W - 400V-50Hz	7300W - 400V-50Hz
RPM	1450 RPM	1450 RPM
diesel tank/detergent tank	18/3,0 l.-4.8/0.79 gal	18/3,0 l.-4.8/0.79 gal
max temp. inlet/outlet	40 °C / 140 °C	40 °C / 140 °C
fuel consumption/heat output	5,6 l/h-1.5 gal/h / 74 kW	5,6 l/h- 1.5 gal/h / 74 kW
machine dimensions	94x65x90 cm	94x65x90 cm
machine weight	114 Kg / 250.8 lbs	116 Kg / 255.2 lbs