

HyperT

GUARANTEED

Easy access to main mechanical components



BL4 21-200

Impact and weather resistant, polypropylene and polyethylene

inlet water filter

CRANKSHAFT PUMP

WATER COOLING

PRESSURE REGULATOR

ANTI SCALE

DETERGENT

DETERGENT TANK

PRESSURE GAUGE

only HyperT 2021

TS Total Stop 24V

1450 RPM

700 mm 400 mm

Standard equipment:

- Gun with rotating coupling.
- Lance with nozzle-holder.
- Power cable 5 m
- High pressure hose 10 m



- Pressure accumulator for hose and gun vibrations prevention (only HyperT 2021 model).



- Integrated elastic joint, for best pump coupling.
- High (> 90%) thermal efficiency burner.



- Header tank and antiscaling device.

Optional:

- Hose-reel with brake (hose not included) cod. 6.608.0010
- Antiscale LC-PRECAL (pcs. 4 x 5 lt.) cod. 3.697.0044



	HYPER T 1515 LP	HYPER T 2015 LP	HYPER T 2021 LP
Code	8.623.0904	8.623.0905	8.623.0902
operat. pressure/max	30+150 bar	30+200 bar	30+200 bar
operat. pressure/max	435+2175 psi	435+2900 psi	435+2900 psi
delivery rate	345+900 l/h	450+900 l/h	630+1260 l/h
delivery rate	1.52+3.96 GPM	1.98+3.96 GPM	2.77+5.55 GPM
abs. power/voltage	5500W-400V-50Hz	7300-400V-50Hz	9700-400V-50Hz
RPM	1450	1450	1450
diesel tank/detergent tank/antiscaling	22/22/2,4 l.-5.82/5.82/0.63 gal	22/22/2,4 l.-5.82/5.82/0.63 gal	22/22/2,4 l.-5.82/5.82/0.63 gal
max temp. inlet/outlet	40 °C / 140 °C	40 °C / 140 °C	40 °C / 140 °C
fuel consumption/heat output	6.6 l/h - 1.25 gal/h / 88 kW	6.6 l/h - 1.25 gal/h / 88 kW	6.6 l/h / 88 kW
machine dimensions	125x69x89 cm	125x69x87 cm	125x69x89 cm
machine weight	170 Kg / 374 lbs	175 kg / 385 lbs	180 kg / 396 lbs