



IECEX



REACH



RoHS

**Intrinsically Safe
Flashlights**

DS-1



(Optional Accessories)



Fastener





Valve



Magnetic Control Switch
With Safety Lock

TECHNOLOGY



SPECS

	Low	High
Battery Size	4*AA	
Light Source	Cree XP-G LED	
Mode	High/Low/Flash/Off	
Light Output	62lm	157lm
Beam Distance	83m	117m
Run Time	13hrs	6hrs 10mins
IP Rating	IP68 (3m)	
Weight	140g	
Dimension	172*47*47mm	

Certifications & Standards:

- UL	CLASS I DIV I GRP ABCD CLASS II DIV I GRP EFG CLASS III TEMP CODE: T4	DS-1
- ATEX	Ex II 1 G Ex ia IIC T4	
- IECEX	Ex ia IIC T4 Ga	
- CE	Approved	
- ROHS	Approved	
- REACH	Approved	

- CREE XP-G POWER LED
- HIGH / LOW / FLASH / OFF
- MAGNETIC CONTROL SWITCH
- SAFETY LOCK
- HIGH IMPACT LENS
- FASTENER PREVENTS FROM OPENING TORCH IN HAZARDOUS PLACES.
- VALVE DESIGN HELPS TO HYDROGEN GAS RELEASED.



Color