



Model		991-NH1 Standard M	lodel	991-NH2 Advanced Model
Camera head	Cable	3m (5m : available as option)		
	View Angle (H ∕V)	72deg / 54 deg		
	Size / View range	1/13" CMOS / 20mm - ∞		
	Illumination	4LED Bulbs (Plus 3	0 LED Bulk	os installed in Sensor Unit)
	Articulation	360 degree Look-a-Round joystick control		
	Protection	IP 67		
	Out- Side diameter	6.9mm		
Video Scope	Monitor display	2.5"		3.5"
	Recording	micro-SD memory card recording (Movie and still Image)		
	2X Zooming	_		0
	Temperature Display	_		0
	Battery system	AA Ni-MH Type Recharge	able Battery	4 ea with Battery charger
Auxiliary LED Illumination		8 LED Bulbs / AA Ni-MH Type Rechargeable Battery 6 ea with Battery Charger		
PROEAR Two-Way communication		0		Ο
Carrying Case		968*406*155 mm / 15 kg		

## **YONE CORPORATION**

Table.1

23 NISHINAKAAI-CHO, NISHINOKYO, NAKAKYOUKU, KYOTO CITY, JAPAN TEL: +81 75 821 1185 FAX:-81 75 801-2263

www.yone-co.co.jp