

ANALOGUE

COOPER

QTY PRICE

1	DH-HAC-T2A21P-0280B	12,800,000
2	DH-HAC-T1A41P-0280B-S2	13,520,000
3	DH-HAC-T2A41P-0280B-S2	16,490,000
4	DH-HAC-T2A51P-0280B-S2	19,960,000
5	DH-HAC-B1A21P-0280B	10,900,000
6	DH-HAC-B2A21P-0280B	13,290,000
7	DH-HAC-B2A21P-0360B	13,290,000
8	DH-HAC-B2A41P-0280B-S2	17,730,000
9	DH-HAC-B2A51P-0360B-S2	19,130,000

2MP

10	DH-HAC-HDW1200TRQP-0280B-S5	14,350,000
11	DH-HAC-HDW1200EMP-A-0280B-S5	17,580,000
12	DH-HAC-HDW1200MP-0280B-S5	14,710,000
13	DH-HAC-HFW1200TP-0280B-S5	15,810,000
14	DH-HAC-HFW1200TP-A-0360B-S5	16,740,000
15	DH-HAC-HFW1200SP-0360B-S5	16,620,000
16	DH-HAC-HFW1200DP-0360B-S5	20,410,000
17	DH-HAC-HFW1200TLP-0280B-S5	15,780,000
18	DH-HAC-HFW1200CP-A-0360B-S5	15,910,000
19	DH-HAC-HFW1200CMP-A-0280B-S5	21,210,000
20	DH-HAC-HFW1231RP-Z-A	42,830,000

2MP (FULL COLOR)

21	DH-HAC-HFW1209CP-A-LED-0360B	20,890,000
22	DH-HAC-HDW1209TLQP-A-LED-0280B	16,940,000
23	DH-HAC-HDW1239TLQP-A-LED-0360B-S2	26,200,000
24	DH-HAC-HFW1239TP-A-LED-0360B-S2	22,010,000

4MP

25	DH-HAC-HFW1400TP-0280B-S3	24,140,000
----	---------------------------	------------

5MP

26	DH-HAC-HDW1500TMQP-A-0280B-S2	26,500,000
27	DH-HAC-HDW1500TLMQP-0280B-S2	23,960,000
28	DH-HAC-HFW1500TP-0360B-S2	25,770,000
29	DH-HAC-HFW1500TP-A-0360B-S2	24,930,000
30	DH-HAC-HFW1500DP-0360B-S2	28,690,000

5MP (FULL COLOR)

31	DH-HAC-HDW1509TLQP-LED-0360B-S2	34,930,000
----	---------------------------------	------------

XVR

32	DH-XVR1B08-I	34,780,000
33	DH-XVR1B16-I	68,700,000
34	DHI-XVR5108HS-4KL	108,500,000
35	DH-XVR5216AN-I3	144,610,000
36	DH-XVR5232AN-I3	248,330,000
37	DH-XVR5104HS-4KL-I3	68,970,000
38	DH-XVR5108HS-4KL-I3	115,560,000
39	DH-XVR5216AN-4KL-I3	222,270,000

IPC

2MP(Entry Series)

40	DH-IPC-HDW1230SP-0280B-S5-QH2	31,260,000
41	DH-IPC-HDW1230TIP-0360B-S5-QH2	31,230,000
42	DH-IPC-HFW1230S1P-0360B-S5-QH2	29,540,000
43	DH-IPC-HFW1230SP-0360B-S5-QH2	33,300,000
44	DH-IPC-HFW1239S1-LED-0360-S5	32,330,000

4MP(Entry Series)

45	DH-IPC-HDBW1431EP-0280B-S4	46,890,000
----	----------------------------	------------

2MP(Lite Series)

46	DH-IPC-HFW2230SP-S-0360B-S2-QH3	38,640,000
47	DH-IPC-HFW2231T-ZS-S2	73,910,000
48	DH-IPC-HDW2231TP-AS-0280B-S2-QH	46,550,000
49	DH-IPC-HDW2231TMP-AS-0280B-S2-QH	49,740,000

2MP(FULL COLOR)

50	DH-IPC-HDW2239TP-AS-LED-0280B-S2	48,020,000
51	DH-IPC-HFW2239SP-SA-LED-0360B-S2	46,640,000

4MP(Lite Series)

52	DH-IPC-HDW2431TMP-AS-0280B-S2	58,610,000
----	-------------------------------	------------

4MP(WizSense)

53	DH-IPC-HDW3441TMP-AS-0280B	66,760,000
54	DH-IPC-HFW3441TP-ZAS-27135	110,230,000

55	DH-IPC-HFW3449EP-AS-LED-0360B	79,250,000
56	DH-IPC-HDW3449TMP-AS-LED-0280B	72,920,000

Eco savvy 3.0

57	DH-IPC-HFW4441EP-AS-0280B	89,810,000
-----------	----------------------------------	-------------------

PTZ

58	DH-SD49225-HC-LA	226,580,000
59	DH-SD49225XA-HNR	259,340,000
60	DH-SD5A432XB-HNR	536,320,000
61	DH-TPC-PT8621A-T	CALL

NVR

62	DHI-NVR4104HS-4KS2/L	59,520,000
63	DHI-NVR4104HS-P-4KS2/L	82,750,000
64	DHI-NVR4108HS-4KS2/L	61,780,000
65	DHI-NVR4216-16P-4KS2/L	187,070,000
66	DHI-NVR2216-I	106,060,000
67	DHI-NVR2216-I2	106,980,000
68	DHI-NVR5216-4KS2	183,010,000
69	DHI-NVR5232-4KS2	192,120,000
70	DHI-NVR5432-4KS2	289,280,000
71	DHI-NVR608-128-4KS2	924,810,000

MP CCTV

مرکز پخش دوربین مداربسته داهوا

لیست قیمت محصولات داهوا

www.mpcctv.com
021-88946050
021-88944334



HDCVI Camera

1	DH-HAC-B2A21P	1,190,000
2	DH-HAC-HFW1200TP	1,520,000
3	DH-HAC-HFW1500TP	2,330,000
4	DH-HAC-HFW1200DP	1,990,000
5	DH-HAC-HFW1500DP	3,520,000
6	DH-HAC-T1A21P	1,080,000
7	DH-HAC-T2A21P	1,190,000
8	DH-HAC-HDW1200RP	1,220,000
9	DH-HAC-HDW1200TQP-A	1,630,000
10	DH-HAC-HDW1200TRQP-A	1,390,000
11	DH-HAC-HDW1500TQP-A	2,130,000
12	DH-HAC-HDW1500TRQP-A	1,900,000
13	DH-HAC-HDW1500TMQP-A	2,750,000

HDCVI Full Color Camera

14	DH-HAC-HFW1209CP-LED	1,575,000
15	DH-HAC-HFW1209CP-A-LED	1,650,000
16	DH-HAC-HFW1209CMP-LED	1,670,000
17	DH-HAC-HFW1209TLMP-LED	1,850,000
18	DH-HAC-HFW1509TP-A-LED	3,240,000
19	DH-HAC-HFW1509TLMP-LED	3,040,000
20	DH-HAC-HFW1509TLMP-A-LED	3,220,000
21	DH-HAC-HDW1209TLQP-LED	1,440,000
22	DH-HAC-HDW1209TLQP-A-LED	1,580,000

23	DH-HAC-HDW1209TQP-A-LED	1,820,000
24	DH-HAC-HDW1509TP-A-LED	3,600,000
25	DH-HAC-HDW1509TLQP-A-LED	3,000,000

HDCVI Recorder

26	DH-XVR1B04-I - Cooper	2,550,000
27	DH-XVR1B08-I - Cooper	3,240,000
28	DH-XVR1B16-I - Cooper	6,870,000
29	DH-XVR5104HS-I3	4,270,000
30	DH-XVR5104HS-4KL-I3	7,390,000
31	DH-XVR5108HS-I3	6,660,000
32	DH-XVR5108HS-4KL-I3	11,050,000
33	DH-XVR5116HS-I3	10,940,000
34	DH-XVR5216AN-I3	14,100,000
35	DH-XVR5216AN-4KL-I3	21,300,000
36	DH-XVR5232AN-S2	*****
		####
37	DH-XVR5232AN-I3	*****
		####

IP VIDEO DISTRIBUTION

PRODUCTS

Network Camera

38	DH-IPC-HFW1230S1P	2,750,000
39	DH-IPC-HFW1230SP	3,540,000
40	DH-IPC-HFW2431SP-S	4,660,000
41	DH-IPC-HFW2531SP-S	6,590,000
42	DH-IPC-HFW4431TP-S	7,900,000
43	DH-HFW3449EP-AS	8,600,000
44	DH-IPC-HFW2531TP-AS	7,330,000
45	DH-IPC-HFW2831TP-ZAS	15,000,000
46	DH-IPC-HDW1230TIP	2,950,000
47	DH-IPC-HDW2431TP-AS	4,660,000

48	DH-IPC-HDW2431TMP-AS	5,520,000
49	DH-IPC-HDW2531TP-AS	6,300,000
50	DH-IPC-HDW2531TMP-AS	6,670,000
51	DH-SD49425XB-HNR	30,000,000
52	DH-SD5A432XB-HNR	55,200,000

Network Full Color Camera

53	DH-IPC-HFW1239S1P-LED	3,050,000
54	DH-IPC-HFW2439SP-SA-LED	5,550,000
55	DH-IPC-HDW1239TIP-LED	3,050,000
56	DH-IPC-HDW2439TP-AS-LED	5,550,000

Network Recorder

57	DH-NVR2108HS-S3	5,500,000
58	DH-NVR4116HS-4K-S2/L	8,160,000
59	DH-NVR4216HS-4K-S2/L	9,100,000
60	DH-NVR4232-4KS2/L	12,000,000
61	DH-NVR4432-4KS2/L	25,140,000
62	DH-NVR5232-4KS2	20,300,000
63	DH-NVR5432-4KS2	27,000,000
64	DH-NVR5832-4KS2	41,670,000
65	DH-NVR608-32-4KS2	42,550,000
66	DH-NVR608-128-4KS2	83,400,000
67	DH-NVR5464-4KS2	47,000,000
68	DH-NVR5864-4KS2	50,000,000

لیست قیمت محصولات داهوا



www.mpcctv.com
021-88946050
021-88944334



Network Camera		price	QTY
Ip series			
1	IPC-HDBW2231RP-ZS	44,600,000	
2	IPC-HDBW2230EP-S	42,800,000	
3	IPC-HDBW2231EP-S	43,680,000	
4	IPC-HDBW2431RP-ZS	84,200,000	
5	IPC-HDBW3241FP-AS-M	67,800,000	
6	IPC-HDBW5242EP-ZE-MF	140,000,000	
7	IPC-HDPW1431R1P	38,000,000	
8	IPC-HDW1230SP-LED	31,000,000	
9	IPC-HDW1230T1P-LED	31,000,000	
10	IPC-HDW1239T1P-LED	30,600,000	
11	IPC-HDW1431T1P	38,000,000	
12	IPC-HDW2230TP-AS	40,000,000	
13	IPC-HDW2231TP-AS	43,200,000	

14	IPC-HDW2239TP-AS-LED	47,300,000	
15	IPC-HDW2431TP-AS	48,200,000	
16	IPC-HDW2439TP-AS-LED	51,800,000	
17	IPC-HDW2531TP-AS	64,800,000	
18	IPC-HDW2831TP-AS	78,500,000	
19	IPC-HDW3449TMP-AS-LED	71,000,000	
20	IPC-HF5241EP-E	98,600,000	
21	IPC-HFW1230SP-S5	31,400,000	
22	IPC-HFW1230S1P	29,300,000	
23	IPC-HFW1431SP	44,900,000	
24	IPC-HFW2230SP-S	30,900,000	
25	IPC-HFW2231SP-S	34,500,000	
26	IPC-HFW2231TP-ZS	69,160,000	
27	IPC-HFW2431SP-S	48,200,000	
28	IPC-HFW2439SP-SA-LED	53,600,000	
29	IPC-HFW2531TP-AS	79,700,000	
30	IPC-HFW2831SP-S	78,600,000	
31	IPC-HFW2831TP-ZS	123,000,000	
32	IPC-HFW3441EP-SA	71,800,000	
33	IPC-HFW3449EP-AS-LED	78,000,000	
34	IPC-HFW5241EP-ZE	132,000,000	
PTZ Series			
35	SD49225-HC-LA1	208,000,000	

36	SD49225XA-HNR-s3	245,000,000	
37	SD49425XB-HNR	290,000,000	
HDCVI Camera			
Cooper Series			
38	HAC-B1A21P	9,500,000	
39	HAC-B1A51P	16,300,000	
40	HAC-T1A21P	9,800,000	
41	HAC-T1A51P	16,400,000	
42	HAC-T2A21P	12,350,000	
Cvi series			
7	HAC-HDW1200TRQP-A	14,200,000	
44	HAC-HDW1209TLQP-LED	14,400,000	
45	HAC-HDW1239TLQP-A-LED	20,000,000	
46	HAC-HDW1500TLMQP-A	23,800,000	
47	HAC-HDW1500TRQP-A	19,000,000	
48	HAC-HDW1500TLMP	22,000,000	
49	HAC-HDW1509TLQP-LED	28,400,000	
50	HAC-HDW1509TLQP-A-LED	30,300,000	
51	HAC-HFW1200RP-Z-IRE60	31,000,000	
52	HAC-HFW1200SP	15,900,000	
53	HAC-HFW1200THP-I4	20,000,000	
54	HAC-HFW1200THP-I8	22,000,000	
55	HAC-HFW1209TLMP-LED	20,000,000	

56	HAC-HFW1209CP-LED	16,400,000	
57	HAC-HFW1239CP-LED	22,500,000	
58	HAC-HFW1239TP-LED	23,600,000	
59	HAC-HFW1500CMP	23,600,000	
60	HAC-HFW1500CMP-A	25,400,000	
61	HAC-HFW1500CP	21,000,000	
62	HAC-HFW1500RP-Z-IRE6	43,800,000	
63	HAC-HFW1500TP-A	24,700,000	
64	HAC-HFW1500THP-I8	27,300,000	
65	HAC-HFW1509TLMP-LED	29,500,000	
66	HAC-HFW1509TP-LED	30,600,000	
xvr Series			
Cooper-I Series			
67	XVR1B04-I	27,200,000	
68	XVR1B08-I	32,200,000	
69	XVR1B16-I	61,000,000	
70	XVR4108HS-I	51,500,000	
71	XVR4116HS-I	75,200,000	
72	XVR5104HS-4KL-I3	68,700,000	
73	XVR5104HS-I3	49,000,000	
74	XVR5108HS-I3	69,000,000	
75	XVR5116HS-I3	106,000,000	
76	XVR5216AN-4KL-I3	217,500,000	

77	XVR5232AN-I3	253,000,000	
78	XVR5432L-I3	418,000,000	
NVR2-I Series			
79	NVR2104HS-I2	60,200,000	
80	NVR2108HS-I	67,500,000	
81	NVR2108HS-8P-I	85,300,000	
82	NVR2216-I2	96,400,000	
83	NVR4108HS-4KS2/L	61,400,000	
84	NVR4208-8P-4KS2/L	100,000,000	
85	NVR4216-4KS2/L	100,000,000	
86	NVR5216-16P-I	318,000,000	
87	NVR5216-4KS2	185,000,000	
88	NVR5216-EI	215,000,000	
89	NVR5232-4KS2	200,000,000	
90	NVR5232-EI	245,000,000	
91	NVR5432-4KS2	291,000,000	
92	NVR5432-EI	318,500,000	
93	NVR5832-4KS2	400,000,000	
94	NVR5864-4KS2	478,000,000	
95	NVR5864-EI	577,000,000	
96	NVR608-32-4KS2	458,000,000	
97	NVR608-64-4KS3	870,000,000	
98	NVR608H-64-XI	955,000,000	

لیست قیمت محصولات داهوا



www.mpcctv.com
021-88946050
021-88944334

۲۸ ماه گارانتی
مادپلای
مرکز جامع ارائه خدمات و گارانتی

MODEL		PRICE
1	DH-HAC-HFW1500RP-Z-IRE6-A	49,450,000
2	DH-HAC-HFW1500DP	33,012,000
3	DH-HAC-HFW1500SLP	30,520,000
4	DH-HAC-HFW1500THP-I8	33,421,500
5	DH-HAC-HFW1500TP-A	27,400,000
6	DH-HAC-HFW2249TP-I8-A	56,340,000
7	DH-HAC-HFW1231TMP-I8-A	31,020,000
8	DH-HAC-HFW1231CMP	28,182,000
9	DH-HAC-HFW1239TP-A-LED	27,470,000
10	DH-HAC-HFW1239TP-LED	26,840,000

11	DH-HAC-HFW1209CMP-LED	2MP Full-color HDCVI Bullet Camera> 24/7 color imaging> 20 m illumination <distance> Max. 30 fps @1080p> Built-in mic (-A)> CVI / CVBS / AHD / TVI switchable Fixed lens (2.8 mm; 3.6 mm optional) > IP67, 12V ± 30% DC	20,130,000
12	DH-HAC-HFW1200CMP	MP HDCVI Bullet Camera with IR Illumination> Up to 30fps @ 1080P> Switchable 2 CVI / CVBS / AHD / TVI outputs> Fixed lens 3.6mm (2.8mm optional)> Built-in ,microphone (-A)> Max. IR illumination range 30m, Intelligent IR illumination > IP67 DC12V	17,450,000
13	DH-HAC-HFW1209CP-LED	·Full-color starlight· 20 m illumination distance· Max. 30fps@1080P · CVI/CVBS/AHD/TVI switchable· Fixed lens (2.8 mm;3.6 mm optional) · IP67, 12V±30% DC	16,720,000
14	DH-HAC-HFW1200RP-Z-IRE6	Max 30fps@1080P(1920×1080)· HD and SD output switchable· 2.7-12mm Motorized · lens· Max. IR length 60m, Smart IR · IP67, DC12V	36,620,000
15	DH-HAC-HFW1230DP	Starlight· Max. 30fps@1080P· HD and SD output switchable· 3.6mm fixed lens · · Max. IR length 80m, Smart IR· IP67, DC12V(6mm, 8mm optional)	25,870,000
16	DH-HAC-HFW1200DP	Max 30fps@1080P(1920×1080)· HD and SD output switchable· 3.6mm fixed lens · · Max. IR length 80m, Smart IR · IP67, DC12V(6mm, 8mm optional)	21,574,800
17	DH-HAC-HFW1200TP-A	2Megapixel CMOS. 25/30fps@1080P, 25/30/50/60fps@720P. 3.6mm fixed *1/2.7 . ,lens. Built-in mic. HD and SD output switchable. DWDR, Day/Night(ICR), AWB, AGC BLC,HLC, 2DNR ,OSD . Max. IR length 30m, Smart IR. IP67, DC12V	19,120,000
18	DH-HAC-HFW1200TP	·2MP HDCVI IR Bullet Camera· Max 30fps@1080P· HD and SD output switchable . 3.6mm fixed lens (2.8mm, 6mm optional)· Max. IR length 30m, Smart IR · IP67, DC12V	16,800,000
19	DH-HAC-HFW1200THP-I8	·2MP HDCVI IR Bullet Camera· Max 30fps@1080P· HD and SD output switchable . 3.6mm fixed lens (2.8mm, 6mm optional)· Max. IR length 80m, Smart IR · IP67, DC12V	22,814,000
20	DH-HAC-HFW1230THP-I8	2MP Starlight HDCVI IR Bullet Camera· Max. 30fps@1080P· HD and SD output ·switchable· 3.6mm fixed lens (6mm, 8mm optional) · Max. IR length 80m, Smart IR IP67, DC12V	23,200,000
21	DH-HAC-HFW1230TP	2MP Starlight HDCVI IR Bullet Camera· Max. 30fps@1080P. Starlight· HD and SD . ,output switchable· 3.6mm fixed lens (2.8mm, 6mm optional)· Max. IR length 30m Smart IR · IP67, DC12V	25,620,000
22	DH-HAC-HFW1230TLP	2MP Starlight HDCVI IR Bullet Camera· Max. 30fps@1080P· HD and SD output . · switchable· 3.6mm fixed lens (2.8mm, 6mm optional)· Max. IR length 40m, Smart IR IP67, DC12V	21,960,000
23	DH-HAC-HFW1200SP	Max 30fps@1080P(1920×1080). 2MP HDCVI IR Bullet Camera· HD and SD output · · switchable· 3.6mm fixed lens (2.8mm, 6mm optional)· Max. IR length 30m, Smart IR IP67, DC12V	18,280,000
24	DH-HAC-HFW1200TLP-A	Max 30fps@1080P> HD and SD output switchable> 3.6mm fixed lens (2.8mm, 6mm < optional) > Built-in mic> Max. IR length 80m, Smart IR> IP67, DC12V	19,110,000
25	DH-HAC-HFW1200TLP	Max 30fps@1080P· HD and SD output switchable· 3.6mm fixed lens (2.8mm, 6mm · optional)· Max. IR length 40m, Smart IR · IP67, DC12V	16,620,000
26	DH-HAC-HFW1200RP	2MP HDCVI IR Bullet Camera· Max 30fps@1080P(1920×1080)· HD and SD output . · switchable· 3.6mm fixed lens (2.8mm, 6mm optional)· Max. IR length 20m, Smart IR IP67, DC12V	14,020,000

27	DH-HAC-HDW1500TP-Z-A	Max. 20fps@5MP(2592*1944). 1/2.7" Progressive CMOS. 20fps@5MP, 25/30fps@4MP. 25/30fps@1080P. HD and SD output switchable. Built-in mic. 2.7-12mm motorized lens. IP67, DC12V. Max. IR length 60m, Smart IR	48,230,000
28	DH-HAC-HDW1509TLQP-A-LED	5MP Full-color HDCVI Quick-to-install Eyeball Camera > Max 25 fps@5MP (16:9 video <output>) > 120dB true WDR, 3D NR > 24/7 color imaging > 20 m illumination distance CVI/CVBS/AHD/TVI switchable > Built-in mic (-A) > 3.6 mm fixed lens (2.8 mm optional) > IP67, 12 V DC > Quick-to-install eyeball saves installation time	38,000,000
29	DH-HAC-HDW1509TLP-A-LED	5MP Full-color Starlight HDCVI Eyeball Camera · Full-color starlight > 20 m LED distance · Max. 20fps@5MP · CVI/CVBS/AHD/TVI switchable · Built-in mic (-A) · 3.6 mm fixed lens (2.8 mm optional) · IP67, 12V±30% DC	33,900,000
30	DH-HAC-HDW1500TMQP-A	5MP Starlight HDCVI PoC IR Quick-to-install Eyeball Camera > Max 25 fps@5MP (16:9 video output) > CVI/CVBS/AHD/TVI switchable > Quick-to-install eyeball saves installation time > 3.6 mm fixed lens (2.8 mm, 6 mm optional) > Built-in mic > Max. IR length 60 m, Smart IR > IP67, PoC (only CVI)/12V±30% DC	31,000,000
31	DH-HAC-HDW1500TLMQP	5MP Starlight HDCVI PoC IR Quick-to-install Eyeball Camera > Max 25 fps@5MP (16:9 video output) > CVI/CVBS/AHD/TVI switchable > Quick-to-install eyeball saves installation time > 3.6 mm fixed lens (2.8 mm, 6 mm optional) > Max. IR length 60 m Smart IR > IP67, PoC (only CVI)/12V±30% DC	26,901,000
32	DH-HAC-HDW1500EMP-A	Max. 20fps@5MP(2592*1944). Built-in mic. IP67, DC12V. HD and SD output switchable. 3.6mm fixed lens (2.8mm, 6mm optional). Max. IR length 50m, Smart IR	34,180,000
33	DH-HAC-HDW1231TQP-A	<2MP Starlight HDCVI Quick-to-install IR Eyeball Camera > Max 30 fps@1080P <(2.8 mm, 6 mm optional)Starlight, 130 dB true WDR, 3D NR> 3.6 mm fixed lens ,CVI/CVBS/AHD/TVI switchable> Super Adapt> Built-in mic> Max. IR length 40 m Smart IR> IP67, DC12V> Quick-to-install saves installation time	29,678,000
34	DH-HAC-HDW1239TP-A-LED	Full-color starlight. 40m LED distance. Max. 30fps@1080P. CVI/CVBS/AHD/TVI switchable. Built-in mic. 3.6mm fixed lens (2.8mm Optional). IP67, 12V±30% DC	30,520,000
35	DH-HAC-HDW1239TP-LED	Full-color starlight. 40m LED distance. Max. 30fps@1080P. CVI/CVBS/AHD/TVI switchable. 3.6mm fixed lens (2.8mm Optional). IP67, 12V±30% DC	29,050,000
36	DH-HAC-HDW1230EMP-A	2MP Starlight HDCVI IR Eyeball Camera. Max. 30fps@1080P. HD and SD output switchable. Built-in mic. 3.6mm fixed lens (2.8mm, 6mm optional). Max. IR length 50m, Smart IR. IP67, DC12V	23,810,000
37	DH-HAC-HDW1230TLP-A	2MP Starlight HDCVI IR Eyeball Camera. Max. 30fps@1080P. HD and SD output . switchable. 3.6mm fixed lens (2.8mm, 6mm optional). Max. IR length 40m, Smart IR IP67, DC12V, Built in Mic	26,840,000
38	DH-HAC-HDW1209TLQP-A-LED	2MP Full-color Starlight HDCVI Eyeball Camera > Full-color starlight > 20 m <illumination distance> Max. 30fps @ 1080P > CVI / CVBS / AHD / TVI switchable Fixed lens (2.8 mm; 3.6 mm optional) > IP67, 12V ± 30% DC	17,314,000
39	DH-HAC-HDW1209TLQP-LED	2MP Full-color Starlight HDCVI Eyeball Camera . Full-color starlight. 20 m . illumination distance. Max. 30fps @ 1080P. CVI / CVBS / AHD / TVI switchable. Fixed lens (2.8 mm; 3.6 mm optional). IP67, 12V ± 30% DC	16,642,000
40	DH-HAC-ME1200EQP-L	2MP HDCVI Active Deterrence Camera. * The parameters and datasheets below can only be applied to 1200-SS series. . Max 30 fps@1080p, CVI/CVBS/AHD/TVI switchable. Active deterrence with warm light. Built-in PIR, 10 m/110' detecting range/angle. Quick-to-install eyeball save installation time. 3.6 mm fixed lens (2.8	21,608,500
41	DH-HAC-HDW1200EMP-A	2MP HDCVI IR Eyeball Camera. Max 30fps@1080P(1920*1080). HD and SD output . switchable. 3.6mm fixed lens (2.8mm, 6mm optional). Max. IR length 50m, Smart IR IP67, DC12V. Built in mic	18,891,800
42	DH-HAC-HDBW1200EP	2MP HDCVI IR Dome Camera. Max 30fps@1080P · IP67, IK10, DC12V · HD and SD · output switchable · 3.6mm fixed lens (2.8mm optional) · Max. IR length 30m, Smart IR	21,340,000

43	DH-HAC-HDW1200MP	2MP HDCVI IR Eyeball Camera- Max 30fps@1080P(1920*1080)- HD and SD output . · switchable- 3.6mm fixed lens (2.8mm, 6mm optional)- Max. IR length 30m, Smart IR IP67, DC12V	15,648,400
44	DH-HAC-HDW1200RP	2MP HDCVI IR Eyeball Camera- Max 30fps@1080p(1920*1080)- HD and SD output . switchable- 3.6mm fixed lens (2.8mm optional)- Max. IR length 20m, Smart IR · DC12V	12,920,000
45	DH-HAC-ME1200EP-LED	2MP HDCVI Active Deterrence Camera · Max . ·30fps@1080P- HD and SD output switchable- 2.8mm/3.6mm fixed lens 10m/110' detecting range/angle- Max. IR length 20m, Smart IR- IP67, DC12V	22,930,000
46	DH-HAC-HUM3201BP-P	2MP Starlight HDCVI Pinhole Camera > Starlight, 120dB true WDR, 3DNR> Max <30fp@1080P> HD and SD output switchable> 2.8mm fixed lens> Audio in interface DC12V	41,600,000
47	DH-HAC-ME1500CP	5MP HDCVI Active Deterrence Camera> Max 20fps@5MP> HD and SD output <switchable> 2.8mm fixed lens (3.6mm optional)> Max. IR length 20m, Smart IR & Built-in PIR, 14:1m/110' detecting range/angle > Active deterrence with white light siren> IP67, DC12V	32,520,000
48	DH-HAC-B2A51P	5MP HDCVI IR Bullet Camera- Max. 20fps@5MP(2592*1944)- HD and SD output . · switchable- 3.6mm fixed lens (2.8mm,6mm optional)- Max. IR length 20m, Smart IR IP67, DC12V	21,358,000
49	DH-HAC-B2A21P	2MP HDCVI IR Bullet Camera- Max. 30fps@1080P (1920*1080)- HD and SD output . ,switchable- 3.6mm fixed lens (6mm optional)- Max. IR length 20m, Smart IR . IP67 DC12V	13,250,000
50	DH-HAC-B1A21P	2MP HDCVI IR Bullet Camera- Max. 30fps@1080P (1920*1080)- HD and SD output . .switchable- 3.6mm fixed lens (2.8mm, 6mm optional)- Max. IR length 20m, Smart IR IP67, DC12V	11,590,000
51	DH-HAC-T2A51P	5MP HDCVI IR Eyeball Camera- Max. 20fps@5MP (2592*1944)- HD and SD output . .switchable- 3.6mm fixed lens (2.8mm,6mm optional)- Max. IR length 20m, Smart IR IP67, DC12V	22,370,000
52	DH-HAC-T2A21P	2MP HDCVI IR Eyeball Camera- Max. 30fps@1080P (1920*1080)- HD and SD output . · switchable · 3.6mm fixed lens (2.8mm,6mm optional)- Max. IR length 20m, Smart IR IP67, DC12V	13,558,200
53	DH-HAC-T1A51P	< (16:9 video output)5MP HDCVI Fixed IR Eyeball Camera> Max. 25 fps@5MP CVI/CVBS/AHD/TVI switchable> 3.6 mm fixed lens (2.8 mm optional)> Max. IR length m, Smart IR> DC12V 20	19,558,000
54	DH-HAC-T1A21P	2MP HDCVI IR Eyeball Camera- Max. 30fps@1080P (1920*1080)- HD and SD output . .switchable- 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 20m, Smart IR DC12V	12,070,000
55	DH-SD59430I-HC	4Megapixel CMOS- Powerful 30x optical zoom- 120dB true WDR, 3D DNR- Max 1/3 · 25/30fps@4M/1080P, 25/30/50/60fps@720P · IR distance up to 100m · IP66	410,460,000
56	DH-SD59230I-HC	2Megapixel STARVIS™ CMOS- Powerful 30x optical zoom- Starlight 1/2.8 · technology- 120dB true WDR, 3D DNR- Max. 25/30fps@1080P, 25/30/50/60fps@720P IR distance up to 150m · IP66 ·	305,380,000
57	DH-XVR5432L-I2	·Channel Penta-brid 5M-N/1080P 1.5U WizSense Digital Video Recorder 32. H.265+/H.265 dual-stream video compression. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 (analog channel)Mbps incoming bandwidth. Up to 2 channels video stream ·perimeter protection. Up to 16 channels video stream (analog channel) SMD plus Up to 2 channels video stream (analog channel) human face recognition. IoT & POS functionalities	394,660,000

58	DH-XVR5232AN-I3	<p>. Channel Penta-brid 5M-N/1080P1U 2HDDs WizSense Digital Video Recorder 32. H.265+/H.265 dual-stream video compression. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 32 channels IP camera inputs, each channel up to 6MP; Max 128 (analog channel)Mbps incoming bandwidth. Up to 2 channels video stream</p> <p>.Perimeter Protection. Up to 16 channels video stream (analog channel) SMD Plus Up to 2 channels video stream (analog channel) human face recognition. IoT & POS functionalities</p>	270,150,000
59	DH-XVR5216AN-4KL-I3	<p>Channel Penta-brid 4K-N/5MP1U 2HDDs WizSense Digital Video Recorder 16 H.265+/H.265 dual-stream video compression- Supports HDCVI/AHD/TVI/CVBS/IP video inputs- Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 (analog channel)Mbps incoming bandwidth- Up to 2 channels video stream</p> <p>.Perimeter Protection- Up to 16 channels video stream (analog channel) SMD Plus Up to 2 channels video stream (analog channel) human face recognition- IoT & POS functionalities</p>	249,340,000
60	DH-XVR5216AN-4KL-S2	<p>Channel Penta-brid 4K-N/5MP1U 2HDDs WizSense Digital Video Recorder 16 H.264+/H.264 dual-stream video compression- Supports HDCVI/AHD/TVI/CVBS/IP video inputs- Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 (analog channel)Mbps incoming bandwidth- Up to 2 channels video stream</p> <p>.Perimeter Protection- Up to 16 channels video stream (analog channel) SMD Plus Up to 2 channels video stream (analog channel) human face recognition- IoT & POS functionalities</p>	234,480,000
61	DH-XVR5216AN-I3	<p>. Channel Penta-brid 5M-N/1080P1U 2HDDs WizSense Digital Video Recorder 16. H.265+/H.265 dual-stream video compression. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 24 channels IP camera inputs, each channel up to 6MP; Max 128 (analog channel)Mbps incoming bandwidth. Up to 2 channels video stream</p> <p>.Perimeter Protection. Up to 16 channels video stream (analog channel) SMD Plus Up to 2 channels video stream (analog channel) human face recognition IoT & POS functionalities</p>	158,210,000
62	DH-XVR5116H-I3	<p>H.265+/H.265 dual-stream video compression- Supports HDCVI/AHD/TVI/CVBS/IP video inputs- Max 24 channels IP camera inputs, each channel up to 6MP; Max 128 (analog channel)Mbps incoming bandwidth- Up to 2 channels video stream</p> <p>.Perimeter Protection- Up to 16 channels video stream (analog channel) SMD Plus Up to 2 channels video stream (analog channel) human face recognition · IoT & POS functionalities</p>	124,950,000
63	DH-XVR5116HS-I3	<p>Channel Penta-brid 5M-N/1080P Compact 1U 1HDD WizSense Digital Video 16 Recorder> H.265+/H.265 dual-stream video compression> Supports Full-channel AI Coding> Supports HDCVI/AHD/TVI/CVBS/IP video inputs> Max 24 channels IP camera inputs, each channel up to 6MP; Max 128Mbps incoming bandwidth> Up to 2 channels video stream (analog channel) Perimeter Protection> Up to 16 channels video stream (analog channel) SMD Plus> Up to 2 channels video stream (analog channel) human face recognition> IoT & POS functionalities</p>	126,770,000
64	DH-XVR5108HS-4KL-I3	<p>Channel Penta-brid 4K-N/5MP Compact 1U 1HDD WizSense Digital Video Recorder 8. H.265+/H.265 dual-stream video compression. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 16 channels IP camera inputs, each channel up to 8MP; Max 128 (analog channel)Mbps incoming bandwidth. Up to 2 channels video stream</p> <p>Perimeter Protection. Up to 8 channels video stream (analog channel) SMD Plus. Up to 2 channels video stream (analog channel) human face recognition. IoT & POS functionalities</p>	124,260,000
65	DH-XVR5108HS-I3	<p>Channel Penta-brid 5M-N/1080p Compact 1U 1HDD WizSense Digital Video 8. -Recorder. H.265+/H.265 dual-stream video compression. Supports Full-channel AI Coding. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 12 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps incoming bandwidth. Up to 1 channel video stream (analog channel) Perimeter Protection. Up to 8 channels video (analog channel)stream (analog channel) SMD Plus. Up to 1 channel video stream human face recognition. IoT & POS functionalities</p>	85,877,000
66	DH-XVR5104HS-4KL-I3	<p>Channel Penta-brid 4K-N/5MP Compact 1U 1HDD WizSense Digital Video Recorder 4. H.265+/H.265 dual-stream video compression. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 8 channels IP camera inputs, each channel up to 8MP; Max 64 (analog channel)Mbps incoming bandwidth. Up to 2 channels video stream</p> <p>Perimeter Protection. Up to 4 channels video stream (analog channel) SMD Plus. Up to 2 channels video stream (analog channel) human face recognition IoT & POS functionalities</p>	76,310,000

67	DH-XVR5104HS-I3	Channel Penta-brid 5M-N/1080p Compact 1U 1HDD WizSense Digital Video 4. -Recorder. H.265+/H.265 dual-stream video compression. Supports Full-channel AI Coding. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 6 channels IP camera inputs, each channel up to 6MP; Max 32 Mbps incoming bandwidth. Up to 1 channel video stream (analog channel) Perimeter Protection. Up to 4 channels video (analog channel)stream (analog channel) SMD Plus. Up to 1 channel video stream human face recognition. IoT & POS functionalities	52,087,560
68	DH-XVR4116HS-I	.Channel Penta-brid 720p Compact 1U 1HDD WizSense Digital Video Recorder 16. H.265+/H.265 video compression. Supports Full-channel AI-Coding. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 18 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps Incoming Bandwidth. Long transmission distance over coax cable. Up to 8 channels video stream (analog channel) SMD Plus	80,983,000
69	DH-XVR4108HS-I	Channel Penta-brid 1080N/720p Compact 1U 1HDD WizSense Digital Video 8. -Recorder. H.265+/H.265 dual-stream video compression. Supports Full-channel AI Coding. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 10 channels IP camera inputs, each channel up to 6MP; Max 32 Mbps incoming bandwidth. Up to 8 channels video stream (analog channel) SMD Plus	58,719,000
70	DH-XVR4104HS-I	Channel Penta-brid 1080N/720p Compact 1U 1HDD WizSense Digital Video 4. -Recorder. H.265+/H.265 dual-stream video compression.Supports Full-channel AI Coding.Supports HDCVI/AHD/TVI/CVBS/IP video inputs.Max 5 channels IP camera inputs, each channel up to 2MP; Max 32 Mbps incoming bandwidth.Up to 4 channels video stream (analog channel) SMD Plus	46,380,000
71	DH-XVR1B16H	.Channel Penta-brid 4M-N/1080P Cooper 1U 1HDD Digital Video Recorder 16. H.265+/H.265 dual-stream video compression. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 24 channels IP camera inputs, each channel up to 6MP; Max .96Mbps incoming bandwidth. Long transmission distance over coax cable Supports 1 SATA HDD, up to 6TB. Smart Search and Intelligent Video System	89,060,000
72	DH-XVR1B16-I	.H.265+/H.265 dual-stream video compression- Supports Full-channel AI-Coding . ,Supports HDCVI/AHD/TVI/CVBS/IP video inputs- Max 18 channels IP camera inputs each channel up to 6MP; Max 64 Mbps Incoming Bandwidth- Long transmission distance over coax cable- Up to 8 channels video stream (analog channel) SMD Plus	77,580,000
73	DH-XVR1B08-I	Channel Penta-brid 1080N/720p Cooper 1U 1HDD WizSense Digital Video Recorder 8. .H.265+/H.265 dual-stream video compression. Supports Full channel AI-Coding . ,Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 10 channels IP camera inputs each channel up to 6MP; Max 40 Mbps incoming bandwidth. Up to 4 channels video stream (analog channel) SMD Plus	37,294,500
74	DH-XVR1A08	Channel Penta-brid 1080N/720P Cooper 1U- H.264 video compression- Supports 8 . HDCVI/AHD/TVI/CVBS/IP video inputs- Max 10 channels IP camera inputs, each channel up to 5MP; Max 40Mbps Incoming Bandwidth- Long transmission distance over coax cable- Supports 1 SATA HDD, up to 6TB	39,620,000
75	DH-XVR1B04-I	Channel Penta-brid 1080N/720p Cooper 1U 1HDD WizSense Digital Video Recorder 4. .H.265+/H.265 dual-stream video compression. Supports Full channel AI-Coding . ,Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 5 channels IP camera inputs each channel up to 2MP; Max 20 Mbps incoming bandwidth. Up to 4 channels video stream (analog channel) SMD Plus	30,072,500
76	DH-XVR1A04	4Channel Penta-brid 1080N/720P Cooper 1U- H.264 video compression- Supports . HDCVI/AHD/TVI/CVBS/IP video inputs- Max 5channels IP camera inputs, each channel up to 2MP; Max 20Mbps Incoming Bandwidth- Long transmission distance over coax cable- Supports 1 SATA HDD, up to 6TB	30,050,000

IP Price List

1	PSD81602-A360	8x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Eight 2Megapixel progressive scan CMOS 5mm fixed lensPTZ: One 1/1.9" 2Megapixel "1/1.9 progressive scan CMOS 5.5mm-206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding ,2x25fps@4096x1800+50/60fps@1080PSupport 360-degree panoramic viewWDR Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLCsmart tracking, Intelligent Function(Tripwire, Intrusion)2/1 channel Audio In/Out, 7/2 channel Alarm In/OutRS485, Micro SD memory, IP67, IK10	Call
2	PSD8802-A180	4x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Four 2Megapixel progressive scan CMOS 5mm fixed lensPTZ: One 1/1.9" 2Megapixel "1/1.9 progressive scan CMOS 5.5mm-206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding ,25fps@4096x1800+50/60fps@1080PSupport 180-degree panoramic viewWDR Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLCsmart tracking, Intelligent Function(Tripwire, Intrusion)2/1 channel Audio In/Out, 7/2 channel Alarm In/OutRS485, Micro SD memory, IP67, IK10	Call
3	PFW8800-A180	4x2MP Multi-Sensor Panoramic Network IR Bullet CameraFour 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encodingMax 25fps@4096x1800, 3.0mm fixed lensSupport180-degree panoramic viewDWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLCIntelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/2 channel Alarm In/OutMax. IR LEDs length 30m, Micro SD +memory, IP67, IK10, PoE	Call
4	PFW8601-A180	3x2MP Multi-Sensor Panoramic Network IR Bullet CameraThree 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encodingMax 25fps@4096x832, 3.6mm fixed lens, Support 180-degree panoramic ,viewWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLCIntelligent Function Tripwire Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/1 +channel Alarm In/OutMax. IR LEDs length 30m, Micro SD memory, IP67, IK10, PoE	Call
5	PDBW8800-A180	4x2MP Multi-Sensor Panoramic Network IR Dome CameraFour 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264Max ,25fps@4096x1800, 3.0mm fixed lensSupport 180-degree panoramic viewDWDR ,Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLCIntelligent Function Tripwire, Intrusion Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/1 channel +Alarm In/OutMax. IR LEDs length 30m, Micro SD memory, IP67, IK10, PoE	Call
6	ITC237-PWIB-IRZ	Megapixel Full HD WDR Access ANPR Camera-Embedded with LPR 2 ١٠٠% algorithm inside the camera- plate cutout, snapshot preview, recording-White list database,1 ch relay out to control the barrier performance for outdoor applications-1/2.8" 2Megapixel progressive scan CMOS , (1920x1080)H.265/H.264M/H.264H/H.264B dual-stream encoding 25/30fps@1080P 2.7mm-12mm Motorize lens WDR(140dB),BLC,HLC,Day/Night(ICR),3DNR,AWB,AGC,BLC Mirco SD card 64GB, IR Distance 3-8m IP67 IK10 PoE	1 65,000,000
7	IPC5831EP-ZE	Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 8 "1/2.5 Triple-stream encoding 15fps@4K (3840x2160),25/30fps@3Mp(2304x1296)2.7mm ,12mm motorized lens, Max. Aperture F1.6WDR, Day/Night(ICR), 3DNR, AWB, AGC-BLCMicro SD card memory , 128 GB, 1/1 Audio In/Out, 2/1 Alarm In/Out Max. IR LEDs Length 50m , Smart IR, IP67,IK10, PoE (Tripwire Intrusion Object (Abandoned/Missing Face	12,400,000
8	IPC-HFW2831T-ZAS-S2	8MP Lite IR Vari-focal Bullet Network Camera8MP, 1/2.7" Progressive CMOSLow -illumination 0.008 Lux@F1.5high image definition 8MP@15fps & 4MP@25/30fps2.7 ,13.5mm Motorized LensSMART H.264+/H.265+, (MJPEG in Sub Stream) VS Intrusion ,TripwireMicro SD 256GB, 1ch Audio I/O, 1ch Alarm I/OWDR (120db), 3D DNR, HLC BLC, AWB, AGC, Roi, Smart illumination, Day/Night ICR Auto Switch12V, PoE, IP67, 4 IR LEDs 60m Distance, Onvif Profile S/C/T	99,000,000
9	HFW2831T-ZS-S2	8MP Lite IR Vari-focal Starlight Bullet Network Camera1/2.7" progressive scan CMOS image sensor, low illumination, high image definitionSmart H.265/H.264 ,codec, MJPEG, high compression rate, ultra-low bit rate8MP (3840 x 2160) @15 fps ,fpsWDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC 25/30@1520x2688 Region of Interest, Voltage Detection 2.7 mm-13.5 mm Motorized fixed lensMax. IR LEDs Length 60m, Micro SD card memory , 256 GBIP67, PoE, Smart Detection (Tripwire Intrusion)	98,000,000

10	IPC-HFW2831TP-AS-S2	<p>8MP Lite IR Fixed-focal Bullet Network Camera 8MP, 1/2.7" CMOS image sensor max 8MP (3840 x 2160) @15 fps, and supports 2688x1520 (2688 x 1520) @25/30 fps Smart H.265+/Smart H.264+, H.265; H.264; H.264B; MJPEG (only supported by the sub stream) Built-in IR LED, max IR distance: 80m, 3.6mm Fixed Lenz Min. Illumination ;Lux@F2.0 ONVIF (Profile S/Profile G/Profile T); CGI; Milestone 0.009 ;Genetec WDR(120db), 3D NR, HLC, BLC, AGC, AWB, ROI, Smart IR Intrusion tripwire Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 GB Micro SD card 12V DC/PoE power support supply, IP67, IK10</p>	73,000,000
11	IPC-HFW2831S-S-S2	<p>8MP Lite IR Fixed-focal Bullet Network Camera 1/2.7" Progressive CMOS image sensor, low illuminance, high image definition Illumination 0.009 Lux@F2.0 SMART (3840 x 2160) H.264+/H.265+, MJPEG, high compression rate, ultra-low bit rate 8MP ,fps, and supports 2688x1520 (2688 x 1520) @25/30 fps WDR (120 db), 3D DNR 15@ HLC, BLC, AGC, AWB, ROI, Smart IR Intrusion, tripwire, SD Card 256GB, IP67, PoE</p>	67,000,000
12	IPC-HFW1830SP-0360B-S6	<p>8MP 8MP 1/2.7" CMOS Entry IR Fixed-focal Bullet Network Camera Outputs max 8MP@15fps, supports 2688 x 1520 (2688 x 1520) @25/30 fps Illumination 0.004 Lux@F2.0 (B/W, 30 IRE) H.265+&H.264+ high compression rate, and ultra-low bit ,rate. WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Built-in MIC 3.6mm fixed lens Built-in IR LED, and the max. illumination distance is 30 m. 12 V DC/PoE power supply, IP67</p>	58,000,000
13	HFW2531TP-ZS	<p>5Megapixel progressive CMOS 2.7-13.5mm Motorized lens 1/2.7 -15fps@5M(2592x1944)&25/30fps@3M(2304x1296) H.265+/H.264+/H.264 dual stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Mirco SD card 128GB, Max IR LEDs Length 60m, Smart IR IP67, PoE, Smart Detection (Tripwire Intrusion)</p>	86,000,000
14	DH-IPC-HFW5449TI-ZE-LED	<p>4MP 1/1.8" CMOS image sensor, Full-color Vari-focal Warm LED Bullet WizMind Network Camera Outputs max. 4MP (2688 x 1520) @30 fps, Focal Length 2.7 mm-12 ,mm Min. Illumination 0.0005 Lux@F1.0 , S/N Ratio > 56 dB Built-in warm illuminator and the max. illumination distance : 70 m ROI, SMART H.264+/H.265+, flexible ;coding, WDR 140db, 3D NR, HLC, BLC IVS (Perimeter Protection) : Tripwire; intrusion fast moving, loitering detection, people gathering; parking detection, Face ;Detection, People Counting, Intelligent Search Alarm: 1 in, 1 out; audio: 1 in, 1 out supports max. 256 G Micro SD card, built-in Mic and speaker 12V DC/PoE power supply, ePoE, IP67 protection, SMD 3.0</p>	165,000,000
15	HFW5442EP-ZE-0832	<p>4MP Pro AI IR Vari-focal, WizMind 1/1.8" 4Megapixel progressive scan CMOS H.265, H.264, H.264B, H.264H, MJPEG triple-stream encoding Max , (140dB) 25/30fps@4Mp(2688x1520), 50/60fps@2Mp(1920 x 1080) WDR -Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, EIS, Defog, Region of Interest, 8mm , 32mm Motorized lens, Max. IR LEDs Length 50m, Smart IR, Micro SD card memory GBAudio in/Out 1/, Alarm In/Out 2/1 Smart Detection Tripwire, intrusion 128 ,, Object Abandoned / Missing, fast moving (Recognition of vehicle and people) loitering detection, parking detection and people gathering Support Line crossing/Region/Queueing people counting; Support 4 accesses independent detection, 4 areas independent detection, Scene Change, Heatmap, IP67, IK10, PoE</p>	1 40,000,000
16	IPC-HFW5241E-Z5E	<p>2MP IR Vari-focal Bullet WizMind Network Camera 2MP 1/2.8" Progressive Lux@F1.3 high image definition 0.0015 STARVIS™ CMOS low illuminance ;2MP@25/30fps 7-35mm Motorized Lens SMART H.264+/H.265+ IVS: Tripwire ;(with accurate classification of vehicle and human) intrusion; fast moving loitering detection; people gathering; parking detection Face Detection with Face Attributes and Face Expression People Counting with Queue Management Micro SD ,card 256 GB, 1ch Audio I/O, 2/1 Alarm I/O WDR (120db), EIS, Defog, 3D DNR, HLC, BLC AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, IK10, 4 IR LEDs 120m Distance, Onvif Profile S/G/T</p>	1 22,000,000
17	DH-IPC-HFW4431TP-S-S4	<p>4MP WDR IR Mini Bullet Network Camera 1/3" 4Megapixel progressive CMOS 3.6mm fixed lens 25/30fps@4Mp(2688x1520) H.265&H.264 triple-stream (Tripwire, Intrusion, Object Abandoned/Missing, Face detection) encoding IVS WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE</p>	55,200,000

18	DH-IPC-HFW3849TI-AS-PV-S3	8MP Smart Dual Illumination Active Deterrence Fixed-focal Bullet WizSense Network Camera 1/2.8" CMOS image sensor, low illuminance, high image definition Outputs max. 8 MP (3840 x 2160)@25/30 fps Min. Illumination 0.004 lux@F1.0 (Color, 30 IRE), 0.0004 lux@F1.0 (B/W, 30 IRE), 0 lux (illuminator on) Built-in warm light/IR LED, the max. illumination distance is 30 m ROI, SMART H.265+/H.264+/H.264, flexible coding, WDR, 3D NR, HLC, BLC, digital watermarking, Intrusion tripwire (support the classification and accurate detection of vehicle and human), Alarm: 1 in, 1 out; audio: 1 in, 1 out (optional) Supports max. 256G SD card; built-in dual MICs; 1-ch speaker 12 VDC/PoE power supply, IP67 protection, Sound and light alarm (red and blue lights) SMD 3.0. One click arming/disarming through alarm input	118,000,000
19	DH-IPC-HFW3449EP-AS-LED-3.6	4MP Full-color WDR IR Mini Bullet Network Camera 1/2.7" 4Megapixel progressive CMOS 3.6mm fixed lens 25/30fps@4Mp(2688x1520)H.265/Smart H.265+/H.264/Smart H.264+ triple-stream encoding IVS(Tripwire, Intrusion, Recognition of vehicle and people, SMD Plus) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE	66,300,000
20	DH-IPC-HFW3449EP-AS-LED-2.8	4MP Full-color WDR IR Mini Bullet Network Camera 1/2.7" 4Megapixel progressive CMOS 2.8mm fixed lens 25/30fps@4Mp(2688x1520)H.265/Smart H.265+/H.264/Smart H.264+ triple-stream encoding IVS(Tripwire, Intrusion, Recognition of vehicle and people, SMD Plus) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE	66,300,000
21	HFW3441TP-ZS-27135	4MP IR Vari-focal Bullet WizSense Network Camera 1/3" 4Megapixel progressive CMOS Min. Illumination: 0.005 Lux@F1.52.7 mm-13.5 mm Motorized lens 25/30fps@4Mp(2688x1520) SMART H.264+/H.265+ triple-stream encoding IVS(Tripwire; intrusion (Recognition of human and vehicle)) WDR Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE	93,000,000
22	DH-IPC-HFW2449S-S-IL	4MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera 4-MP CMOS image sensor, low luminance, and high definition image Outputs max. 4 MP (2688 x 1520)@20 fps, and supports 2560 x 1440 @25/30 fps H.265 codec, high compression rate, ultra-low bit rate Min. Illumination: 0.008 lux@F1.6 (Color, 30 IRE), 0.0008 lux@F1.6 (B/W, 30 IRE), 0 lux (illuminator on) Built-in warm light/IR LED, the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding, Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, Intrusion tripwire (support the classification and accurate detection of vehicle and human) Supports max. 256 G Micro SD card, built in MIC 12 VDC/PoE power supply, easy for installation, IP67 protection, SMD Plus	49,500,000
23	DH-IPC-HFW2441T-ZS	4MP IR Vari-focal Bullet WizSense Network Camera Outputs max. 4 MP (2688 x 1520)@20 fps, and supports 2560 x 1440 (2560 x 1440)@25/30 fps Min. Illumination 20@1520 (illuminator on) lux@F1.5 (Color, 30 IRE), 0.0008 lux@F1.5 (B/W, 30 IRE), 0 lux 0.008 H.265 codec, high compression rate, ultra-low bit rate, Focal Length 2.7 mm-13.5 mm Built-in IR LED, and the max. illumination distance is 60 m ROI, SMART H.264+/H.265+, flexible coding, WDR 120db, 3D NR, HLC, BLC Intrusion, tripwire, Alarm: 1 in (support the classification and accurate detection of vehicle and human), out (Only - ZAS supports), audio: 1 in, 1 out (Only - ZAS supports), 256G SD card 1 (optional) built in MIC 12 VDC/PoE power supply, easy for installation, IP67, IK10 protection, SMD Plus	84,000,000
24	IPC-HFW2439SP-SA-LED-0360B-S2	4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS slow illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps, 3.6mm Fixed lens SMART H.264+/H.265+, IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in MIC 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/C/T	46,200,000
25	HFW2431TP-AS-S2	4MP Lite IR Fixed-focal Bullet Network Camera 1/3" CMOS image sensor Outputs max. 4MP (2688 x 1520) @20 fps, and supports 2560x1440 (2560 x 1440) @25/30 fps, Built-in IR LED, max IR distance: 80 m, Intelligent detection: Intrusion, tripwire H.265; H.264; H.264B; MJPEG (only supported WDR(120 dB), 3D NR, HLC, BLC digital watermarking Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 GB Micro (optional) SD card 12V DC/POE, IP67 protection, IK10 protection	56,500,000

26	HFW2431TP-ZS-S2	4MP WDR IR Bullet Network Camera1/3" 4MP image sensorSMART H.264/H.265 dual .stream encoding4MP (2688 × 1520)@20 fps,2560 × 1440 @25fpsMin ,120dB)Illumination:0.008 Lux@F1.5, 2.7-13.5 mm Motorized lens WDR Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection ,Micro SD memory 256 GB, max IR distance:60 m, Smart IR, IP67(Tripwire Intrusion) PoE	73,500,000
27	IPC-HFW1431SI-S4-S5	4MP Entry IR Fixed-focal Bullet Network Camera4MP, 1/3" Progressive CMOSlow ,illumination 0.03 Lux @ F2.0high image definition 4MP@25/30fps3.6mm fixed lens Smart H.265+/H.264+WDR(120db), Roi, BLC, HLC, 3D DNR, AWB, AGC, Day/Night Auto ICR, Smart Illumination 12V, PoE, IP67, 1 IR LEDs 30m Distance, ONVIF (Profile S/Profile G/Profile T	31,500,000
28	HFW1431SP-0360B-S4	4MP Entry IR Fixed-focal Bullet Network Camera 1/3"4Megapixel progressive × CMOSSMART H.264/H.265 dual stream encoding4MP (2688 × 1520)@20 fps,2560 ,120dB)25fpsMin. Illumination:0.03 Lux@F2.0, 3.6 Fixed lensWDR@ 1440 ,Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance:30 m, Smart IR IP67, PoE	37,000,000
29	HFW3541EP-AS	5MP IR Fixed focal Bullet WizSense Network Camera1/2.7" CMOS image sensor,Outputs max. 5MP (2592 × 1944) @20 fps H.265 codecSMART H.264+/H.265+WDR(120db), 3D DNR, HLC, BLC, digital watermarking,Min Illumination 0.0005 Lux@F1.6 (B/W, 30IRE)12V DC/POE IP67 SMD Plus Supports max. 256 G Micro SD card, built-in Mic	Call
30	IPC-HFW3549TIP-AS-PV	.MP 1/2.7" CMOS image sensor, low luminance, Smart Dual IlluminationMin-5 Illumination : 0.003 lux@F1.0 (Color, 30 IRE) / 0.0003 lux@F1.0 (B/W, 30 IRE) / 0 lux , Lens Fixed-focal 3.6 mm , 15.6 m Recognize & 7.8 m Identify(Illuminator on) , Illumination Distance : 30 m (2 IR LED) / 30 m (2 warm light)AI H.265, AI H.264 Smart H.265+, Smart H.264+, Built-in MICMain stream: 2880 × 1620 or 2960 × 1668 20fps / 2688 × 1520 @(30 fps)WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Roi(4@ years), Smart Illumination, Defog, Scene Self-adaption Storage : FTP, SFTP, Micro , SD card (support max. 256 G), NAS ROM : 128MB, RAM : 512MB, S/N Ratio > 56db Sound and Light Alarm,Active Deterrence, IVS (Tripwire, intrusion), SMD 4.0, Smart , (10/100 Base-T)Search, Quick Pick, AI SSA Audio In/out : 1/1 , Alarm in/out : 1/1, RJ-45 W (12 VDC); 4.4 W (PoE), IP67 3.3	99,500,000
31	HFW3549EP-AS-LED-0360B	"5MP Full-color Fixed-focal Warm LED Bullet WizSense Network Camera5MP,1/2.7 ,CMOS image sensorlow illumination 0.003 Lux@F1.05MP@20 fps, 4MP@25/30 fps 3.6mm Fixed lensSMART H.264+/H.265+, IVS Intrusion/TripwireWDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Roi, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic12V, PoE, IP67, Built-in warm light, max. illumination distance: 30 m, Onvif Profile S/C/T	73,500,000
32	IPC-HFW3541TP-ZS-27135	5MP IR Vari-focal Bullet WizSense Network Camera5MP,1/2.7" Progressive CMOS0.005 Lux@F1.5 (Color, 30IRE), 0.0005 Lux@F1.5 (B/W, 30IRE), 0 Lux high image definition 5MP@20fps2.7-13.5mm Motorized(Illuminator on) LensSMART H.264+/H.265+ 3 StreamsIVS Intrusion, Tripwire, Accurate ,Human/Vehicle Classification, SMD PlusMicro SD 256GBWDR (120db), 3D DNR, HLC BLC, AWB, AGC, Roi, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 4 IR LEDs 60m Distance, Onvif Profile S/C/T	1 11,000,000
33	IPC-HFW2531TP-AS-S2	5MP Lite IR Fixed-focal Bullet Network Camera5MP,1/2.7" Progressive CMOSlow illumination 0.008 Lux@F1.6high image definition 5MP@20fps, 3.6mm fixed LensSMART H.264+/H.265+, IVS Intrusion/Tripwire1ch Alarm I/O, 1ch Audio I/O, Micro ,SD 256GBWDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Roi, Smart Illumination Day/Night ICR Auto Switch 12V, PoE, IP67, IK10, IR LED 80m Distance, Onvif Profile S/C/T	64,800,000
34	HFW2431SP-S-S2	4MP WDR IR Bullet Network Camera1/3" 4MP image sensorSMART H.264/H.265 dual .stream encoding4MP (2688 × 1520)@20 fps,2560 × 1440 @25fpsMin ,illumination:0.008 Lux@F1.6, 3.6mm Fixed lensWDR(120dB), Day/Night(ICR), 3DNR AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion)Micro SD memory GB, max IR distance: 30 m, Smart IR, IP67, PoE 256	42,500,000
35	HFW2249SP-S-IL-0360B	2MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera2-MP CMOS image sensor, low luminance, 0.0002 lux@F1.6 (B/W, 30 IRE)Outputs *1/2.8 ,+max. 2 MP (1920 × 1080)@25/30 fps, Fixed Lens 3.6mmSmart H.265+, Smart H.264 ,H.264H, H.265, H.264,Built-in warm light/IR LED : 30m/30mROI, WDR, 3D NR HLC, BLC, digital watermarkingSMD Plus, Intrusion, tripwire (two functions ,supported : detection of vehicle and human) Supports max. 256 G Micro SD card built in MIC.12 VDC/PoE power supply, easy for installation, IP67	41,000,000

36	HFW2249SP-S-IL-0280B	2MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera2-MP CMOS image sensor, low luminance, 0.0002 lux@F1.6 (B/W, 30 IRE)Outputs ~1/2.8 ,+max. 2 MP (1920 × 1080)@25/30 fps, Fixed Lens 2.8mmSmart H.265+, Smart H.264 ,H.264H, H.265, H.264, H.264BBuilt-in warm light/IR LED : 30m/30mROI, WDR, 3D NR HLC, BLC, digital watermarkingSMD Plus, Intrusion, tripwire (two functions ,supported : detection of vehicle and human) Supports max. 256 G Micro SD card built in MIC.12 VDC/PoE power supply, easy for installation, IP67	41,000,000
37	HFW2231SP-S-0360B-S2	2MP WDR IR Bullet Network Camera, starlight1/2.8" 2Megapixel progressive ,CMOSMin. Illumination:0.002 Lux@F1.6Outputs max. 2MP (1920 × 1080) @25/30 fps ,3.6mm Fixed lensSMART H.264/H.265 dual-stream encoding, IVS(Tripwire intrusion)WDR(120dB), Day/Night(ICR), 3DNR, AWB, ACC, BLC, HLC, Roi Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE	31,000,000
38	HFW2230SP-S	2MP IR Bullet Network Camera1/2.7" CMOS image sensor, low illumination, high image definition H.265+/H.265/H.264+/H.264 Double-stream encoding ,25/30fps@1080P(1920×1080)DWDR, Day/Night(ICR), 3DNR, AWB, ACC, BLC, HLC ,ROI3.6mm, Max. IR LEDs Length 30m, Smart IRMicro SD card memory 128 GB, IP67 (Tripwire Intrusion)PoE, AVI	30,000,000
39	IPC-HFW2239SP-SA-LED-S2	2MP Lite Full-color Fixed-focal Bullet Network Camera1/2.8" CMOS image ,+sensor,Outputs max. 2MP (1920 × 1080) @25/30 fps ROI, SMART H.264+/H.265 ,flexible coding,Min Illumination 0.0017 Lux@F1.0Intelligent detection: Intrusion tripwireWDR(120db), 3D NR, HLC, BLC, digital watermarkingSupports max. 256 GB Micro SD card and built-in Mic,12V DC/PoE ,IP67	37,500,000
40	IPC-HFW2231T-ZS-S2	2MP Lite IR Vari-focal Bullet Network Camera2MP, 1/2.8" Progressive CMOS, low illuminance 0.002 Lux@F1.5high image definition 2MP@25/30fps, 2.7-13.5mm Motorized Lens, SMART H.264+/H.265+ IVS Intrusion, Tripwire, Micro SD card 256 GBWDR(120db), Roi, BLC, HLC, 3D DNR, AWB, ACC, Day/Night Auto ICR, Smart Illumination 12V, PoE, IP67, IK10, 4 IR LEDs 60m Distance, Onvif Profile S/G/T	65,000,000
41	HFWI530SP-0360B-S6	5MP 1/2.7" CMOS image sensorOutputs max. 5MP (2880 × 1620) @20 fps,Fixed-focal 3.6mm min illumination 0.003 Lux@F2.0 (B/W, 30 IRE)H.265 codec, SMART H.264 ,H.265+, Built-in IR LED, and the max. illumination distance is 30 m Rotation mode/+ DWDR, 3D NR, HLC, BLC, digital watermarking Built-in MIC, IP67,POE	39,800,000
42	DH-IPC-HFW1239S1-LED-S5	2MP Lite Full-color Fixed-focal Bullet Network Camera2MP, 1/2.8" Progressive CMOslow illumination 0.005 Lux @F1.6high image definition 2MP@25/30fps3.6mm fixed lensSMART H.264+/H.265+DWDR/BLC/HLC/AWB/ACC/3D DNR/ROI, Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 15m Distance, Onvif Profile S/T	26,400,000
43	HFW1230TIP-ZS	2MP Entry, 1/2.8" CMOS image sensor, low luminance, and high definition image ,Outputs max. 2MP (1920 × 1080)@25/30 fps.Min. Illumination : 0.008 Lux@F1.7 (Color IRE), 0.0008 Lux@F1.7 (B/W, 30 IRE) Motorized vari-focal, 2.8 mm-12 mm, IR 30 ,Distance 50 m(2 IR)Smart H.265+, Smart H.264+, H.265 codec, high compression rate ultra-low bit rate. DWDR, 3D DNR, HLC, BLC, AWB, ACC, Roi(4 years), Smart ,(802.3af)Illumination, S/N Ratio > 56 dB 1 Port RJ-45 (10/100 Base-T), 12V DC/PoE IP67, Humidity ≤95%	52,000,000
44	HFW1230SIP-0360B-S5	2MP Entry IR Fixed-Focal Bullet Network Camera1/2.8" CMOS image sensor, low (1920 × 1080)illuminationFixed Lens 3.6mm, F2.0, Horizontal: 84° Outputs max. 2MP fpsSmart H.265+, Smart H.264+, H.265, H.264, H.264BONVIF (Profile S/Profile 25/30@ ,T)Built-in efficient IR illuminator, and the max. illumination distance is 30 m ROI DWDR, 3D NR, HLC, BLC, digital watermarking2V DC/PoE power supply, IP67	24,000,000
45	HFW1230SP-S4-S5	2MP Entry IR Fixed-focal Bullet Network Camera1/2.7" 2Megapixel progressive CMOSSMART H.264/H.265 dual stream encodingmax. 2MP (1920 × 1080p) @25/30 ,fpsMin. Illumination:0.01 Lux@F2.03.6 Fixed lensDWDR, Day/Night(ICR), 3DNR AWB, ACC, BLC, HLC, ROI max IR distance:30m, Smart IRIP67, PoE	27,000,000
45	HFW1230SP-S4-S5	2MP Entry IR Fixed-focal Bullet Network Camera1/2.7" 2Megapixel progressive CMOSSMART H.264/H.265 dual stream encodingmax. 2MP (1920 × 1080p) @25/30 ,fpsMin. Illumination:0.01 Lux@F2.03.6 Fixed lensDWDR, Day/Night(ICR), 3DNR AWB, ACC, BLC, HLC, ROI max IR distance:30m, Smart IRIP67, PoE	27,000,000

46	HDW4431EMP-AS-S4	4MP IR Eyeball Network Camera 1/3" 4Megapixel progressive CMOS 2.8mm fixed lens 25/30fps@4Mp(2688x1520)H.265&H.264 triple-stream encoding IVS(Tripwire, (Intrusion, Object Abandoned/Missing, Face detection) WDR(120dB Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Built-in Mic Micro SD memory 256GB Max IR LEDs Length 50m, Smart IR, IP67, PoE	48,000,000
47	HDBW3441EP-AS	4MP IR Fixed focal Dome WizSense Network Camera 1/3" CMOS image sensor Outputs max. 4MP (2688 x 1520)@30 fps H.265 codec, SMART H.264+/H.265+WDR(120db), 3D DNR, HLC, BLC, digital watermarking Supports max C Micro SD card, 12V DC/POE, IP67, IK10, SMD Plus Min Illumination 0.0005 256 Lux@F1.6 (B/W, 30IRE) Audio Input 1 channel (RCA port), Audio Output 1 channel Alarm Input 1 channel in, Alarm Output 1 channel out (RCA port)	57,000,000
48	HDW3441TMP-AS-0280B	4MP IR Fixed focal Eyeball WizSense Network Camera 1/3" 4Megapixel progressive CMOS Min. Illumination: 0.005 Lux@F1.6 2.8mm Motorized lens 25/30fps@4Mp(2688x1520) SMART H.264+/H.265+ triple-stream (120dB) encoding IVS(Tripwire; intrusion (Recognition of human and vehicle)) WDR Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Rol Built-in Mic, Micro SD memory 256GB Max. IR LEDs Length 50m, Smart IR, IP67, PoE	54,000,000
49	HDBW2831EP-S-S2	8Megapixel progressive CMOS Min. Illumination: 0.009 Lux@F2.0 3.6mm Fixed 1/2.7 Lens max. 8MP (3840 x 2160) @15 fps, 2688x1520 (2688 x 1520) @25/30 fps SMART H.264+/H.265+, flexible coding IVS(Tripwire; intrusion), Abnormality detection, Motion detection, video tampering WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC BLC, HLC, Rol Micro SD memory 256GB Built-in IR LED Max.Length 30m, IP67, PoE	69,500,000
50	HDBW2531RP-ZAS	5Megapixel progressive CMOS 2.7-13.5mm Motorized lens 1/2.7 -20fps@5M(2592x1944)&25/30fps@3M(2304x1296) H.265+/H.265/H.264 dual stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 1/1 Audio in/out, 1/1 Alarm in/out Micro SD card 128GB Max IR LEDs Length 30m, Smart IR IP67, IK10, PoE	86,000,000
51	IPC-HDBW2531E-S-S2	5MP Lite IR Fixed-focal Dome Network Camera 5MP, 1/2.7" Progressive CMOS Min illumination 0.008 Lux @ F1.6 Max 5MP@20fps SMART H.264+/H.265+ IVS: Intrusion, tripwire Micro SD card 256GB WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC HLC, Rol max IR distance: 30m, 12V DC, PoE, IP67, IK10	43,200,000
52	IPC-HDW2831TP-AS-S2	8MP Lite IR Fixed-focal Eyeball Network Camera 1/2.7" CMOS image sensor Outputs max. 8MP (3840 x 2160) @15 fps Min illumination 0.009 Lux@F2.0 Built-in IR LED, max IR distance: 30 m SMART H.264+/H.265+ WDR, 3D NR, HLC, BLC, digital watermarking Supports max. 256 GB Micro SD card, built-in MIC 12V DC/PoE, IP67	70,000,000
53	DH-IPC-HDW2449T-S-IL	4MP Smart Dual Illumination Fixed-focal Eyeball WizSense Network Camera Outputs max. 4 MP (2688 x 1520)@20 fps, and supports 2560 x 1440 @25/30 (B/W, 30 IRE)fps Min. illumination : 0.008 lux@F1.6 (Color, 30 IRE), 0.0008 lux@F1.6 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate Built-in 0 warm light/IR LED, the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding, WDR, 3D NR, HLC, BLC, digital watermarking Intrusion, tripwire (support the classification and accurate detection of vehicle and human Supports max. 256 G Micro SD card; built in MIC, 12 VDC/PoE power supply, easy for installation, IP67 protection, SMD Plus	51,000,000
54	IPC-HDW2439TP-AS-LED-0360B	4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps 3.6mm Fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 2 Warmlight LED 30m Distance, Onvif Profile S/C/T	47,200,000
55	IPC-HDW2439TP-AS-LED-0280B-S2	4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps 2.8mm Fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 2 Warmlight LED 30m Distance, Onvif Profile S/C/T	47,200,000

56	DH-IPC-HDBW2441E-S	4MP 1/2.9" CMOS image sensor, IR Fixed-focal Dome WizSense Network CameraOutputs max. 4 MP (2688 × 1520)@20 fps, and supports 2566 × 1440@25/30 fpsMin. Illumination 0.008 lux@F1.6 (Color,30IRE), 0.0008 lux@F1.6 (B/W,30IRE), 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rateBuilt-in IR LED, and the max. illumination distance is 30 mROI, SMART H.264+/H.265+, flexible coding, WDR 120db, 3D NR, HLC, BLCIntrusion, tripwire (support the classification and accurate detection of vehicle and human) Supports max. 256 G Micro SD card ,built in MIC12 VDC/PoE power supply, easy for installation, IP67, IK10 protection SMD Plus	46,800,000
57	DH-IPC-HDBW2441R-ZS	4MP IR Vari-focal Dome WizSense Network Camera, 4-MP 1/2.9" CMOS image × sensorOutputs max. 4 MP (2688 × 1520)@20 fps and supports 2560 × 1440 , (2560 fps)Min. Illumination 0.008 lux@F1.5 (Color, 30 IRE) , 0.0008 lux@F1.5 25/30@(1440 , 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low(B/W, 30 IRE) bit rateBuilt-in IR LED, and the max. illumination distance : 40 m, ROI, SMART ,H.264+/H.265+WDR 120dB, 3D NR, HLC, BLC, Focal Length 2.7 mm-13.5 mmIntrusion tripwire (support the classification and accurate detection of vehicle and human)Alarm: 1 in, 1 out (Only - ZAS supports); audio: 1 in, 1 out (Only - ZAS ,supports); 256G SD card; built in MIC12 VDC/PoE power supply, easy for installation IP67 and IK10 protection, SMD Plus	79,500,000
58	HDBW2431RP-ZS-27135-S2	4MP WDR IR Dome Network Camera1/3" 4Megapixel progressive CMOSSMART .H.264/H.265 dual stream encoding4MP (2688 × 1520)@20 fps,2560 × 1440 @25fpsMin ,(120dB)Illumination:0.008 Lux@F1.52.7-13.5 mm Motorized lensWDR Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection Micro SD memory 256 GB1/ Audio in/out, 1/ Alarm in/outmax(Tripwire Intrusion) IR distance:40 m, Smart IRIP67, IK10, PoE	72,000,000
59	HDBW2431RP-ZAS-S2	4MP WDR IR Dome Network Camera1/3" 4Megapixel progressive CMOSSMART .H.264/H.265 dual stream encoding4MP (2688 × 1520)@20 fps,2560 × 1440 @25fpsMin ,(120dB)Illumination:0.008 Lux@F1.52.7-13.5 mm Motorized lensWDR Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection Micro SD memory 256 GB1/ Audio in/out, 1/ Alarm in/outmax(Tripwire Intrusion) IR distance:40 m, Smart IRIP67, IK10, PoE	73,000,000
60	HDBW2431EP-S-0360B-S2	4MP IR Mini Dome Network Camera1/3" 4Megapixel progressive CMOSSMART .H.264/H.265 dual stream encoding4MP (2688 × 1520)@20 fps,2560 × 1440 @25fpsMin ,Illumination:0.008 Lux @ F1.63.6 mm Fixed lensWDR(120dB), Day/Night(ICR), 3DNR AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion)Micro SD memory GBmax IR distance:30 m, Smart IRIP67, IK10, PoE 256	41,000,000
61	HDBW2431EP-S-0280B-S2	4MP IR Mini Dome Network Camera1/3" 4Megapixel progressive CMOSSMART .H.264/H.265 dual stream encoding4MP (2688 × 1520)@20 fps,2560 × 1440 @25fpsMin ,Illumination:0.008 Lux @ F1.62.6 mm Fixed lensWDR(120dB), Day/Night(ICR), 3DNR AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion)Micro SD memory GBmax IR distance:30 m, Smart IRIP67, IK10, PoE 256	41,000,000
62	HDW2431TP-AS-0280B-S2	4MP Lite IR Fixed-focal Eyeball Network Camera1/3" CMOS image sensor, Outputs 4MP (2560 × 1440)@25/30 fps H.265 coding, SMART H.264+/H.265+, Fixed Lens 2.8mmMin. Illumination 0.008 Lux @ F1.6 WDR(120db), 3D NR, HLC, BLC, digital watermarking,Intelligent detection: Intrusion, tripwire Max. 256 GB SD card and built-in Mic ,12V DC/POEIP67	43,200,000
63	HDW2431TMP-AS-0280B-S2	4MP WDR IR Eyeball Network Camera, Starlight1/3" 4Megapixel progressive × CMOSSMART H.264/H.265 dual stream encoding4MP (2688 × 1520)@20 fps,2560 ,(120dB)25fpsMin. Illumination:0.008 Lux@F1.62.8 mm Fixed lensWDR@ 1440 Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection ,Micro SD memory 256 GB, Built in Micmax IR distance:30 m(Tripwire Intrusion) Smart IRIP67, PoE	44,000,000
64	HDBW1431EP-0280B-S4	4MP Entry IR Fixed-focal Dome 1/3" CMOS image sensor Network, low illuminationMin. Illumination : 0.03 Lux @ F2.0 ,Illumination Distance : 30 m(3 IR /LED), S/N Ratio > 56db Lens Fixed-focal 2.8 mm , Horizontal: 93° / Vertical: 53° Diagonal: 111° Smart H.265+, H.265, Smart H.264+, H.264Main Stream: 2688 × 1520 (20 ,fps), high compression rate, ultra-low bit rateWDR (120db), 3D DNR, HLC, BLC, AWB : AGC, Roi(4 years), Smart IlluminationStorage(FTP, SFTP, NAS) , ROM :128MB, RAM -512MB12V DC/POE (802.3af), Power Consumption < 5.5W, 1 port RJ-45 (10/100 Base T) ,IP67, IK10	37,500,000

65	HDW1431TIP-A-0360B-S4	4MP Entry IR Fixed-focal Eyeball Network Camera 1/3"4 Megapixel progressive CMOS (2560x1440) Fixed-focal 3.6mm 20fps@4M (2688x1520) & 25fps@4M (ICR) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR (120dB), Day/Night Image flip, 3D DNR, HLC, BLC, digital watermark Support ROI, Built-in MICMax. IR LEDs Length 30m, IP67, PoE	37,200,000
66	HDW1431TIP-0280B-S4-S5	4MP Entry IR Fixed-focal Eyeball Network Camera 1/3"4 Megapixel progressive CMOS -20fps@4M (2688x1520) & 25fps@4M (2560x1440) H.265+/H.265/H.264+/H.264 dual stream encoding WDR (120dB), Day/Night (ICR), 3DNR, AWB, AGC, BLC, HLC Support ROI Max. IR LEDs Length 30m, IP67, PoE	34,000,000
67	DH-IPC-HDW2249TP-S-IL-0280B	2MP Smart Dual Illumination Fixed-focal Eyeball WizSense Network Camera 2-MP CMOS image sensor, low luminance Min. illumination: 0.0002 lux@F1.6 (B/W 1/2.8 : IRE) , Fixed Lens 2.8 mm Outputs max. 2 MP (1920 x 1080) @25/30 fps Smart Codec 30 , Smart H.265+, Smart H.264+, H.264H, H.265, H.264, H.264B SMD Plus, Intrusion tripwire (accurate detection of vehicle and human). Supports max. 256G Micro SD card, built in MIC. ROI, WDR, 3D NR, HLC, BLC, digital watermarking Built-in warm light/IR LED : 30m/30m 12 VDC/PoE power supply, easy for installation, IP67	41,000,000
68	HDW2231TMP-AS-S2	2MP WDR IR Eyeball Network Camera, Starlight 1/2.8" 2Megapixel progressive CMOS Min. illumination: 0.002 Lux@F1.6 Outputs max. 2MP (1920 x 1080) @25/30 fps 2.8mm Fixed lens SMART H.264/H.265 dual-stream encoding IVS (Tripwire , intrusion) WDR (120dB), Day/Night (ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Built-in Mic Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE	35,000,000
69	IPC-HDW2231TP-AS-0280B-S2	2MP Lite IR Fixed-focal Eyeball Network Starlight Camera 2MP, 1/2.8" Progressive CMOS Slow illumination 0.002 Lux @F1.6 high image definition 2MP@25/30fps 2.8mm , fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T	34,500,000
70	IPC-HDW2230T-AS-S2	2MP IR Eyeball Network Camera 2MP, 1/2.7" Progressive CMOS Slow illumination Lux @ F1.6 high image definition 2MP@25/30fps 2.8mm fixed lens SMART 0.005 , H.264+/H.265+ IVS Intrusion, Tripwire Micro SD 256GB, Built-in Mic DWDR, 3D DNR , HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T	30,000,000
71	IPC-HDBW2230E-S-S2	2MP Lite IR Fixed-focal Dome Network Camera 2MP, 1/2.7" Progressive CMOS Slow illumination 0.005 Lux @F1.6 high image definition 2MP@25/30fps 2.8mm Fixed , Lens SMART H.264+/H.265+ IVS Tripwire; intrusion Micro SD 256GB DWDR, 3D DNR , HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE IP67, 3 IR LEDs 30m Distance, Onvif Profile S/G/T	29,800,000
72	HDW1530TP-0280B-S6	5MP Entry IR Fixed-focal Eyeball Network Cam 1/2.7" CMOS image sensor low illumination 0.003 Lux @F2 Outputs max. 5MP (2880 x 1620) @20 H.265 code, SMART H.264 +/H.265 DWDR, 3D NR, HLC, BLC, digital watermarking Built-in MIC, 12 V DC/PoE power supply	40,500,000
73	DH-IPC-HDW1239TI-A-LED-S5	2MP Lite Full-color Fixed-focal Eyeball Network Camera Outputs max. 2MP (1920 .fps) H.265 codec, high compression rate, ultra-low bit rate Min 25/30@ (1080 illumination : 0.005 Lux @F1.6, Built-in LEDs, max LED distance: 15 m, built in , MICROI, SMART H.264/H.265, flexible coding, applicable to various Rotation mode DWDR, 3D DNR, HLC, BLC, digital watermarking, 12V DC/PoE power support, IP67 protection	29,500,000
74	DH-IPC-HDW1239TI-LED-0360B-S5	MP Entry Full-color Fixed-focal Bullet Network Camera 2MP, 1/2.8" Progressive 2 CMOS Slow illumination 0.005 Lux @F1.6 high image definition 2MP@25/30fps 3.6mm fixed lens Smart H.265+/Smart H.264+ DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/T	26,400,000
75	DH-IPC-HDW1239TIP-LED-0280B-S5	MP Entry Full-color Fixed-focal Bullet Network Camera 2MP, 1/2.8" Progressive 2 CMOS Slow illumination 0.005 Lux @F1.6 high image definition 2MP@25/30fps 2.8mm fixed lens Smart H.265+/Smart H.264+ DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/T	26,400,000
76	DH-IPC-HDW1230TI-A-S5	(1920 x 1080) 2MP Entry IR Fixed-Focal Eyeball Network Camera Outputs max. 2MP fps H.265 codec, high compression rate, ultra-low bit rate, Min. illumination 25/30@ Lux @F2.0 Built-in efficient IR illuminator, and the max. illumination distance 0.01 : is 30 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various, built in MIC Rotation mode, DWDR, 3D NR, HLC, BLC, S/N Ratio 56 dB, digital watermarking 12V DC/PoE power supply, IP67 protection	27,800,000

77	HDW1230TIP-0280B-S5	2MP Entry IR Fixed-Focal Eyeball Network Camera/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding max. 2MP (1920 x 1080p) @25/30 ,fps Min. Illumination:0.01 Lux@F2.0, 2.8 Fixed lens DWDR, Day/Night(ICR), 3DNR AWB, AGC, BLC, HLC, ROI, EIS max IR distance:30 m, Smart IR, IP67, PoE	24,000,000
78	HDBW1230EP-0360B-S2	2Megapixel progressive scan CMOS, 3.6mm fixed lens 1/2.7 H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920x1080)DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m, IP67, IK10, PoE	27,000,000
79	DH-SD29204T-GN	2MP CMOS Sensor, 2.7mm - 11mm, 4x Optical Zoom H.264+/H.264 1/2.7 Encoding Max. 25/30fps@1080P, 25/30/50/60fps@720PWDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 100' /s pan speed, 360' endless pan rotation Up to 300 ,presets, 5 auto scan, 8 tour, 5 pattern Built-in Mic, IR Distance up to 30m, POE (Tripwire Intrusion Scene Change Face Abandoned-Missing Object)	72,500,000
80	DH-SD1A203T-GN	2MP STARVIS™ CMOS (Starlight) H.265+/H.265/H.264+/H.264 Triple-streams 1/2.8 , (120dB) encoding Max. 25/30fps@1080P, 2.7mm - 8.1mm, 3x Optical Zoom WDR Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max Pan: 80' /s; Tilt: 40' /s speed Pan: 0' - 355'; Tilt: 5' - 90' rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern, Support Defog, IR Distance up to 15m, IP 66, support POE (Tripwire Intrusion Abandoned Missing Face Detection)	74,000,000
81	SD3A205-GNP-PV	2MP Starlight IR AI WizSense Network PTZ Camera H.265; H.264B; H.264M; H.264H MJPEG; MJPEG (Sub Stream); H.265+; H.264+ Focal Length 2.7 mm-13.5 mm, Optical Zoom 5x Tripwire and intrusion, Deep-learning-based perimeter protection SMD , Plus IR distance up to 30m Starlight technology Up to 300 presets DWDR, HLC, BLC AGC, AWB, 2D/3D DNR, Day/Night Auto (ICR), RoI, Defog Built-in Mic, Built-in ;Speaker, Two Way Audio ONVIF Profile S&G&T; CGI IP66; TVS 2000V lightning proof surge protection; voltage transient protection	96,500,000
82	DH-SD6CE230U-HNI	2MP STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Encoding Max 1/2.8 , 50/60fps@1080P 4.5mm-135mm Powerful 30x optical zoom Max 200' /s pan speed -endless pan rotation WDR(120db), Day/Night(ICR), Ultra DNR, BLC, HLC Auto 360' , (tracking, Tripwire, Intrusion, Abandoned/Missing, Face Detection, Heat Map Support Defog, ROI, EIS Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto , Pan Alarm 7/2 in/out, Audio 1/1 in/out, 1*Video output RS485, IR Distance up to 200m PoE+, IP67, IK10	3 40,000,000
83	DH-SD6CE245XA-HNR	2MP 45x Starlight IR WizSense Network PTZ Camera/2.8" 2Megapixel STARVIS CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Minimum , illumination: Color(0.005Lux@F1.6), B/W(0.0005Lux@F1.6) Max. 50/60fps@1080P ,(ICR) 3.95mm-177.7mm Focal Length 45x optical zoom WDR(120dB), Day/Night 2D/3D DNR, BLC, HLC, AGC, AWB Auto-tracking, Perimeter protection, Face detection, SMD Plus Tripwire and intrusion, alarm triggering by target types Support Defog, ROI Up to 300 presets, 8 tour, 5 pattern, Auto (human and vehicle) scan, Auto Pan 1*Video output, Rs485/2 Alarm in/out, 1/1 Audio in/out IR Distance up to 250m, PoE+, IP67, IK10	480,000,000
84	DH-SD6CE245U-HNI	2MP 45x Starlight IR PTZ Network Camera/2.8" 2Megapixel STARVIS CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Minimum , illumination: Color(0.005Lux@F1.6), B/W(0.0005Lux@F1.6) Max. 50/60fps@1080P 3.95mm-177.7mm Focal Length 45x optical zoom WDR(120dB), Day/Night(ICR), Ultra , DNR, BLC, HLC, AGC, AWB Auto-tracking and IVS (Tripwire Intrusion, Abandoned/Missing, Face Detection, Heat Map) Support Defog, ROI, EIS Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan 1*Video output, Rs485/2 Alarm in/out, 1/1 Audio in/out IR Distance up to 250m, PoE+, IP67, IK10	Call
85	SD5A245XA-HNR	2MP 45x Starlight IR WizSense Network PTZ Camera/2.8" 2Megapixel STARVIS CMOS H.265; H.265+; H.264+; H.264; MJPEG (Sub Stream) Max. 50/60 :fps@1080P Pan/Tilt Range Pan: 0'-360'; Tilt: -15'--90' Manual Control Speed Pan ,s-240' /s; Tilt: 0.1' /s-120' /s WDR(120db), HLC, BLC, 2D/3D DNR, RoI, EIS, Defog/0.1' ,AWB, AGC, Privacy Masking, Day/Night Auto Auto Tracking, SMD Plus, Intrusion Tripwire, Object Abandoned/Missing, Face Detection Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Alarm I/O 2/1, Audio I/O 1/1, Supports Two Way :Talk Focal Length 3.95 mm-177.7 mm, Min. Illumination Color: 0.005 Lux@F1.6 B/W Lux@F1.6 0 Lux (IR on) IR distance up to 150 m, 45x optical zoom ONVIF 0.0005 Profile S&G&T, DC 24V/2.5A ± 25%; PoE+ (802.3at), Operating Temperature -40°C to 70°C IP67; IK10; TVS 6000V lightning protection; surge protection; voltage+ transient protection	470,000,000

86	DH-SD5A232XB-HNR	™2MP 32x Starlight IR WizSense Network PTZ Camera/2.8" 2Megapixel STARVIS CMOS32x optical zoom,Max. 50/60 fps@2MMin Illumination Color: 0.005 ;+lux@F1.6,Focal Length 4.8 mm-154 mm Smart H.265+; H.265; Smart H.264 H.264BFace detection ,tracking and perimeter protection,SMD PLUS IR distance up to 150 m,PoE+, IP67, IK10WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC	407,000,000
87	DH-SD5A232XA-HNR	2Megapixel STARVIS™ CMOSH.265+/H.264+/H.264 Triple-streams™1/2.8 encodingMax. 50/60fps@1080P, 4.9mm-156mm 32x optical zoomMax 400°/s pan ,(2D/3D)speed, 360° endless pan rotationWDR(120dB), Day/Night(ICR), Ultra DNR ,BLC, HLCSupport Defog, ROI, Auto-tracking and IVS(Tripwire ,Intrusion,Abandoned/Missing, Face Detection) Up to 300 presets,8 tour, 5 pattern ,+Auto scan, Auto PanAlarm 2/I in/out, Audio 1/I in/outIR Distance up to 150m, PoE IP67, IK10	4 07,000,000
88	DH-SD49425ZB-HNR	4MP 25x Starlight IR WizSense Network PTZ Camera, Image Sensor:1/2.8" ,STARVIS™ CMOS1/2.8" 4Megapixel CMOS, Powerful 25x optical zoom, ROM: 4GB RAM: 1GBStarlight technology, Max.25/30fps@4M, Illuminator Number: 4Focal .Length: 4.8 mm-120 mm, Field of View: H: 60.0°-2.5°; V: 30.8°-2.2°; D: 66.7°-2.9° Min Illumination: Color: 0.005Lux@F1.6, B/W: 0.0005Lux@F1.6: 0Lux@F1.6 (IR light ,on)Illuminator On/Off Control: Zoom Prio/Manual/SmartIRPerimeter protection Face Detection, Smart Capture, SMD PLUS, IVS: Object Abandoned/Missing Support PoE+, IR distance up to 100m, BLC, WDR 120db, HLC, AGC, ANR, ROI, Electronic DefogPan: 0.1°-200°/s, Tilt: 0.1°-120°/s, Presets: 300, Tour: 8 (up to 32 presets per tour), Pattern: 5, Scan: 5 IP66, DC 12V/3A, PoE+ (802.3at) Audio Input: 1, Audio Output: 1, Alarm I/O: 2/I	267,000,000
89	SD49425XB-HNR	4MP 25x Starlight IR WizSense Network PTZ Camera/2.8" STARVIS™ Progressive ,CMOSH.265+/H.265/H.264+/H.264/MJPEG (sub stream)Max.25/30fps@4M, 960P 720P4.8mm-120mm 25x optical zoomMax 240°/s pan speed, 360° endless pan ,rotationWDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB AGC, Auto iris, Auto focus IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest) False Alarm Avoidance for Animals, Leaves, Bright LightSupport Defog and EISUp to 300 presets,8 tour, 5 ,+pattern, Auto scan, Auto PanBuilt-in 2/I Alarm in/out, Audio 1/I in/out, Support PoE	2 67,000,000
90	SD49225XA-HNR-S3	™2MP 25x Starlight IR WizSense Network PTZ Camera/2.8" 2Megapixel STARVIS CMOS, 25x optical zoom, Min Illumination Color: 0.005 lux@F1.6Max. 25/30 fps@1080pIR distance up to 100 m , Perimeter protection,Face detection,SMD :Plus,IP66Pan: 0° to 360° endless,Tilt: -15° to +90° , auto flip180° , Pan: 200°/s; Tilt s Smart H.265+; H.265; Smart H.264+; H.264B; H.264M; H.264H; MJPEG (Sub/100° Stream) Tripwire and intrusion. Support alarm triggering by target types (human ,and vehicle) WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC AWB, AGC	220,000,000
91	SD49225XA-HNR	™2MP 25x Starlight IR PTZ AI Network Camera/2.8" STARVIS ,CMOSH.265+/H.265/H.264+/H.264/MJPEG (sub stream)Max. 1-60fps@1080P,960P 720P4.8mm-120mm 25x optical zoomMax 240°/s pan speed, 360° endless pan ,rotationWDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB AGC, Auto iris, Auto focus IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest) False Alarm Avoidance for Animals, Leaves, Bright LightSupport Defog and EISUp to 300 presets,8 tour, 5 ,+pattern, Auto scan, Auto PanBuilt-in 2/I Alarm in/out, Audio 1/I in/out, Support PoE	2 20,000,000
92	SD49225ZB-HNR	2Megapixel STARVIS™ CMOSPowerful 25x optical zoom - Focal Length 4.8 "1/2.8 :mm-120 mmMax. 25/30 fps@1080p - Min. Illumination Color: 0.005 lux@F1.6 / B/W lux / 0 lux (IR light on)IVS (Perimeter Protection) : Tripwire , intrusion /SMD 0.0005 Plus / Face Detection / Motion Detection Smart H.265+; H.265; Smart H.264+WDR(120dB),DNR(2D/3D), BLC, HLC, AWB, AGC , Roi , Electronic DefogIR distance up to 100 m - Smart IR - 4 IR - S/N Ratio ≥ 55 dBPresets 300 / Tour 8 (up to 32 presets per tour) / Pattern 5 / Scan 50Alarm I/O : 2/I - IP66 - Power Supply 12 VDC, 3 A PoE+Storage : FTP/Micro SD card (512 GB)/NAS -	220,000,000

93	SD59430U-HNI	<p>CMOS Sensor H.265+/H.265/H.264+/H.264 Encoding, Ultra-low bit rateMax 71/3 25/30fps@4M(2592x1520) & 50/60fps @1080P resolutionWDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus4.5mm - 135.0mm , 30x Optical ZoomMax 400 's pan speed, 360 ' endless pan rotationUp to 300 presets, 5 auto scan, 8 tour, 5 patternMicro SD card memory , 64 GB Audio In/Out, Alarm In/Out, IP66, POE+IR Distance up to 100m(AC24V)/80m(DC12V)Smart Detection (Tripwire Intrusion Scene Change Face Anonedoned-Missing Object</p>	<p>3 50,000,000</p>
94	SD5A432XB-HNR	<p>4MP 32x Starlight IR WizSense Network PTZ Camera1/2.8" 4Megapixel STARVIS .Progressive CMOSH.265+, H.264+, H.265, H.264, MJPEG(Sub Stream) 3 Stream, Max 25/30fps@4MMin. Illumination Color: 0.005 Lux@F1.35, B/W: 0.0005 Lux@F1.6, 0 Lux 4.8 mm-154 mm Powerful 32x optical zoom, Max. Aperture F1.35-F4.4Support (IR on) .human, motor vehicle and non-motor vehicle image captureTripwire and intrusion Support alarm triggering by target types (human and vehicle)Support filtering false alarms caused by animals, rustling leaves, bright lights, etc. Pan: 0 ' to 360 ' ,(120)endless , Tilt: -15 ' to +90 ' , auto flip 180 ' , Pan: 0.1 ' -300 ' /s , Tilt: 0.1 ' -200 ' /s WDR EIS, Defog, Rol,2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Alarm I/O : 2/1 , Audio I/O : 1/1 PoE+, IP67; IK10; TVS 6000 V,</p>	<p>440,000,000</p>
95	DH-SD5A432GB-HNR	<p>4MP 32x Starlight IR WizSense Network PTZ Camera Image Sensor 1/2.8" CMOS .Max. Resolution 2560 (H) x 1440 (V)Electronic Shutter Speed 1/1 s-1/30,000 s, Min Illumination, Color: 0.005 lux@F1.6, B/W: 0.0005 lux@F1.6 Illumination Distance 150 :m(IR), Focal Length 4.8 mm-154 mmManual Control Speed Pan: 0.1 ' /s-300 ' /s, Tilt s-200 ' /sPreset 300, Tour 8 (up to 32 presets per tour), Pattern 5, Scan/0.1 ' 5Perimeter Protection, Face Detection, Auto Tracking, Quick Pick, SMD BLC, WDR ,db, WB, AGC, ANR, Rol, EIS, Defog Electronic, S/N Ratio ≥55 dBStorage : FTP 120 :;) Micro SD card (512 GB); NAS, Alarm I/O 2/1, A, Audio I/O 1/1Power Supply 24 VDC, 2.5 A Operating Temperature -40 ' C to +70 ' C, (25%</p>	<p>460,000,000</p>
96	SD5A432XA-HNR	<p>4MP 32x Starlight IR WizSense Network PTZ Camera1/2.8" 4Megapixel STARVIS .Progressive CMOSH.265+, H.264+, H.265, H.264, MJPEG(Sub Stream) 3 Stream, Max 25/30fps@4MMin. Illumination Color: 0.005 Lux@F1.35, B/W: 0.0005 Lux@F1.35, 0 Lux (IR on)4.9 mm-156 mm Powerful 32x optical zoom, Max. Aperture F1.35-F4.4Max ,Presets Speed: Pan: 400 ' /s Tilt: 300 ' /s, Pan: 0 ' -360 ' endless rotationWDR(120), EIS ,Defog, Rol,2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICRDeep Learning Auto Track, Tripwire, intrusion, Object Abandoned/Missing, SMD Plus, Face ,Detection, human/motor vehicle/non-motor vehicle Classification ,Animals/Leaves/Light False Alarm FilteringUp to 300 presets,8 tour, 5 pattern Auto scan, Auto PanMicro SD card (256G), 1/1 Audio I/O, 2/1 Alarm I/O, ONVIF Profile ;S&G&TIR distance up to 150m, DC 24 V/2.5 A, PoE+, IP67, IK10, 6000V lightning proof surge protection; voltage transient protection</p>	<p>4 28,000,000</p>
97	SD5A445XA-HNR	<p>4MP 45x Starlight IR WizSense Network PTZ Camera1/2.8" 4Megapixel STARVIS .Progressive CMOSH.265+/H.265+/H.264+/H.264/MJPEG(Sub Stream) 3 Streams, Max 25/30fps@4MMin. Illumination Color: 0.005 Lux@F1.6 B/W: 0.0005 Lux@F1.6 0Lux 3.95 mm-177.7 mm Powerful 45x optical zoom Max. Aperture (IR light on) F1.6-F4.95Max Presets Speed: Pan: 400 ' /s Tilt: 300 ' /s, Pan: 0 ' -360 ' endless rotationWDR(120), EIS, Defog, Rol,2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICRDeep Learning, Auto Track, Tripwire, intrusion, Object Abandoned/Missing, SMD Plus, Face Detection, human/motor vehicle/non-motor vehicle Classification, Animals/Leaves/Light False Alarm FilteringUp to 300 presets,8 tour, 5 pattern, Auto scan, Auto PanMicro SD card (256G), 1/1 Audio I/O, 2/1 ,Alarm I/O, ONVIF Profile S&G&TIR distance up to 150m, DC 24 V/2.5 A, PoE+, IP67 IK10, 6000V lightning proof; surge protection</p>	<p>5 35,000,000</p>
98	SD6CE445XA-HNR	<p>4MP 45x Starlight IR WizSense Network PTZ Camera1/2.8" 4Megapixel STARVIS .Progressive CMOSH.265+/H.265/H.264+/H.264/MJPEG(Sub Stream) Max ;25/30fps@4MMinimum Illumination Color: 0.005 Lux@F1.6; B/W: 0.0005 Lux@F1.6 Lux@F1.6 (IR on)3.95 mm-177.75 mm Powerful 45x optical zoom Max. Aperture 0 F1.6-F4.95Pan/Tilt Range Pan: 0 ' -360 ' endless; Tilt: -20 ' -90 ' ,auto flip 180 ' Preset Speed Pan: 300 ' /s; Tilt: 200 ' /s WDR 120db, BLC, HLC, Auto ICR, AWB, AGC, 2D/3D DNR, Rol, EIS, DefogDeep-learning-based auto tracking and perimeter -protectionFace detection, SMD Plus, Tripwire, intrusion. Human/Vehicle/Motor non Motor Vehicle DetectionUp to 300 presets,8 tour, 5 pattern, Auto scan, Auto PanMicro SD card (256G), 1/1 Audio I/O, 7/2 Alarm I/O, ONVIF Profile S&G&TIR distance up to 250m, DC 24 V/2.5 A, PoE+, IP67, IK10</p>	<p>5 60,000,000</p>

99	DHI-NVR1104HS-S3/H (V2.0)	Channel IPC Input, 4K Lite H.265 NVR 1/4 Live & Playback Smart H.265+/Smart 4 H.264+/H.265/H.264 Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60Mbps for forwarding. Up to 8MP Resolution for Preview & Playback Decoding Capacity: 1-ch@8MP(30FPS) or 1-ch@5MP(30FPS) or 2-ch@4MP(30FPS) or ch@3MP(30FPS) or 4-ch@1080P(30FPS) Video Output 1 VGA/1 HDMI simultaneous-2 video output, maximum resolution 1080P1 SATA 2.0 port, up to 8TB1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only1 RJ-45 port (10/100 (Mbps), P2P Support, ONVIF(profile T/profile S/profile G	27,000,000
100	NVR2104HS-P-I	Channel Compact 1U 4PoE WizSense Network Video Recorder, New 4.0 user 4 interface H.264/H.265/Smart H.264+/Smart H.265+/MJPEG, H.265 auto switch1 VGA/1 HDMI simultaneous video output, HDMI 4K, non-simultaneous video output is also supported on 1080p 1-channel face detection and recognition (AI by NVR); or 2 channel perimeter detection (AI by NVR); or 4-channel SMD (AI by NVR); up to 10 .face databases and 5,000 face imagesMax. decoding capability: 4*1080P@30fps Supports adaptive decoding Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding Resolution 12M/8M/5M/4M/3M/2M/720P/D1 AI disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3 -channel 4MP@30 fps; 6- channel 1080p@30 fps AI enabled: 1-channel 8MP@30 fps; 1 channel 5MP@30 fps; 2-channel 4MP@30 fps; 4-channel 1080p@30 fps 4 PoE Ports, 1 SATA port, up to 8 TB, 1 front USB 2.0 port, 1 rear USB 2.0 port, 1 RJ-45 port (10/100 (Mbps), 4 RJ-45 ports with PoE power supply (10/100 Mbps	60,000,000
101	NVR2104HS-4KS2	channel IP camera input H.265/H.264 codec decoding Max 80Mbps incoming 4 bandwidth Up to 8Mp resolution preview & playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support	32,500,000
102	NVR2104HS-P-4KS2	channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming 4 bandwidth Up to 8Mp resolution preview & playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, 4PoE Port, P2P support	42,500,000
103	DHI-NVR1108HS-S3/H	Channel IPC Input, 4K Lite H.265 NVR 1/4/8/9 Live & Playback Smart H.265+/Smart 8 H.264+/H.265/H.264 Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding. Up to 8MP Resolution for Preview & Playback Decoding Capacity: 1-ch@8MP(30FPS) or 1-ch@5MP(30FPS) or 2-ch@4MP(30FPS) or ch@3MP(30FPS) or 4-ch@1080P(30FPS) Video Output 1 VGA/1 HDMI simultaneous-2 video output, maximum resolution 1080P1 SATA 2.0 port, up to 8TB1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only1 RJ-45 port (10/100 (Mbps), P2P Support, ONVIF(profile T/profile S/profile G	33,500,000
104	NVR2108HS-4KS2	channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming 8 bandwidth Up to 8Mp resolution preview & playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support	40,000,000
105	NVR2108HS-8P-4KS2	channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming 8 bandwidth Up to 8Mp resolution preview & playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, 8Port PoE, P2P support	56,500,000
106	NVR2108HS-S3	Channel Lite Series, Compact 1U 1HDD Network Video Recorder Smart 8 * H.265+/H.265/Smart H.264+/H.264 decoding format Max. decoding capability: 6 1080p@30 fps. Supports adaptive decoding AI by camera: perimeter protection, and SMD Plus Multi-channel Playback Up to 8 channels, HDD Interface 1 SATA port, up to TB Audio Input/Out: 1/1, Network Port 1 * RJ-45, 10/100 Mbps Power Supply 12 16 VDC, 1.5 A	43,000,000
107	NVR2108HS-I2	Channel Compact 1U 1HDD WizSense Network Video Recorder Smart 8 H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Max. decoding capability: 6 * 1080p@30 fps. Supports adaptive decoding 1-channel face detection and recognition (AI by NVR) 1-channel perimeter protection (AI by NVR), 4-channel SMD Plus (AI by NVR) AI by camera: Face detection and recognition, perimeter protection, and SMD Plus HDD 1 SATA port, up to 10 TB, RCA Input 1, RCA Output 1 Power Supply 12 VDC, 1.5 A, Operating Temperature -10 °C to +55 °C	58,000,000

108	NVR2108HS-I	<p>Channel 12MP WizSense NVR 1/4/8 Live & PlaybackSmart 8</p> <p>H.265+/H.264+/MJPEGNetwork Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwardingAi Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled: 1ch 8MP@30fps or 1ch 5MP@30fps or 2ch 4MP@30fps or 4ch 2MP@30fpsHDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Libraryor 2ch Perimeter Ai By NVR or 4ch SMD Plus Ai by NVR, Human/Vehicle Classification1 SATA II port, up to 8TB1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port1 RJ-45 port (profile T/profile S/profile G), P2P Support, ONVIF (1000Mbps)</p>	58,000,000
109	NVR4108HS-4KS2	<p>channel IP camera input1/4/8/9 channel Live Preview, 8CH Playback H.265/H.264 8 codec decodingMax 80Mbps incoming bandwidthUp to 8MP Resolution for Preview ,and Playback HDMI/VGA simultaneous video outputSupport1 SATA HDD up to 6TB USB2.0100 Mbps Network Card, P2P support 2</p>	47,000,000
110	DHI-NVR2216-4KS2	<p>,Channel 4K Lite H.265 NVR 1/4 Live & PlaybackDual-core embedded processor 16 H.265/H.264 codec decodingMax 80Mbps incoming bandwidth, Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output2 SATA III ,Ports, up to 6TB capacity for each, Total 12TB1 front USB 2.0 port, 1 rear USB 2.0 port 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (1000Mbps), P2P Support</p>	62,000,000
111	NVR2116HS-I	<p>Channel 12MP WizSense NVR 1/4/9/16 Live & PlaybackSmart 16</p> <p>H.265+/H.264+/MJPEGNetwork Bandwidth 200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwardingAi Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled: 1ch 8MP@30fps/1ch 5MP@30fps/2ch 4MP@30fps/4ch 2MP@30fpsHDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Libraryor 2ch Perimeter ,Ai By NVR or 4ch SMD Plus Ai by NVR, Human/Vehicle Classification1 SATA II port up to 8TB1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 (profile T/profile S/profile G)port1 RJ-45 port (1000Mbps), P2P Support, ONVIF</p>	73,000,000
112	NVR2116HS-I2	<p>Channel Compact 1U 1HDD WizSense Network Video RecorderSmart 16</p> <p>H.265+/H.265/Smart H.264+/H.264/MJPEG decoding formatNetwork Bandwidth: AI :off: Access: 144 Mbps; Storage: 144 Mbps; Forward: 72 MbpsAI on: Access: 72 Mbps ;Storage: 72 Mbps; Forward: 36 MbpsResolution: 12MP; 8MP; 5MP; 4MP; 3MP; 2MP 720p; DIDecoding Capability: AI disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fpsAI enabled: 1-channel 8MP@30 fps; 1-channel 5MP@30 fps; 2-channel 4MP@30 fps; 4-channel 1080p@30 fps1 x VGA, 1 x HDMI (simultaneous) 4K Output1-channel face detection and recognition (AI by NVR); 1-channel perimeter protection (AI by NVR); up to 10 face databases and 5,000 face images; 4-channel SMD Plus (AI by NVR);AI by camera: Face detection and recognition, perimeter protection, and SMD Plus1 SATA II port, up to 10TB1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)</p>	72,000,000
113	DHI-NVR2216-I	<p>Channel 12MP WizSense NVR 1/4/9/16 Live & PlaybackSmart 16</p> <p>H.265+/H.264+/MJPEGNetwork Bandwidth 200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwardingAi Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled: 1ch 8MP@30fps/1ch 5MP@30fps/2ch 4MP@30fps/4ch 2MP@30fpsHDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Libraryor 2ch Perimeter ,Human/Vehicle Classification2 SATA 2.0 port :Ai By NVR or 4ch SMD Plus Ai by NVR up to 8TB each, Total 16TB1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)</p>	90,000,000
114	NVR4116HS-4KS2	<p>Channel Compact 1U 4K&H.265 Lite Network Video RecorderSmart H.265+/Smart 16 H.264+/H.265/H.264; H.265 auto switchMax 80Mbps Incoming BandwidthUp to 8MP Resolution for Preview and Playback8-channel decoding@1080p (30 fps)AI by Camera: Perimeter protection; SMD Plus; people counting; heat map target classification (human, vehicle)HDMI(4K)/VGA simultaneous video output1 SATA III port, up to 10 TB, 1 front USB 2.0 port, 1 rear USB 3.0 portAudio I/O 1/1 for Two Way Talk Only100 Mbps Network Card, P2P support</p>	69,000,000

T15	NVR4T16HS-4KS2/L	channel IP camera input, 16 channel Live Preview Smart H.265/H.264 codec 16 decodingMax 80Mbps incoming bandwidthUp to 8MP Resolution for Preview and Playback 16-ch@720P decoding capacity Support SMD Plus by Camera HDMI(4K)/VGA simultaneous video outputSupport 1 SATA HDD up to 8TB, 2 USB2.0/100 Mbps Network Card, P2P support	69,000,000
T16	NVR4216-4KS2/L	channel IP camera input, 16 channel Live PreviewSmart H.265+/H.264+ codec 16 decodingMax160Mbps incoming bandwidthMax. decoding capability: 8 x 1080p@30 fps. Supports adaptive decoding 8-ch@1080P decoding capabilityHDMI(4K)/VGA ,simultaneous video outputAI by Camera: Face detection with Face Attributes perimeter protection, IVS, people counting, heat map, and SMD Support 2 SATA ,HDD up to 10TB, 2 USB Ports (1 USB2.0, 1 USB3.0)4 Alarm Input, 2 Relay Output (profile T/S/C)1000Mbps Network Card, P2P support, ONVIF1	90,000,000
T17	NVR4216-16P-4KS2/L	channel IP camera input, 16 channel Live PreviewSmart H.265+/H.264+ codec 16 decodingMax160Mbps incoming bandwidthMax. decoding capability: 8 x 1080p@30 fps. Supports adaptive decoding 8-ch@1080P decoding capabilityHDMI(4K)/VGA ,simultaneous video outputAI by Camera: Face detection with Face Attributes perimeter protection, IVS, people counting, heat map, and SMD Support 2 SATA HDD up to 10TB, 2 USB Ports (1 x front USB2.0 , 1 x back USB2.0)4 Alarm Input, 2 Relay (profile T/S/C)Output, 1*1000Mbps Network Card, 16 Port PoE, ONVIF	1 51,000,000
T18	NVR4232-4KS2/L	Channel 1U 2HDDs Network Video RecorderSmart H.265+/H.264+ codec 32 decodingMax160Mbps incoming bandwidthMax. decoding capability: 8 x 1080p@30 fpsHDMI(4K)/VGA simultaneous video outputAI by Camera: Face detection with attributes, perimeter protection, IVS, people counting, heat map, and SMD, Human x Vehivle Classification2 SATA III ports, up to 10 TB each port, 1 x front USB2.0; 1 & ,back USB2.04 Alarm Input, 2 Relay Output, 1*1000Mbps Network Card, P2P support (profile T/S/C)ONVIF	108,000,000
T19	NVR4232-4KS2	channel IP camera input, 16 channel Live Preview H.265/H.264 codec 32 decodingMax 200Mbps incoming bandwidthUp to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video outputSupport 2 SATA HDD up to 6TB2 USB Ports (1 USB2.0, 1 USB3.0)4 Alarm Input, 2 Relay Output1*1000Mbps Network Card, P2P support	1 08,000,000
T20	DHI-NVR5232-4KS2(V2.0)	32Channel 1U 4K & H.265 Pro Network Video Recorder (V2.0)Smart H.265+/H.265/H.264+/H.264/MJPEG decodingMax 320Mbps incoming bandwidth, Up (30fps)to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P decoding1*HDMI(4K)/1*VGA simultaneous video output2*SATA HDDs(10 TB for each HDD), 2 USB(1 USB3.0,1 USB2.0)1*1000 Mbps Network Card, RS232, RS485,4/2 Alarm In/out, P2P Support	1 79,000,000
T21	NVR4432-4KS2/I	Channel 1.5U 4HDDs WizSense Network Video RecorderSmart 32 H.265+/H.265/Smart H.264+/H.264/MJPEGAccess, storage or forwarding at 256 ;Mbps, Max. decoding capability: 10 x 1080p@30 fps Face detection; face recognition perimeter protection,SMD PlusMulti-channel Playback Up to 16 channelThe maximum HDD capacity 4 SATA ports, up to 10 TBAlarm Input 16,Alarm Output 42 RJ-45 10/100/1000 Mbps self-adaptive Ethernet port	1 95,000,000
T22	NVR5432-4KS2(V2.0)	32Channel 1.5U 4K & H.265 Pro Network Video Recorder (V2.0) Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decodingMax 320Mbps incoming -bandwidthUp to 12Mp resolution preview & playbackMax 4-ch@8MP(30fps), 16 ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0,1 USB2.0) Support 1 e-SATA, 2*1000 Mbps Network CardRS232, RS485,16/6 Alarm In/out, P2P Support	2 55,000,000
T23	DHI-NVR5464-4KS2(V2.0)	64Channel 1.5U 4K&H.265 Pro Network Video Recorder (V2.0)Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decodingMax 320Mbps incoming -bandwidth, Up to 12Mp resolution preview & playbackMax 4-ch@8MP(30fps), 16 ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0,1 USB2.0)Support 1 e-SATA, 2*1000 Mbps Network Card, RS232, RS485,16/6 Alarm In/out, P2P Support	3 00,000,000
T24	NVR5832-4KS2	channel IPC input, 32 Channel Live PreviewH.265/H.264/MJPEG/MPEG4 codec 32 decodingMax 320Mbps incoming bandwidth, Up to 12Mp resolution preview&playbackMax16ch@1080P 4ch@4K H.265 H.264 Playback2HDMI/VGA simultaneous video outputSupport 8 SATA HDDs up to 48TB, 4 USB(2 USB3.0, 2 USB2.0)2*1000 Mbps Network Card, RS232, 16 Alarm In, 6 Relay Output, P2P Support, Raid 0/1/5/6/10	3 30,000,000

125	DHI-NVR5864-4KS2(V2.0)	Channel 2U 4K & H.265 Pro Network Video Recorder (V2.0)Smart 64 H.265+/H.265/H.264+/H.264/MJPEG decodingMax 320Mbps incoming bandwidth, Up (30fps)to 12Mp resolution preview & playbackMax 4-ch@8MP(30fps), 16-ch@1080P decoding2*HDMI/2*VGA simultaneous video output8*SATA HDDs(10 TB for each ,HDD), 4 USB(2 USB3.0,2 USB2.0)1*e-SATA, 2*1000 Mbps Network Card, RS232 RS485,16/6 Alarm In/out , P2P Support	4 40,000,000
126	NVR608-32-4KS2	Intel Dual-core Processor, 32 channel IPC input, 32 Channel Live Preview (1st ,Screen:1/4/8/9/16/25/36,2nd Screen: 1/4/8/9/16) H.265/H.264/MJPEG codec decoding Max 384Mbps incoming bandwidth Up to 12Mp resolution preview&playback2HDMI/VGA simultaneous video outputSupport 8 SATA HDDs up to 48TB,1 eSATA PortSupport Raid 0/1/5/6/10, 4 USB(2 USB3.0, 2 USB2.0)2*1000 Mbps Network Card, RS232, RS485, 16 Alarm In , 8 Relay Output	3 75,000,000
127	NVR608-64-4KS2	Intel Quad-core Processor64 channel IPC input, 32 Channel Live Preview(1st Screen:1st Screen: 1/4/8/9/16/25/36, 2nd Screen: 1/4/8/9/16), H.265/H.264/MJPEG & codec decoding Max 384Mbps incoming bandwidthUp to 12Mp resolution preview playback2HDMI/VGA simultaneous video output8 SATA III ports, up to 10 TB for a single HDD,1 eSATA PortSupport Raid 0/1/5/6/10Support Smart Tracking and , Intelligent Video4 USB(2 USB3.0, 2 USB2.0), 2*1000 Mbps Network CardRS232 RS485,16 Alarm In , 8 Relay Output	6 50,000,000
128	DHI-NVR608-128-4KS2	Channel 2U Ultra 4K H.265 Network Video Recorder (1st Screen: 1/4/8/9/16/25/36 128 2nd Screen: 1/4/8/9/16) H.265/H.264/MJPEG codec decodingMax 384Mbps incoming, bandwidthUp to 12Mp resolution preview & playback 2HDMI(different Source)/VGA simultaneous video output Support 8 SATA (8TB for each HDD),1 eSATA PortSupport Raid 0/1/5/10Support Smart Tracking and Intelligent Video4 USB(2 USB3.0, 2 USB2.0), 2*1000 Mbps Network Card RS232 , RS485, 16/8 Alarm In/Output	7 60,000,000
129	ESS1508C	2U standard 19-inch rack caseConnect master device via eSATA or USB1 eSATA port transmission speed up to 3Gbps1 USB 3.0 port data transmission higher than normal Powerful R / W performance: read >64MB/s, write >64MB/s ESS1508C: Max support Internal 8 SATA HDD up to 48TB Recommended with DVR, NVR connection	1 16,000,000
130	PFS3006-4ET-36	Port Fast Ethernet Switch with 4-Port PoE4 PoE ports with10/100 Mbps Base-TX2-6 uplink ports with10/100Mbps Base-TXPort1-4 ≤30W, whole PoE budget 36WSupport 802.3af and 802.3at standardsOperating Temperature: -10 °C to± 55 °CSupport 250 m long distance PoE tansmissionSupport PoE+ watchdogSwitching Capacity 1.2 Gbps, Packet Forwarding Rate 0.89 Mpps, MAC Table Size 2K, Jumbo Frame 2048 byte Standards IEEE 802.3, IEEE 802.3u, IEEE 802.3XESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 6kV Differential mode: 4kV	22,500,000
131	PFS3106-4ET-60 (V2.0)	Port PoE Switch (Unmanaged)4 × RJ-4510/100 Mbps (PoE)1 × RJ-4510/100/1000-4 Mbps (Uplink)1 × SFP 100/1000 Mbps (Uplink)Intelligent PoE, Hi-PoE 60W (Orange Port), PoE watchdog, 250 m long distance PoE transmissionWide operating temperature: -30 °C to +65 °C (-22 °F to +149 °F)Switching Capacity 6.80 Gbps, Packet Forwarding Rate 3.57 Mpps, Packet Buffer Memory 1 Mbit, MAC Table Size 8K Communication Standard IEEE802.3; IEEE802.3u; IEEE802.3X; IEEE 802.3ab; IEEE 802.3zPoE Standard IEEE802.3af; IEEE802.3at; Hi-PoE, 250 m long distance PoE ,transmissionStatics Protection Air discharge:15kV Contact discharge:8kV Thunder-proof Common mode:4kV Differential mode:2kV	41,000,000
132	PFS3010-8ET-65	Port Fast Ethernet Switch with 8-Port PoEPort 1-8: 8 × RJ-4510/100 Mbps-10 Port 9-10: uplink with 10/100 MbpsSupport 802.3af and 802.3at(PoE) standardsSupport 250 m long distance PoE tansmissionSupport PoE ,watchdogPort1-8 ≤30W, whole PoE budget ≤65WSwitching Capacity 2.0 Gbps Packet Forwarding Rate 1.49 Mpps , MAC Table Size 2K, Jumbo Frame 2048 byte ESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 6kV Differential mode: 4kV	32,150,000
133	PFS3110-8ET-96 (V2.0)	Port Unmanaged Desktop Switch with 8 Port PoEPort 1-8: 8 × RJ-4510/100 Mbps-10 Port 9: 1 × RJ-45 10/100/1000 Mbps (uplink)Port 10: 1 × SFP 1000 Mbps(PoE) Communication Standard IEEE802.3/IEEE802.3u/IEEE802.3X/IEEE(uplink) /802.3ab/IEEE 802.3zPoE Standard IEEE802.3af/ IEEE802.3at/ Hi-PoE ,IEEE802.3btPort 1-2 ≤ 90 W, Port 3-8 ≤ 30W, totals ≤ 96 WIntelligent PoE, BT 90W Long distance PoE, PoE watchdog, Wide working temperatureLightning Protection Air discharge:8kV Contact discharge:6kV, ESD Protection Common mode:4kV Differential mode:2kV	59,500,000

134	PFS3218-16ET-135	Layer 2 PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 16 * RJ45 10/100 Mbps Port 1-2s60W, Port 3-16s30W, total≤135W IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z PoE Standard IEEE802.3af IEEE802.3at, Hi-PoE Intelligent PoE, PD Alive (PoE Watchdog), Long Distance PoE Transmission, Smooth Transmission Wide Working Temperature: -10 to 55°C (14°F to 131°F), VLAN Port Isolation Switching Capacity 7.2 Gbps, Packet Forwarding Rate :Mpps, Packet Buffer Memory 4 Mbit, MAC Table Size 8K ESD Air discharge 5.3568 :8kV Contact discharge: 6kV, Thunderproof Common mode: 4kV Differential mode 2kV	102,000,000
135	PFS3226-24ET-240	Layer 2 PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 24 * RJ45 10/100 Mbps intelligent PoE, PD Alive (PoE Watchdog), Long Distance PoE Transmission, Smooth Transmission Wide Working Temperature: -10 to 55°C (14°F to 131°F), VLAN Port Isolation Port 1/2 support Hi-PoE (60W), PoE+, PoE Port 1 (14°F to 131°F), 60W, Port 3-24s30W, total≤240W IEEE802.3, IEEE802.3u, IEEE802.3x≥2 IEEE802.3ab, IEEE802.3z PoE Standard IEEE802.3af, IEEE802.3at, Hi-PoE Switching Capacity 8.8 Gbps, Packet Forwarding Rate 6.5472 Mpps MAC Table Size 8K ESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 4kV Differential mode: 2kV	131,000,000
136	PFT1300	PoE Extender 1*10/100 Base-T PoE power receiving port 1*10/100 Base-T PoE power supply port, supply power for the next extender 1*10/100 Base-T PoE power supply port, supply power for IPC Support passive PoE cascade power supply and Ethernet data exchange Support IEEE 802.3af/at standard power supply IP Camera able to cascade level 2 PoE Extender, connect to 3 IPC (power consumption <=8W), max transmission distance 300m	6 650,000
137	PFM700	Channel HDMI Transmission Signal *1080P/1080i/720P/576P/576i/480P/480i* Resolution Output Signal, *60M (max) Transmission Distance *Input voltage ,DC5V *Use single UTP (CAT-5E and CAT-6) real-time transmit 1-ch HD video signal: support HDMI 1.3	18,700,000
138	NKB1000	, Keyboard to Control : Dahua High Speed Dome (all models) Dahua Standalone DVR , Dahua Network High Speed Dome Network Video Server, Connection : RS485 RS422, USB, RS232 & Network Three Dimensional Joystick Control of PTZ -Functions Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control, On Screen Menu & User Operation Procedure Tips Connect to SmartPSS via USB	12,200,000