

## JVS-N916-YDL


## 3.0MP Full-Color Video & Audio PoE Network Camera



## **Key Features**

- Resolution 2304x1296@20fps
- Ingress Protection IP66
- 4x IR-LED + 4x Warm-LED Up to 30 Meters
- Spotlight on motion detection
- Full-Color with Dual Smart Illumination
- Support Humanoid Detection
- With built-in PoE
- Built-in Mic

## **Dimensions (mm)**



| Specifications       |   |
|----------------------|---|
|                      |   |
| Video                |   |
| Image Sensor         | 1/ 2.9" CMOS  |
| Max Resolution       | 2304x1296   |
| Effective Pixels     | 3.0MP   |
| Compression Standard | H.265 / H.264   |
| Maximum Frame Rate   | 2304x1296@20fps   |
| SNR(dB)              | 52dB  |
| Bit Rate             | 256Kbps~8Mbps   |
| Illumination         | 0Lux (IR ON)  |
| Lens                 |   |
| Lens                 | 3.6mm   |
| Viewing Angle        | H: 78.5°, V: 42.8°, D:92.6°                                 |
| IR-LEDs              | 4x IR-LED + 4x Warm-LED                                     |
| IR-Distance          | Up to 30 Meters   |
| Function             |   |
| Motion Detection     | Support   |
| Email Alert          | Support   |
| Day& Night           | Support   |
| Recording            | Support (NVR, Windows PC, Smartphone)                       |
| DHCP                 | Support   |
| FTP                  | Not Supported   |
| Pan/Tilt             | Not Supported   |
| SD-Card              | Not Supported   |
| Privacy Mask         | Support up to 8 areas                                       |
| Exposure Control     | Support   |
| Image Adjustment     | Support   |
| Auto. White Balance  | Support   |
| Image Rotation       | Support (Mirror/Flip)                                       |
| Network              |   |
| Ethernet             | 10M/100M Ethernet, RJ45 Port                                |
| Protocols            | HTTP, TCP/IP,UDP, ICMP, RTSP, RTP, RTCP,<br>SMTP, DHCP, DNS |
| Stream               | 2x Streams  |
| Wi-Fi                | Not Supported   |
| LAN                  | Support   |
| ONVIF                | ONVIF 2.4   |
| User                 | Up to 13 Users  |
| Browser              | IE8+, Chrome18+ ~ 42-                                       |
| Smart Phone          | iOS/Android   |
| General              |   |
| Dimensions(W*H*D)    | 182x65x65mm   |
| Weights              | ≤460g   |
| Material             | Metal   |
| Working Temperature  | -20°C~60°C  |
| Humidity             | RH 10%~90%  |
| •                    |   |
| Power Supply         | DC12V, PoE<br>Dov. $\leq 2W$ Night $\leq 6W$                |
| Consumption          | Day ≦3W Night ≦ 6W  |
| Waterproof           | IP66  |

 $\ensuremath{\textcircled{C2021}}$  Jovision Technology Co., Ltd. All rights reserved.

Note: Design and specifications are subject to change without notice. Under no circumstances, this document shall be reproduced, distributed or changed partially or wholly without formal authorization of Jovision Technology Co., Ltd