

JVS-N936-MDL

3MP Dome Full-Color Audio IP Camera



Features

- Light's On When People Come, Light's Off When People Leave
- Double Wick, Two warm light, Two infrared
- Support Humanoid Detection
- Support Region Intrusion Detection, Line Crossing Detection, Video Tampering Detection, Defocus Detection
- Equipped With unique VQC (Video Quality Catalyst) Technology
- Built-in MIC and Speaker

Specifications

Video	
Image Sensor	1/2.8" CMOS Sensor
Max Resolution	2304x1296
Effective Pixels	3.0MP
Compression Standard	H.265/H.264
Frame Rate	25fps
Bit Rate	128Kbps~4096Kbps
SNR (dB)	52dB
Min. Illumination	0Lux (IR ON)
Lens	
Lens	2.8mm(M12)
FOV	H:100.4°, V:53.9°, D:118.6°
Lights	2 Warm Light LEDs + 2 IR LEDs

IR Distance	IR: Up to 30 Meters Warm Light: Up to 25 Meters
Function	
Exposure Control	Auto
White Balance	Auto
Gain Control	Auto
Image Enhancement	3D DNR
Advanced OSD	Support OSD large font function, OSD flashing on alarm, OSD and time to set the position separately
Motion Detection	Support Humanoid Detection
Image Setting	Flip, Saturation, Brightness, Contrast, Sharpness
Day and night function	Day and night automatic switching
Privacy Mask	Support up to 8 areas
Intelligent Analysis	Region Intrusion Detection, Line Crossing Detection, Video Tampering Detection, Defocus Detection
Alarm Method	Email Alarm, Client Alarm
Remote Operation	System, Audio and video, Image, Alarm, Network management
Expansion Interface	Built-in MIC and Speaker
Network	
Ethernet	10M / 100M Ethernet , 1 RJ45
Stream	2x Streams
Protocols	HTTP, TCP/IP, UDP, ICMP, RTSP, RTP, RTCP, SMTP, DHCP, DNS
ONVIF	standard ONVIF
Network transmission	CloudSEE 2.0, GB28181
Browser	IE8+, Chrome18+, Firefox5.0+, Safari5.02+
User	Up to 13 Users
App	Support iOS/Android
General	
Power Supply	DC12V/2A or PoE
Power Consumption	<3W (During day); <6W (At night)
Working Temperature	-20°C ~ 60°C
Working Humidity	10% ~ 90% Rh
Material	White/Plastic
Dimensions (WxHxD)	100x84x100mm
Weight	210g