

# JVS-HD6610-FR

10CH H.265 AI NVR



## Key features

- Full HD Video output.
- Supports 10Ch 5.0Megapixel IP Cameras
- H.265 Video Compression
- ONVIF 2.4 Standard, compatible with ONVIF IP Cameras
- Support CloudSEE on PC and Smart Phone, iOS/Android
- With Digital Zoom, Privacy Mask functions.
- Face Recognition Function

## Specifications

Model	JVS-HD6610-FR
<b>Video and Audio</b>	
<b>IP Camera Input</b>	10 Channel
<b>Audio Input/ Output</b>	1 Channel Output, RCA
<b>Display</b>	
<b>Interface</b>	1 HDMI, 1 VGA
<b>Resolution</b>	HDMI: 2560X1440/1920×1080/1440×900/1280×1024/1280×720/1024×768
	VGA: 1920×1080/1440×900/1280×1024/1280×720/1024×768
<b>Multi-screen Display</b>	1/4/5/6/7/8/9/10
<b>OSD</b>	Camera Name & Time, Recording, Alarm Detecting, Remote connection, Volume, Channel Number
<b>Recording</b>	
<b>Compression</b>	H.265/H.264
<b>Resolution</b>	10Ch 5.0MP/4.0MP/1080P/960P/720P
<b>Record Mode</b>	Auto, Schedule, MD, Smart Analysis, Alarm
<b>Video Detection and Alarm</b>	
<b>Trigger Events</b>	Recording, Snapshot, PTZ, Voice, E-mail, Client, Buzzer
<b>Video Detection</b>	Motion Detection, No Video Detection, People Counting, People Density, Video Covering, Line Crossing Detection, Region Entrance Detection, Fast Moving Detection
<b>Face Recognition</b>	
<b>Face Recognition</b>	Alarm Setting, Face Database Management, Search Face by Face, Search Video by Face
<b>Playback and Backup</b>	
<b>Sync Playback</b>	1ch 5.0MP, 1ch 4.0MP, 1ch 3.0MP
<b>Search Mode</b>	Time /Date, Channel, Recording Type
<b>Playback Function</b>	Day View, Hour View, Back Step, Rewind, Pause, Play, Fast Forward, Slow, Step, Full Screen, Snap, Sound On/Off, Zoom
<b>Backup Mode</b>	USB Device/Network
<b>Network</b>	
<b>Interface</b>	1 RJ-45 port (10/100Mbps)
<b>Protocol</b>	TCP/IP, DHCP, UDP, SMTP, NTP
<b>Smart Phone</b>	iPhone, Android, TCP/UDP Protocol
<b>ONVIF</b>	ONVIF 2.4
<b>Storage</b>	
<b>SATA</b>	1 SATA interface
<b>Capacity</b>	Up to 10TB
<b>General</b>	
<b>Power Supply</b>	12V DC
<b>Consumption</b>	≤ 10 W (Without HDD)
<b>Working Temperature</b>	-10°C~ 55°C
<b>Working Humidity</b>	10 % ~ 90 %
<b>Dimensions</b>	260×219×45mm
<b>Weight</b>	≤ 1kg (Without HDD)