

## JVS-H930E




## pecifications

## **Key Features**

- Resolution 2048x1536.
- With IR LED Lights and IR-CUT, monitoring day and night.
- Supports two-way talk
- Wi-Fi (Built-in antenna)
- PAN and TILT
- Support 128GB SD Card
- With Human Tracking Smart Function

## Dimension:



Unit: mm

Video	
Image Sensor	1/3″ CMOS
Max Resolution	Up to 2048*1536
Effective Pixels	3.0 MP
Compression Standard	H.264/H.265
Framerate (fps)	Up to 20fps
Bitrate	128Kbps~1024bps
Illumination	0Lux (IR ON)
Lens	
Interface Type	M12
Lens	4mm
Viewing Angle	H:74.1°, V: 40.5°, D: 86.9°
Focusing System	Fixed
Function	
Privacy Masking	Supports 4 zone masking
Exposure Mode	Auto
Automatic Gain Control	Auto
White Balance	Auto
Motion Detection	Support
Day-Night Vision	IR-CUT, Supports color/black switch
Remote Control	System Management, Audio/Video Management, Image Management, Storage Management, Alarm Management, Network Management.
Detection Alarm	E-mail Alarm, Client-end Alarm, Smartphone Message Alarm
Two-way Talk	Support
Storage	Up to 128GB
Pan/Tilt	H: 350°, V: 55°
ONVIF	Support
Interface	
Audio Input	1 Channel Internal MIC
Audio Output	1 Channel Internal Speaker
Ethernet Port	Yes
TF Card	Support
Reset	Support
Network	
Ethernet	10M/100M Ethernet, RJ45 Port
Wi-Fi Stream	Support
Stream	Dual stream TCP/IP, ICMP, UDP, SMTP,
Protocols	FTP,DHCP,DNS,PPPOE
General	
Network Transmission	CloudSEE P2P Transmission Protocol
IR Light	4 pcs IR LED Lights
IR Distance	Up to 12m
Working Temperature	-10°C~55°C
Humidity	90%RH
Power Supply	DC5V/1.5A
Consumption	5W
Color/Material	White/ABS+PC
Dimension (WxHxD)	85 x 85 x 119 (mm) 220
Weight (g)	
Installation	Wall, Ceiling, Desktop

 $\textcircled{\sc c}$  2021 Jovision Technology Co., Ltd. All rights reserved.

Note: Design and specifications are subject to change without notice. Under no circumstances, this document shall be reproduced, distributed or changed partially or wholly without formal authorization of Jovision Technology Co., Ltd