

# JVS-N819-LPR

8.0MP Motorized Zoom Full-Color Auto License Plate Recognition Network Camera



## Features

- Motorized Varifocal Lens (2.7-13.5mm)
- 24/7 Full-Color with VQC Technology
- Built-in Mic and Speaker
- Support SD Card (Up to 512G)
- Built-in Recognition Algorithm Support Over 50 Countries Vehicle and Standard License Plates Around the World
- Easy to Install and Suitable for Multiple Scenarios (Entrance, Parking Lot, Sidewalk, High Pole, Low Pole, etc.)
- More Than 95% Recognition Accuracy and Fake License Plates Recognition (Photocopy or Screenshot)
- Supports Customized Allowlist and Blocklist

## Specifications

Video	
Image Sensor	1/2.8" CMOS
Max Resolution	3840x2160
Effective Pixels	8.0MP
Compression Standard	H.264/H.265+
Framerate	30fps
Bitrate	Main Stream: 256Kbps ~ 4096Kbps Sub Stream: 68Kbps~1024Kbps Third Stream: 68Kbps~1028Kbps
SNR (dB)	≥50dB
Min. Illumination	0Lux (light ON)
Lens	
Lens	Motorized Zoom Lens, 2.7mm-13.5mm
Focal lens & FOV	2.7mm-13.5mm    Horizontal FOV: 101.4° to 26.9° Vertical FOV: 53.6° to 15.2°    Diagonal FOV: 118.7° to 30.5°
Function	
Audio Codec	G.711U/G.711A (default)
Exposure Control	Auto
White Balance	Auto
Gain Control	Auto
Digital 3D Noise Reduction	Support
OSD Information Setting	By default: The customized OSD supports a maximum of six lines, each line contains a maximum of 32 characters. One Chinese character is counted as two characters
SNTP	Support

<b>Schedule Reboot</b>	Support
<b>Smart Defog</b>	Support
<b>Smart Motion Detection</b>	Not Support
<b>Image Setting</b>	Support Saturation, Brightness, Contrast, Sharpness adjustment
<b>Image Style</b>	Standard, Soft, Transparent
<b>Day and Night Function</b>	Auto, Always Black & White, Always Color, Scheduled Color
<b>Privacy Mask</b>	Support up 8 areas
<b>Night Vision Optimization</b>	Support
<b>WDR</b>	120dB
<b>Screen Settings</b>	Screen mirroring, Screen flipping
<b>IP Adaptation</b>	Support automatic adaptation of IP address (Optional)
<b>Intelligent Analysis</b>	Not Support
<b>Alarm Method</b>	Email Alarm, Client Alarm
<b>Remote Operation</b>	System, Audio and Video, Image, Alarm, Network management, Storage management, Intelligent Analysis
<b>Audio Function</b>	Built-in Mic and Speaker
<b>SD Card</b>	Support ( 512G )
<b>Peripheral Extension Interface</b>	Audio Input/Output, Alarm Input/Output
<b>Network</b>	
<b>Ethernet</b>	10/100Mbps Ethernet
<b>Stream</b>	3x Streams
<b>Network Protocols</b>	HTTP, TCP/IP, UDP, ICMP, RTSP, RTP, RTCP, SMTP, DHCP, DNS
<b>Access Protocol</b>	Standard ONVIF, Public Cloud
<b>Network Transmission</b>	CloudSEE 2.0
<b>Fusion Cloud Platform</b>	Support
<b>Browser</b>	IE8+, Chrome18+, Firefox5.0+, Safari5.02+
<b>User</b>	Up to 13 Users
<b>App</b>	Support iOS/Android
<b>General</b>	
<b>Lights</b>	4 Warm Light LEDs + 4 IR LEDs
<b>IR Distance</b>	IR: Up to 80 Meters Warm Light: Up to 60 Meters
<b>Waterproof Level</b>	IP67
<b>Power Supply</b>	DC12V/2A or PoE
<b>Power Consumption</b>	<6W (During Day); <12W (At Night)
<b>Working Temperature</b>	-30°C ~ +60°C
<b>Working Humidity</b>	10% ~ 90% Rh
<b>Color/Material</b>	Black and White/Metal + Plastic
<b>Dimensions (WxHxD)</b>	103x91x255mm
<b>Weight</b>	732g
<b>Installation Method</b>	Wall or Ceiling Mount

## Dimension

