

# JVS-N933-KDL-PE


## 3MP Full-Color Audio PoE IP Camera



## **Key Features**

- Resolution 2304x1296@25fps
- Light's on when people come, light's off when people leave
- Double wick, two white light, two infrared
- Support humanoid detection (Default does not mark the humanoid box)
- Built-in Microphone
- PoE

## Dimension(mm)



#### **Specifications**

Specifications	
Model	JVS-N933-KDL-PE
Video	
Image Sensor	1/2.9" CMOS Sensor
Max. Resolution	2304x1296
Effective Pixels	3.0MP
Compression Standard	H.265/ H.264
Framerate	25fps
Bitrate	204Kbps~5Mbps
SNR (dB)	52dB
Min. Illumination	0Lux (Fill light ON)
Lens	
Lens	2.8mm, 4mm, 6mm (M12)
Fill Light	2x Double wick filling lamp (Infrared/ Warm)
Fill Light Distance	Up to 30m.
Function	
Exposure Control	Auto
White Balance	Auto
Image Enhancement	3D DNR
Advanced OSD	Support OSD large font function, OSD flashing on
7 ta various GGB	alarm, OSD and time to set the position separately
<b>Motion Detection</b>	Support human detection (Default does not mark the human box)
Image Setting	Rotate, Saturation, Brightness, Contrast, Sharpness
Day and Night Function	Day and night automatic switching
Privacy Mask	Support up 8 areas
Intelligent Analysis	Not Support
Alarm Method	Email Alarm, Client Alarm
	System, Audio and video, Image, Alarm,
Remote Operation	Network management
Audio	Built-in Microphone
Network	
Ethernet	1x RJ45 10M / 100M Ethernet
Stream	2x Streams
Protocols	HTTP, TCP/IP, UDP, ICMP, RTSP, RTP, RTCP, SMTP, DHCP, DNS
Interoperability	ONVIF 2.4
Network Transmission	CloudSEE 2.0
Browser	IE8+, Chrome18+, Firefox5.0+, Safari5.02+
User	Up to 13 Users
Арр	Support iOS/Android
General	
Power Supply	DC12V/2A
Power Consumption	<3W (During day); <6W (At night)
Working Temperature	-20°C ~ 60°C
Working Humidity	10% ~ 90% Rh
Material	Plastic
Dimensions	100x100x92mm
Weight	170g
	-