

JVS-ND6616-HD(R2 version)

16CH H.265 1SATA NVR



Key features

- •Supports 16Ch 5.0Megapixel IP Camera
- •Adopt the new Vstar GUI, easy to operate and run smoothly
- •Support intelligent coding VSMart, greatly reducing storage space
- •Improved compatibility for hard disks, and up to 10TB
- Support Intelligent Detection and Human Detection

Description



Index	Description	Index	Description
1	RJ45	4	HDMI
2	Audio Out	5	USB
(3)	VGA	(6)	Power

Specifications

Model	del JVS-ND6616-HD		
Video and Audio			
IP Camera Input	16Channel		
Audio Input/ Output	1 Channel Output, RCA; 16Channel Audio output through HDMI		
Display			
Interface	1 HDMI, 1 VGA		
Resolution	HDMI: 2560X1440,1920×1080,1440×900,1280×1024,1280×720, 024×768 VGA:		
Mara Da a a dinan	1920×1080,1440×900,1280×1024,1280×720,1024×768		
Max Decoding	16ch@ 5.0MP/4.0MP/1080P/960P/720P 25fps		
Multi-screen Display	4/5/6/7/8/9/10/11/12/13/14/15/16 Camera Name & Time, Recording, Alarm Detecting,		
OSD	Remote connection, Volume, Channel Number		
Recording			
Compression	H.265/H.264		
Resolution	16Ch 5.0MP/4.0MP/1080P/960P/720P		
Record Mode	Manual, Schedule, MD		
Video Detection and A	Narm		
Trigger Events	Recording, Snapshot, PTZ, Voice, E-mail, Client, Buzzer		
Video Detection	Motion Detection, No Video Detection		
Playback and Backup			
Sync Playback	Playback 1ch 5.0MP, 1ch 4.0MP, 1ch 3.0MP,2ch 1080P		
Search Mode	Channel number / recording type / date		
Playback Function	Day View, Hour View, Back Step, Rewind, Pause, Play, Fast Forward, Slow, Step, Full Screen, Snap, Sound On/Off, Zoom		
Backup Mode	FAT32 USB Device/Network		
Network			
Interface	1 RJ-45 port (10/100Mbps)		
Network Function	TCP/IP, DHCP, UDP, SMTP, NTP		
Smart Phone	iPhone, Android		
Interoperability	ONVIF 2.4		
Storage			
SATA	1 SATA interfaces		
Capacity	up to 10TB		
General			
Power Supply	DC 12V		
Consumption	≤ 10 W (Without HDD)		
Working Temperature	ring Temperature -10°C~ 55°C		
Vorking Humidity 10 % ~ 90 %			
Dimensions	260*48*227mm		
Weight	≤ 1.0kg (Without HDD)		