





Main

Range	TeSys
Product name	TeSys F
Product or component type	Contacteur
Device short name	LC1F
Contacteur application	Motor control Resistive load
Utilisation category	AC-1 AC-3
Poles description	3P
Power pole contact composition	3 NO
[Ue] rated operational voltage	<= 460 V DC <= 1000 V AC 50/60 Hz
[Ie] rated operational current	115 A (<= 55 °C) at <= 440 V AC AC-3 200 A (<= 40 °C) at <= 440 V AC AC-1
Motor power kW	30 kW at 220...230 V AC 50/60 Hz 65 kW at 1000 V AC 50/60 Hz 80 kW at 660...690 V AC 50/60 Hz 75 kW at 500 V AC 50/60 Hz 59 kW at 440 V AC 50/60 Hz 59 kW at 415 V AC 50/60 Hz 55 kW at 380...400 V AC 50/60 Hz
Control circuit type	AC 50 Hz
Control circuit voltage	220 V AC 50 Hz
Overvoltage category	III
[I _{th}] conventional free air thermal current	200 A at <= 40 °C
I _{rms} rated making capacity	1150 A AC conforming to IEC 60947-4-1
Rated breaking capacity	920 A conforming to IEC 60947-4-1
[I _{cw}] rated short-time withstand current	320 A <= 40 °C 10 min 400 A <= 40 °C 3 min 520 A <= 40 °C 1 min 640 A <= 40 °C 30 s 1100 A <= 40 °C 10 s
Associated fuse rating	200 A gG at <= 440 V 125 A aM at <= 440 V
Average impedance	0.37 mOhm at 50 Hz - I _{th} 200 A
[U _i] rated insulation voltage	1500 V conforming to VDE 0110 group C 1000 V conforming to IEC 60947-4-1
Power dissipation per pole	5 W AC-3 15 W AC-1
Mounting support	Plate
Standards	EN 60947-1 EN 60947-4-1 IEC 60947-1 IEC 60947-4-1 JEM 1038
Product certifications	BV CCC CSA DNV GL RINA RMRoS UL LROS

Connections - terminals	Control circuit : screw clamp terminals 2 cable(s) 1...4 mm ² - cable stiffness: solid - without cable end Control circuit : screw clamp terminals 1 cable(s) 1...4 mm ² - cable stiffness: solid - without cable end Control circuit : screw clamp terminals 2 cable(s) 1...2.5 mm ² - cable stiffness: flexible - with cable end Control circuit : screw clamp terminals 1 cable(s) 1...4 mm ² - cable stiffness: flexible - with cable end Control circuit : screw clamp terminals 2 cable(s) 1...4 mm ² - cable stiffness: flexible - without cable end Control circuit : screw clamp terminals 1 cable(s) 1...4 mm ² - cable stiffness: flexible - without cable end Power circuit : connector 1 cable(s) 95 mm ² Power circuit : lugs-ring terminals 1 cable(s) 95 mm ² Power circuit : bar 2 x (20 x 3 mm)
Tightening torque	Control circuit : 1.2 N.m Power circuit : 10 N.m
Operating time	5...15 ms opening 23...35 ms closing
Mechanical durability	10 Mcycles
Operating rate	2400 cyc/h at <= 55 °C

Complementary

Control circuit voltage limits	0.35...0.55 U _c at 55 °C drop-out 50/60 Hz 0.85...1.1 U _c at 55 °C operational 50/60 Hz
Inrush power in VA	550 VA at 20 °C (cos φ 0.3) 50 Hz
Hold-in power consumption in VA	45 VA at 20 °C (cos φ 0.3) 50 Hz
Heat dissipation	12...16 W

Environment

IP degree of protection	IP2x front face with shrouds (ordered separately) conforming to VDE 0106 IP2x front face with shrouds (ordered separately) conforming to IEC 60529
Protective treatment	TH
Ambient air temperature for operation	-5...55 °C
Ambient air temperature for storage	-60...80 °C
Permissible ambient air temperature around the device	-40...70 °C
Operating altitude	3000 m without derating in temperature
Mechanical robustness	Shocks contactor closed 15 Gn for 11 ms Shocks contactor open 9 Gn for 11 ms Vibrations contactor closed 6 Gn, 5...300 Hz Vibrations contactor open 2 Gn, 5...300 Hz
Height	162 mm
Width	163.3 mm
Depth	171 mm
Product weight	3.43 kg

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0843 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Available Download End Of Life Manual