


Simaran

ردیف	مدل	مشخصات فنی	تصویر	قیمت مصرف کننده (ریال)
		IP Camera		
1	SM-IP2G600WF-D   Smart Dual Light	Wi-Fi PT Camera Up to 30m (based on actual environment) 1/3" CMOS Sensor/ 2MP(20FPS) /4 mm fixed Lens/2Stream/S+265/H.265 DWDR/ 8m White light view distance; 15m IR view distance/ 0.02Lux@ F2.0 /Smart IR 3D DNR, HLC, BLC,AWB,AGC, Defog,Privacy Mask Surge Protection / 5VDC, Built-in Mic, Built-in Speaker SD Card Max 512GB, Auto Tracking Smart Alarm/ONVIF/Reset Button/P2P/Plastic	  	72,500,000
2	SM-IP2G402AKD   Dual Light	1/3" CMOS Sensor/ 2MP(25FPS) / 4 mm fixed Lens/2Stream/S+265/H.265/ DWDR/15m White light view distance; 30m IR view distance/ 0.02Lux@ F1.6 /Smart IR / built-in MIC/ 3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask/Motion detection 1*RJ-45 (10/100 Base-T),POE/ONVIF/Surge Protection IP67 Plastic	 	63,000,000
3	SM-IP2G501AKD   Dual Light	1/3" CMOS Sensor/ 2MP(25FPS) / 2.8 mm fixed Lens/2Stream/S+265/H.265/ DWDR/15m White light view distance; 30m IR view distance/ 0.02Lux@ F1.6/Smart IR / built-in MIC/ 3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask,Motion detection 1*RJ-45 (10/100 Base-T) ,POE/ONVIF/Surge Protection/ Plastic	 	63,000,000
4	SM-IP2G250OS 	2MP IR Omni Camera 1/3" CMOS Sensor/ 2MP(25FPS) / 2.8 mm fixed Lens/2Stream/S+265/H.265/ DWDR/ 50m IR view distance/ 0.02Lux@ F1.6 /Smart IR / built- in MIC/ 3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask/ Motion detection/ Surge Protection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P IP67 Plastic	  	156,000,000
5	SM-IP2G414SPS1-WS  Polar Day	1/2.9" CMOS Sensor/2MP(25FPS) / 2.8 mm fixed Lens/2Stream/S+265/H.265/ True WDR 120dB/Super Starlight /15m White light view distance/ 0.0002Lux@ F1.0 /Smart IR/ built-in MIC/ 3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask/Surge Protection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P IP67 (Metal+ Plastic) Video Analytics: Smart Alarm(SMD1.0)	    	133,000,000
6	SM-IP2G513SPS1-WS  Polar Day	1/2.9" CMOS Sensor/2MP(25FPS) / 2.8 mm fixed Lens/2Stream/S+265/H.265/ True WDR 120dB/Super Starlight /15m White light view distance/ 0.0002Lux@ F1.0 /Smart IR/ built-in MIC/ 3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask/Surge Protection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P IP66 (Metal+ Plastic) Video Analytics: Smart Alarm(SMD1.0)	    	133,000,000

7	SM-IP4G414STS1(2.8)  Smart Dual Light	1/3" CMOS Sensor/ 4MP(25FPS) / 2.8mm fixed Lens/2Stream/S+265/H.265/ DWDR/15m White light view distance; 30m IR view distance/ 0.02Lux@ F1.6 /Smart IR/ built-in MIC/ 3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask/Surge Protection 1*RJ-45 (10/100 Base-T) , POE/ONVIF/P2P IP67 (Metal+ Plastic) Video Analytics: Smart Alarm (human and vehicle detection) SMD1.0	 	116,000,000
8	SM-IP4G414STS1(4)  Smart Dual Light	1/3" CMOS Sensor/ 4MP(25FPS) / 4mm fixed Lens/2Stream/S+265/H.265/ DWDR/15m White light view distance; 30m IR view distance/ 0.02Lux@ F1.6 /Smart IR/ built-in MIC/ 3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask/Surge Protection 1*RJ-45 (10/100 Base-T) , POE/ONVIF/P2P IP67 (Metal+ Plastic) Video Analytics: Smart Alarm (human and vehicle detection) SMD1.0	 	115,000,000
9	SM-IP4G513STS1  Smart Dual Light	1/3" CMOS Sensor/ 4MP(25FPS) / 2.8mm fixed Lens/2Stream/S+265/H.265/ DWDR/15m White light view distance; 30m IR view distance/ 0.02Lux@ F1.6 /Smart IR/ built-in MIC/ 3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask/Surge Protection 1*RJ-45 (10/100 Base-T) , POE/ONVIF/P2P IP66 (Metal+ Plastic) Video Analytics: Smart Alarm (human and vehicle detection) SMD1.0	 	115,000,000
10	SM-IP6G414STS1  Smart Dual Light	1/2.7" CMOS Sensor/ 6MP(25FPS) / 2.8 mm fixed Lens/2Stream/S+265/H.265/ DWDR/15m White light view distance; 30m IR view distance/ 0.02Lux@ F1.6 /Smart IR/ built-in MIC/ 3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask/Surge Protection 1*RJ-45 (10/100 Base-T) , POE/ONVIF/P2P IP67 (Metal+ Plastic) Video Analytics: Smart Alarm (human and vehicle detection) SMD1.0	 	160,000,000
11	SM-IP6G513STS1  Smart Dual Light	1/2.7" CMOS Sensor/ 6MP(25FPS) / 2.8 mm fixed Lens/2Stream/S+265/H.265/ DWDR/15m White light view distance; 30m IR view distance/ 0.02Lux@ F1.6 /Smart IR/ built-in MIC/ 3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask/Surge Protection 1*RJ-45 (10/100 Base-T) , POE/ONVIF/P2P IP66 (Metal+ Plastic) Video Analytics: Smart Alarm (human and vehicle detection) SMD1.0	 	160,000,000
12	SM-IP5G414LTS2-WS  Smart Dual Light	1/2.7" CMOS Sensor/ 5MP(25FPS) / 2.8 mm fixed Lens/2Stream/S+265/H.265/ True WDR 120dB/Starlight/15m White light distance; 50m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC/ ROI, 3D DNR, HLC, BLC, AWB, AGC, ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) , POE/12VDC/ONVIF/P2P, Support Micro SD Card up to 512GB, IP67 (Metal+Plastic) Video Analytics: SMD2.0 (Human/Vehicle Classification); Tripwire,Perimeter	 True WDR Starlight  	191,000,000
13	SM-IP5G428LTS2-WS  Smart Dual Light	1/2.7" CMOS Sensor/ 5MP(25FPS) / 2.8 mm fixed Lens/2Stream/S+265/H.265/ True WDR 120dB/Starlight/ 15m White light distance; 80m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC/ ROI, 3D DNR, HLC, BLC, AWB, AGC, ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) , POE/12VDC/ONVIF/P2P, Support Micro SD Card up to 512GB, IP67 Metal Video Analytics: SMD2.0 (Human/Vehicle Classification); Tripwire,Perimeter	 True WDR Starlight  	240,000,000

14	SM-IP5G513LTS2-WS  Smart Dual Light	1/2.7" CMOS Sensor/ 5MP(25FPS) / 2.8 mm fixed Lens/2Stream/S+265/H.265/ True WDR 120dB/Starlight/ 15m White light distance; 30m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC / ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) , POE /12VDC/ONVIF/P2P, Support Micro SD Card up to 512GB, IP67 (Metal+Plastic) Video Analytics: SMD2.0 (Human/Vehicle Classification); Tripwire,Perimeter	 True WDR Starlight  	192,500,000
15	SM-IP5G513LTS2-WSI  Smart Dual Light	1/2.7" CMOS Sensor/ 5MP(25FPS) / 2.8 mm fixed Lens/2Stream/S+265/H.265/ True WDR 120dB/Starlight/ 10m White light distance; 30m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC / ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) , POE /12VDC/ONVIF/P2P, Support Micro SD Card up to 512GB, IP67,IK10 (Metal+Plastic) Video Analytics: SMD2.0 (Human/Vehicle Classification); Tripwire,Perimeter	 True WDR Starlight IK10  	193,500,000
16	SM-IP5G428LTS2Z-WS  Smart Dual Light	1/2.7" CMOS Sensor/ 5MP(25FPS) / 2.7~13.5mm Motorized Lens/2Stream/S+265/H.265/ True WDR 120dB/Starlight/ 15m White light distance; 80m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC / ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) , POE /12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 1/1, Support Micro SD Card up to 512GB, IP67 Metal Video Analytics: SMD2.0 (Human/Vehicle Classification); Tripwire,Perimeter	 True WDR Starlight  	315,000,000
17	SM-IP5G527LTS2Z-WSI  Smart Dual Light	1/2.7" CMOS Sensor/ 5MP(25FPS) / 2.7~13.5mm Motorized Lens/2Stream/S+265/H.265/ True WDR 120dB/Starlight/ 10m White light distance; 30m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC / ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) , POE /12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 1/1, Support Micro SD Card up to 512GB, IP67,IK10 Metal Video Analytics: SMD2.0 (Human/Vehicle Classification); Tripwire,Perimeter	 True WDR Starlight IK10  	315,000,000
18	SM-IP8G424LTS2-WS  Smart Dual Light	1/2.8" CMOS Sensor/ 8MP(20FPS) / 2.8 mm fixed Lens/3Stream/S+265/H.265/Motion JPEG True WDR 120dB/Starlight/ 15m White light distance; 50m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC / ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection/ Corridor Mode 1*RJ-45 (10/100 Base-T) , POE /12VDC/ONVIF/P2P, Support Micro SD Card up to 512GB, IP67 Metal Video Analytics: SMD2.0 (Human/Vehicle Classification); Tripwire,Perimeter	 True WDR Starlight  	280,000,000
19	SM-IP8G523LTS2-WS  Smart Dual Light	1/2.8" CMOS Sensor/ 8MP(20FPS) / 2.8 mm fixed Lens/3Stream/S+265/H.265/Motion JPEG True WDR 120dB/Starlight/ 15m White light distance; 30m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC / ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection/ Corridor Mode 1*RJ-45 (10/100 Base-T) , POE /12VDC/ONVIF/P2P, Support Micro SD Card up to 512GB, IP67 Metal Video Analytics: SMD2.0 (Human/Vehicle Classification); Tripwire,Perimeter	 True WDR Starlight  	280,000,000

20	SM-IP8G428LTS2Z-WS Smart Dual Light	1/2.8" CMOS Sensor/ 8MP(20FPS) / 2.7~13.5mm Motorized Lens/3Stream/S+265/H.265/Motion JPEG True WDR 120dB/Starlight/ 15m White light distance; 80m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC/ ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection/ Corridor Mode 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 1/1, Support Micro SD Card up to 512GB, IP67 Metal Video Analytics: SMD2.0 (Human/Vehicle Classification);Tripwire,Perimeter	True WDR Starlight  	410,000,000
21	SM-IP4G418PDSZ-WSLR(2.8-12) Dual Light	4MP LPR Network Camera 1/1.8" CMOS Sensor/ 4MP(25FPS) / 2.8~12mm Motorized Lens/3Stream/S+265/H.265/Motion JPEG True WDR 120dB/Starlight/ 40m White light distance; 30m IR distance/ 0.002Lux@ F1.3~F2.2 /Smart IR/ built-in MIC & Speaker ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 2/1, RS485, Support Micro SD Card up to 512GB, IP67 (Metal+Plastic) SMART Functions(Pro)- Supports license plate recognition-Early Warning(EW)- SMD (Human/Vehicle Classification)	True WDR Starlight LPR  	Call
22	SM-IP4G418PDSZ-WSLR(8-32) Dual Light	4MP LPR Network Camera 1/1.8" CMOS Sensor/ 4MP(25FPS) / 8~32mm Motorized Lens/3Stream/S+265/H.265/Motion JPEG True WDR 120dB/Starlight/ 60m White light distance; 60m IR distance/ 0.002Lux@ F1.6~F1.7 /Smart IR/ built-in MIC & Speaker ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 2/1, RS485, Support Micro SD Card up to 512GB, IP67 (Metal+Plastic) SMART Functions(Pro)- Supports license plate recognition-Early Warning(EW)- SMD (Human/Vehicle Classification)	True WDR Starlight LPR  	Call
23	SM-IP5G418PDS-WST Dual Light	5MP Thermal Network Camera 1/2.7" CMOS Sensor/Optical:5MP(25FPS) ,Thermal:720P Thermal:7mm;Optical:6mm fixed Lens/ 2Stream/S+265/H.265/Motion JPEG True WDR 120dB/Starlight/ 15m White light distance; 50m IR distance/ 0.002Lux@Thermal:F1.2; Optical:F1.6 /Smart IR/ built-in MIC & Speaker ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 2/1, RS485, Support Micro SD Card up to 512GB, IP67 (Metal+Plastic) SMART Functions(Lite) -Thermal SMD (Human/Vehicle Classification)	True WDR Starlight Fire Detection  	Call
24	SM-IP5G424PDS-WSFC Dual Light	5MP Face Capture Network Camera 1/2.7" CMOS Sensor/ 5MP(25FPS) / 1080P 50fps 4mm fixed Lens/3Stream/S+265/H.265/Motion JPEG True WDR 120dB/Starlight/ 15m White light distance; 50m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC & Speaker ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection/ Corridor Mode 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 1/1, Support Micro SD Card up to 512GB, IP67 Metal SMART Functions(Lite)- Face Capture- Early Warning(EW) SMD (Human/Vehicle Classification)	True WDR Starlight Face Capture  	295,000,000

25	SM-IP5G523PDS-WSFC PRO Dual Light	5MP Face Capture Network Camera 1/2.7" CMOS Sensor/ 5MP(25FPS) / 1080P 50fps 2.8mm fixed Lens/3Stream/S+265/H.265/Motion JPEG True WDR 120dB/Starlight/ 15m White light distance; 30m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC & Speaker ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection/ Corridor Mode 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 1/1, Support Micro SD Card up to 512GB, IP66 Metal SMART Functions(Lite)- Face Capture- Early Warning(EW) SMD (Human/Vehicle Classification)	True WDR Starlight Face Capture  SMD 	295,000,000
26	SM-IP8G418P2S-WSP PRO Polar Day	8MP Polar day Panoramic Network Camera Dual 1/2.7" CMOS Sensor/ 8MP(25FPS) 2.8mm fixed Lens/2Stream/S+265/H.265/Motion JPEG True WDR 120dB/Super Starlight/ 15m White light distance/ 0.0001Lux@ F1.0 /built-in MIC & Speaker ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 1/1, Support Micro SD Card up to 512GB, IP67 (Metal+Plastic) SMART Functions(Lite)- Early Warning(EW) SMD (Human/Vehicle Classification)	True WDR Super starlight Panoramic  SMD 	515,000,000
27	HISILICON SM-IP842PH-SFR PRO IR	8MP 180° Panoramic Network Camera 1/2.8" SONY(4pcs*2MP) progressive scan CMOS Sensor / 8MP(4096 × 1800) (25FPS) 3.2mm fixed Lens x 4 /3Streams/H.265+/H.264+ DWDR/ Starlight/ 20m IR/ 0.008 lux/ 12V DC/ PoE/ ONVIF 1/1 CH Audio In/Output , 1/1 CH Alarm In/Output, SD Card Max 256GB, RS485 3D DNR, HLC, BLC, defog, EIS, IP67, IK10 SMART Functions / Supports face detection and comparison	Face Recognition Starlight  Panoramic	585,000,000
28	SM-IPS27MFP PRO Dual Light	Face Panel & Access Control Terminal Standalone/7 inch LCD screen/Face Liveness Detection 1/2.8" progressive scan CMOS Sensor/ 2MP(25FPS) 4.3 mm x 2 lens/3Streams/H265+/H264+/ WDR(72dB), 3D DNR, HLC, BLC, defog, DC12V/1A Face Recognition Distance: 1.5m Face Picture Database: 10,000 White Light Distance: 1m soft light IR Light Distance: 2m 1 Built-in MIC/Built-in Speaker - 1/1 CH Alarm In/Output 1CH RJ45-1CH Wiegand-1CH Lock-1CH Door contact input-Exit Buttonx1-Tamper Buttonx1-Built-in card reader door opening modes (Only card, Only face recognition, card and face recognition, card Or face recognition) Card Type: Mifare Card/Desfire Card/FM1208 Card/Gicard SMART Functions /Supports face detection and comparison	Card Reader Door Control  Face Recognition 	130,000,000
29	SM-IP2G614PS-23X-WS PRO IR	2MP 23X IR PTZ Camera 1/2.8" CMOS Sensor/ 2MP(25FPS) /5mm~115mm Motorized Lens/3Stream/23X Optical Zoom/S+265/H.265/Motion JPEG True WDR 120dB/ Starlight/ 150m IR view distance/ 0.001Lux@ F1.5~F3.0 /Smart IR ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog, Demist/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P, SD Card Max 512GB/ Power-off Memory/ IP66 (Metal+plastic) Video Analytics: Tripwire; Double Tripwire; Perimeter; Object Abandon; Object Missing;Heatmap; Video Abnormal; SMD (Human/Vehicle Classification)	True WDR Starlight  	635,000,000

30	SM-IP4G624PS-25X-WSFC PROIR	4MP Face Capture 25X IR PTZ Camera 1/2.7" CMOS Sensor/ 4MP(25FPS) /4.8mm~120mm Motorized Lens/ 3Stream/ 25X Optical Zoom/ S+265/H.265/Motion JPEG True WDR 120dB/ Starlight/ 150m IR view distance/ 0.001Lux@ F1.67~F3.67 /Smart IR ROI, 3D DNR, HLC, BLC,AWB,AGC, ANR, Defog, Demist/ Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 1/1, SD Card Max 512GB/ Power-off Memory/ IP66 Metal SMART Functions(Pro)- Face Capture- Auto-Tracking SMD (Human/Vehicle Classification)	True WDR Starlight Auto Tracking Face Capture 	1,160,000,000
31	SM-IP5G614PS-23X-WSFC PROIR	5MP Face Capture 23X IR PTZ Camera 1/2.7" CMOS Sensor/ 5MP(25FPS) /5mm~115mm Motorized Lens/3Stream/23X Optical Zoom/S+265/H.265/Motion JPEG True WDR 120dB/ Starlight/ 150m IR view distance/ 0.001Lux@ F1.67~F3.67 /Smart IR ROI, 3D DNR, HLC, BLC,AWB,AGC, ANR, Defog, Demist/ Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 1/1, SD Card Max 512GB/ Power-off Memory/ IP66 (Metal+Plastic) SMART Functions(Pro)- Face Capture SMD (Human/Vehicle Classification)	True WDR Starlight Face Capture 	990,000,000
32	SM-IP5G626PS-30X-WSFC PROIR	5MP Face Capture 30X IR PTZ Camera 1/2.7" CMOS Sensor/ 5MP(25FPS) /4.7mm~141mm Motorized Lens/ 3Stream/ 30X Optical Zoom/S+265/H.265/Motion JPEG True WDR 120dB/ Starlight/ 200m IR view distance/ 0.001Lux@ F1.6~F4.3 /Smart IR ROI, 3D DNR, HLC, BLC,AWB,AGC, ANR, Defog, Demist/ Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/24V:AC&DC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 8/2, RS-485, SD Card Max 512GB/ Power-off Memory/ IP66 Metal SMART Functions(Pro)- Face Capture- Auto-Tracking SMD (Human/Vehicle Classification)	True WDR Starlight Auto Tracking Face Capture 	Call
33	SM-IP6P4G616PDS-25X-WSFC PRO Polar Day	6MP 25X Polar Day Panoramic AEW PTZ Camera Panorama: 1/1.8" CMOS Sensor/6MP(25FPS)/2.8mm fixed Lens/2Streams/DWDR,Super starlight/30m White light distance/0.0001lux @ F1.0 Detail: 1/2.7" CMOS Sensor/4MP(25FPS)/4.8mm~120mm Motorized Lens/3Streams/25X Optical Zoom/ True WDR 120dB/ Starlight/30m White light distance; 150m IR distance/0.001Lux@ F1.67~F3.67 S+265/H.265/Motion JPEG/ ROI, 3D DNR, HLC, BLC,AWB,AGC, ANR, Defog, Demist/ Smart IR/ Privacy Mask/ Surge Protection/ Motion Detection/ 1*RJ-45 (10/100/1000 Base-T) ,POE/24V:AC&DC/ONVIF/P2P built-in Speaker, Audio I/O: 1/1, Alarm I/O: 2/1, SD Card Max 512GB/ Power-off Memory/ IP66 (Metal+plastic) SMART Functions(Pro)- Face Capture- Auto-Tracking- Auto Early Warning(AEW) SMD (Human/Vehicle Classification)	True WDR AEW Super starlight Panoramic Face Capture 	Call
		NVR		
34	SM-N64G10AK2-4PE AK	4CH input - Record 6MP@25fps - 4*100M RJ45 PoE ports S+265,H.265,S+264 Bandwidth (Input 60Mbps/Output 40Mbps) Support IPC Alarm input/ SATA × 1, max 6T / HDMI-VGA/USB2.0×2/P2P/ ONVIF/RTSP/DHCP/DDNS/ RJ45 100Mbps × 1,cloud upgrade Motion Detection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی		108,500,000

35	SM-N68G10AK2-8PE AK	8CH input - Record 6MP@25fps - 8*100M RJ45 PoE ports S+265 ,H.265,S+264 Bandwidth (Input 60Mbps/Output 40Mbps) Support IPC Alarm input/ SATA × 1, max 6T / HDMI-VGA/USB2.0×2/P2P/ ONVIF/RTSP/DHCP/DDNS/ RJ45 100Mbps × 1,cloud upgrade Motion Detection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی		138,000,000
36	SM-N610G10S-8PE	10CH input - Record 6MP@25fps - 8*100M RJ45 PoE ports S+265,H.265,S+264 Bandwidth (Input 60Mbps/Output 40Mbps) Support IPC Alarm input/ SATA × 1, max 6T / 4K HDMI-VGA; USB2.0×2/P2P/ ONVIF/RSTP/DHCP/DDNS/ RJ45 100Mbps × 1,cloud upgrade Motion Detection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی		145,000,000
37	SM-N85G10L	5CH input - Record 8MP@25fps /S+265,H.265,S+264/ Bandwidth (Input 60Mbps/Output 40Mbps) Support IPC Alarm input/SATA × 1, max 8T / 4K HDMI-VGA/USB2.0×2/P2P/ONVIF/RTSP/DHCP/DDNS/ RJ45 100Mbps × 1, cloud upgrade- Dual Stream Record SMART Function(AI by Camera); Human/Vehicle Classification قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	VCA  Dual Stream Recording	100,000,000
38	SM-N810G10L	10CH input - Record 8MP@25fps /S+265,H.265,S+264/ Bandwidth (Input 60Mbps/Output 40Mbps) Support IPC Alarm input/SATA × 1, max 8T / 4K HDMI-VGA/USB2.0×2/P2P/ONVIF/RTSP/DHCP/DDNS/ RJ45 100Mbps × 1, cloud upgrade- Dual Stream Record SMART Function(AI by Camera); Human/Vehicle Classification قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	VCA  Dual Stream Recording	112,000,000
39	SM-N810G11L	10CH input - Record 8MP@25fps /S+265,H.265,S+264/ Bandwidth (Input 60Mbps/Output 40Mbps) Support IPC Alarm input/ 1-RCA Audio Output / SATA × 1, max 10T / 4K HDMI-VGA/USB2.0×2/P2P/ ONVIF/RTSP/DHCP/DDNS RJ45 100Mbps × 1, cloud upgrade- Dual Stream Record SMART Function(AI by Camera); Human/Vehicle Classification قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	VCA  Dual Stream Recording	155,000,000
40	SM-N820G11LS	20CH input - Record 8MP@25fps / S+265,H.265,S+264/ Bandwidth (Input 100Mbps/Output 80Mbps) Support IPC Alarm input/ 1-ch Audio Output / SATA × 1, max 10T/ 4K HDMI-VGA /USB2.0×2 P2P/ ONVIF/RTSP/DHCP/DDNS RJ45 100Mbps × 1, cloud upgrade- Dual Stream Record SMART Function(AI by Camera): Supports People Counting; Face Detection (Gender; Age; Glasses; Face Mask; Body Temp); Fire Detection; Temperature Measurement; Human/Vehicle Classification قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	VCA Fire Detection  Dual Stream Recording Face Detection	206,000,000
41	SM-N1610G12L-AI	10CH input - Record 16MP@25fps / S+265,H.265,S+264/ Bandwidth (Input 100Mbps/Output 80Mbps) Support Alarm I/O: 4Ch input,1Ch Output/ Audio I/O: 1-ch input,1-ch RCA Output SATA × 1, max 10T/ 4K HDMI-VGA /USB2.0×2/ P2P/ ONVIF/RTSP/DHCP/DDNS RJ45 100Mbps × 1, cloud upgrade- Dual Stream Record SMART Function(AI by Camera & NVR): Supports People Counting; Face Recognition (Gender; Age; Glasses; Face Mask; Body Temp); Fire Detection; Temperature Measurement; Human/Vehicle Classification; SMD قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	DeeP Learning Algorithm Fire Detection  Dual Stream Recording Face Recognition	230,000,000

42	SM-N1620G12L-AI	20CH input - Record 16MP@25fps / S+265,H.265,S+264/ Bandwidth (Input 100Mbps/Output 80Mbps) Support Alarm I/O: 4Ch input,1Ch Output/ Audio I/O: 1-ch input,1-ch RCA Output SATA × 1, max 10T/ 4K HDMI-VGA /USB2.0×2/ P2P/ ONVIF/RTSP/DHCP/DDNS RJ45 100Mbps × 1, cloud upgrade- Dual Stream Record SMART Function(AI by Camera & NVR): Supports People Counting; Face Recognition (Gender; Age; Glasses; Face Mask; Body Temp); Fire Detection; Temperature Measurement; Human/Vehicle Classification; SMD قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 DeeP Learning Algorithm  Fire Detection  Dual Stream Recording  Face Recognition 	255,000,000
43	SM-N1620G22L-AI	20CH input - Record 16MP@25fps / S+265,H.265,S+264/ Bandwidth: Input 160Mbps(AI on:120Mbps)/Output 80Mbps Support Alarm I/O: 4Ch input,1Ch Output/ Audio I/O: 1-ch input,1-ch RCA Output SATA × 2, max 10T/ 4K HDMI-VGA /USB2.0×2/ P2P/ ONVIF/RTSP/DHCP/DDNS RJ45 1000Mbps × 1, cloud upgrade- Dual Stream Record SMART Function(AI by Camera & NVR): Supports People Counting; Face Recognition (Gender;Age; Glasses;Face Mask; Body Temp); Fire Detection; Temperature Measurement; Human/Vehicle Classification; SMD قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 DeeP Learning Algorithm  Fire Detection  Dual Stream Recording  Face Recognition 	412,000,000
44	SM-N1632G22L-AI	32CH input - Record 16MP@25fps / S+265,H.265,S+264/ Bandwidth: Input 160Mbps(AI on:120Mbps)/Output 80Mbps Support Alarm I/O: 4Ch input,1Ch Output/ Audio I/O: 1-ch input,1-ch RCA Output SATA × 2, max 10T/ 4K HDMI-VGA /USB2.0*2/ P2P/ ONVIF/RTSP/DHCP/DDNS RJ45 1000Mbps × 1, cloud upgrade SMART Function(AI by Camera & NVR): Supports People Counting; Face Recognition (Gender; Age; Glasses; Face Mask; Body Temp); Fire Detection; Temperature Measurement; Human/Vehicle Classification; SMD قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 DeeP Learning Algorithm  Fire Detection  Face Recognition 	488,000,000
45	SM-N1640G22P-AI	40CH input - Record 16MP@25fps / S+265,H.265,S+264/ Bandwidth: Input 400Mbps(AI on: 200Mbps)/ Output 400Mbps(AI on: 200Mbps) Support Alarm I/O: 16Ch input,4Ch Output/ Audio I/O: 1-ch input,1-ch RCA Output SATA × 2, max 10T/ 4K HDMI-VGA /1×USB2.0; 1×USB3.0/ RS485×1 / RS232×1/ P2P/ONVIF/RTSP/DHCP/DDNS RJ45 1000Mbps × 2, cloud upgrade- Dual Stream Record SMART Function(AI by Camera & NVR): Supports License Plate Recognition; People Counting; Face Recognition (Gender; Age; Glasses; Face Mask; Body Temp); Fire Detection; Temperature Measurement; Human/Vehicle Classification; SMD قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 DeeP Learning Algorithm  LPR  Fire Detection  Dual Stream Recording  Face Recognition 	800,000,000
46	SM-N1640G42P-AI	40CH input - Record 16MP@25fps / S+265,H.265,S+264/ Bandwidth: Input 400Mbps(AI on: 200Mbps)/ Output 400Mbps(AI on: 200Mbps) Support IPC Alarm input/ Audio I/O: 1-ch input,1-ch RCA Output SATA × 4, max 10T/ Support RAID0, RAID1, RAID5, RAID6, RAID10/ 4K HDMI-VGA /1×USB2.0; 1×USB3.0/ P2P/ONVIF/RTSP/DHCP/DDNS RJ45 1000Mbps × 2, cloud upgrade- Dual Stream Record SMART Function(AI by Camera & NVR); Supports License Plate Recognition; People Counting; Face Recognition (Gender; Age; Glasses; Face Mask; Body Temp); Fire Detection; Temperature Measurement; Human/Vehicle Classification; SMD قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 DeeP Learning Algorithm  LPR  Fire Detection  Dual Stream Recording  RAID  Face Recognition 	950,000,000

47	SM-N1640G82P-AI PRO	40CH input - Record 16MP@25fps / S+265,H.265,S+264/ Bandwidth: Input 400Mbps(AI on: 320Mbps)/ Output 400Mbps(AI on: 200Mbps) Support Alarm I/O: 16Ch input,4Ch Output/ Audio I/O: 1-ch input,1-ch BNC Output SATA × 8, max 24T; 1×eSATA/ Support RAID0, RAID1, RAID5, RAID6, RAID10, RAID50, RAID60 / 4K HDMI×2-VGA×2/ 2×USB2.0; 1×USB3.0/ RS485×2 / RS232×1/ P2P/ONVIF/RTSP/DHCP/DDNS RJ45 1000Mbps × 2, cloud upgrade- Dual Stream Record SMART Function(AI by Camera & NVR): Supports License Plate Recognition; People Counting; Face Recognition (Gender; Age; Glasses; Face Mask; Body Temp); Fire Detection; Temperature Measurement; Human/Vehicle Classification; SMD قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	DeeP Learning Algorithm LPR Fire Detection  Dual Stream Recording RAID Face Recognition	Call
48	SM-N1680G82P-AI PRO	80CH input - Record 16MP@25fps / S+265,H.265,S+264/ Bandwidth: Input 400Mbps(AI on: 320Mbps)/ Output 400Mbps(AI on: 200Mbps) Support Alarm I/O: 16Ch input,4Ch Output/ Audio I/O: 1-ch input,1-ch BNC Output SATA × 8, max 24T; 1×eSATA/ Supports RAID0, RAID1, RAID5, RAID6, RAID10, RAID50, RAID60 / 4K HDMI×2- VGA×2 / 2×USB2.0; 1×USB3.0/ RS485×2 / RS232×1/ P2P/ONVIF/RTSP/DHCP/DDNS RJ45 1000Mbps × 2, cloud upgrade- Dual Stream Record SMART Function(AI by Camera & NVR): Supports License Plate Recognition; People Counting; Face Recognition (Gender;Age;Glasses;Face Mask; Body Temp); Fire Detection; Temperature Measurement; Human/Vehicle Classification; SMD قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	DeeP Learning Algorithm LPR Fire Detection  Dual Stream Recording RAID Face Recognition	Call
کلیه محصولات لیست با گارانتی شرکت سیماران می باشند				
 simaran_camera			 cctv_simaran	