Simaran

ردیف	مدل	مشخصات فنی	تصویر	قیمت مصرف کننده (ریال)
		Dual Light- HD Camera		
1	SM-5HD2362DMA	1/2.7" Progressive CMOS 5MP(2608*1960)@20fps/4MP-2MP@25fps TVI,AHD,CVI,CVBS/3.6mm fixed Lens/DWDR/0.04 Lux@ F1.0 , Dual light camera 20m Warm light view distance; 30m IR view distance 2D DNR,AWB, HLC, BLC,AGC,COC 12VDC/1CH built-in MIC IP67(Metal)		89,000,000
2	SM-5HD1282DMA	1/2.7" Progressive CMOS 5MP(2608*1960)@20fps/4MP-2MP@25fps TVI,AHD,CVI,CVBS/2.8mm fixed Lens/DWDR/0.04 Lux@ F1.0 , Dual light camera 20m Warm light view distance; 30m IR view distance 2D DNR,AWB, HLC, BLC,AGC,COC 12VDC/1CH built-in MIC IP67(Metal)		89,000,000
3	SM-2HD2362DMA	1/3" Progressive CMOS 2MP(1920*1080)@25fps TVI,AHD,CVI,CVBS/3.6mm fixed Lens/DWDR/0.08 Lux@ F1.0 , Dual light camera 20m Warm light view distance; 30m IR view distance 3D DNR,AWB, HLC, BLC,AGC,COC 12VDC/1CH built-in MIC IP67(Metal)		71,000,000
4	SM-2HD1282DMA	1/3" Progressive CMOS 2MP(1920*1080)@25fps TVI,AHD,CVI,CVBS/2.8mm fixed Lens/DWDR/0.08 Lux@ F1.0 , Dual light camera 20m Warm light view distance; 30m IR view distance 3D DNR,AWB, HLC, BLC,AGC,COC 12VDC/1CH built-in MIC IP67(Metal)		71,000,000
		XVR		
5	SM-5GXN401L	4CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite, 1080P, 720P real time preview & Record 5MP Lite@20fps, 4MP Lite/1080P/720P@25fps(PAL)/ 1CH(Up to 5CH) IP Up to 2MP(25fps) H.265 /HDD SATA×1, up to 10TB/HDMI/USB 2.0 × 2/ P2P(ScamVU)/DDNS/Network RJ45 100Mbps × 1 - Max 20/32 Mbps incoming/Outgoing bandwidth Support coaxial audio- Without web Motion Detection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی		118,000,000
6	SM-5GXN801L	8CH TVI&AHD&CVI: 5MP Lite@12fps, 1080N/720P real time preview & Record 5MP Lite@12fps, 1080N/720P:25fps/ 2CH(Up to 10CH) IP Up to 2MP(25fps) H.265/HDD SATA×1, up to 10TB HDMI/USB2.0*2/P2P(ScamVU)/DDNS/ Network RJ45 100Mbps × 1 - Max 40/56 Mbps incoming/Outgoing bandwidth Support coaxial audio- Without web Motion Detection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی		131,600,000

7	SM-5GXN1601L	16CH TVI&AHD&CVI: 5MP Lite@12fps, 4MP Lite@15fps, 1080N,720P real time preview & Record 5MP Lite@6fps, 4MP Lite@9fps, 1080N@15fps, 720P@18fps/ 4CH IP Up to 2MP(25fps) H.265/HDD SATA×1, up to 10TB HDMI/USB2.0*2/P2P(ScamVU)/DDNS/ Network RJ45 100Mbps × 1 - Max 16/64 Mbps incoming/Outgoing bandwidth Support coaxial audio Motion Detection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	AOC 	241,000,000
8	SM-5GXN441M-AI Smart Dual Light	4CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite,1080P,720P real time preview & Record 5MP Lite@20fps, 4MP Lite,1080P,720P@25fps(PAL)/ 2CH(Up to 6CH) IP Up to 5MP(25fps) H.265/ 4 in-1 out Audio /HDD SATA×1, up to 10TB/ 4K HDMI-VGA-CVBS/USB 2.0 × 2/ RS485 × 1 /P2P(ScamVU)/DDNS/Network RJ45 100Mbps × 1 - Max 24/48 Mbps incoming/Outgoing bandwidth Support coaxial audio AI Functions:Perimeter Intrusion Detection/Line Crossing Detection/Human&Vehicle Detection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	AOC SMD 	182,000,000
9	SM-5GXN841M-AI Smart Dual Light	8CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite,1080P,720P real time preview & Record 5MP Lite@15fps, 4MP Lite@20fps,1080P@18fps,720P@25fps(PAL)/ 4CH (Up to 12CH) IP Up to 5MP(25fps) H.265/ 4 in-1 out Audio /HDD SATA×1, up to 10TB/ 4K HDMI-VGA-CVBS/USB 2.0 × 2/ RS485 × 1/ P2P(ScamVU)/DDNS/Network RJ45 100Mbps × 1 - Max 48/64 Mbps incoming/Outgoing bandwidth Support coaxial audio AI Functions:Perimeter Intrusion Detection/Line Crossing Detection/Human&Vehicle Detection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	AOC SMD 	236,000,000
10	SM-5GXN1641M-AI Smart Dual Light	16CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite,1080P,720P real time preview & Record 5MP Lite@12fps, 4MP Lite,1080P@15fps, 720P@25fps/ 4CH (Up to 20CH) IP Up to 5MP(25fps) H.265/ 4 in-1 out Audio/ HDD SATA×1, up to 10TB/ 4K HDMI-VGA/ USB 2.0*1, USB 3.0*1 /RS485 × 1 / P2P(ScamVU)/DDNS/Network RJ45 1000Mbps × 1 - Max 80/96 Mbps incoming/Outgoing bandwidth Support coaxial audio AI Functions :Perimeter Intrusion Detection/Line Crossing Detection/Human&Vehicle Detection/Face Recognition قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	AOC SMD  Face Recognition	540,000,000
11	SM-4KGXN441H-AI Smart Dual Light	4CH TVI&AHD&CVI: 4K@15fps; 5MP@20fps; 4MP,1080P,720P real time preview & Record 4K@7fps, 5MP@12fps, 4MP@15fps, 1080P@25fps/ 2CH (Up to 6CH) IP Up to 4K(25fps) H.265/ 4 in-1 out Audio/ 4 in-1 out Alarm HDD SATA×1, up to 10TB/ 4K HDMI-VGA-CVBS USB 2.0 × 2/ RS485 × 1/ P2P(ScamVU)/DDNS/Network RJ45 100Mbps × 1 - Max 36/48 Mbps incoming/Outgoing bandwidth Support coaxial audio AI Functions : Perimeter Intrusion Detection/Line Crossing Detection/Human&Vehicle Detection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	AOC SMD 	250,000,000

12	SM-4KGXN841H-AI Smart Dual Light	8CH TVI&AHD&CVI: 4K@15fps; 5MP@20fps; 4MP,1080P,720P real time preview & Record 4K@10fps, 5MP@14fps, 4MP@18fps, 1080P@25fps/ 4CH (Up to 12CH) IP Up to 4K(25fps) H.265/ 8 in-1 out Audio/ 8 in-1 out Alarm HDD SATA×1, up to 10TB/ 4K HDMI-VGA-CVBS/ USB 2.0 × 2/ RS485 × 1 / P2P(ScamVU)/DDNS/Network RJ45 100Mbps × 1 - Max 96/96 Mbps incoming/Outgoing bandwidth Support coaxial audio AI Functions:Perimeter Intrusion Detection/Line Crossing Detection/Human&Vehicle Detection/Face Recognition قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 Face Recognition	490,000,000
13	SM-4KGXN16162H-AI Smart Dual Light	16CH TVI&AHD&CVI: 4K@15fps; 5MP@20fps; 4MP,1080P,720P real time preview & Record 4K@10fps, 5MP@15fps, 4MP@20fps, 1080P@25fps/ 8CH(Up to 24CH) IP Up to 4K(25fps) H.265/ 16 in-1 out Audio/ 16 in-1 out Alarm/ HDD SATA×2, up to 10TB, ESATA× 1 / 4K HDMI-VGA-CVBS/USB 3.0×1; USB2.0×1 /RS485 × 1/ P2P(ScamVU)/DDNS/Network RJ45 100Mbps × 1 - Max 144/192 Mbps incoming/Outgoing bandwidth Support coaxial audio AI Functions:Perimeter Intrusion Detection/Line Crossing Detection/Human&Vehicle Detection/Face Recognition قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 Face Recognition	980,000,000
14	SM-5GXN3284P-AI Smart Dual Light	32CH TVI&AHD&CVI: 5MP Lite@20fps; 4MP Lite,1080P,720P real time preview & Record 5MP Lite@15fps, 4MP Lite@20fps, 1080P@15fps, 720P@25fps/ 4CH(Up to 32CH) IP Up to 5MP(25fps) H.265/ 8 in-1 out Audio/ 16 in-1 out Alarm/ HDD SATA× 4, up to 10TB, ESATA× 1 / 4K HDMI-VGA-CVBS/USB 3.0×1; USB2.0×1 /RS485 × 1/ P2P(ScamVU)/DDNS/Network RJ45 1000Mbps × 2 - Max 128/216 Mbps incoming/Outgoing bandwidth Support coaxial audio AI Functions: Perimeter Intrusion Detection/Line Crossing Detection/Region Detection/sound Detection/Human&Vehicle Detection/Face Recognition/video tempering قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 Face Recognition	1,140,000,000
کابل				
15	SM-C48U64P	کابل شبکه UTP CAT6 مغزی مس 0/48 8 رشته (هر رشته 1 عدد مفتول) - (4Pairs) 1 عدد حلقه 305 متری		1,560,000
16	SM-A52U64P	کابل شبکه UTP CAT6 مغزی آلومینیوم مسوار 0/52 8 رشته (هر رشته 1 عدد مفتول) - (4Pairs) 1 عدد حلقه 305 متری		780,000
دزدگیر				

17	SM-CP520	مرکز کنترل دزدگیر 4 زون با سیم + 1 زون بی سیم (با قابلیت گسترش) کنترل دستگاه از طریق تماس، پیامک و نرم افزار IOS و ANDROID 20 حافظه تلفن (GSM,SMS) 2 عدد خروجی قابل کنترل با پیام کوتاه و صوتی زون 24 ساعته و حالت نیمه فعال و دینگ دانگ و تاخیری 1 خروجی AUX جهت تغذیه تجهیزات دسترسی آسان به تنظیمات دستگاه از طریق پنل دزدگیر دسترسی به منو از طریق پسورد دارای سیستم هشدار سیگنال مزاحم		210,000,000
18	SM-SD440PR	چشمی دزدگیر حرکتی باسیم Nicera500 BP Sensor type ولتاژ کاری 9 الی 15 ولت 14 متر برد آشکار سازی 140 درجه زاویه آشکار سازی passive infrared دارای قابلیت تنظیم میزان حساسیت قابلیت تنظیم LED بصورت ON/OFF مجهز به ورودی Tamper دارای انتخاب NC - NO خروجی آلارم رله		22,000,000
19	SM-SD450PR	چشمی دزدگیر حرکتی باسیم HLI 968 Sensor type ولتاژ کاری 9 الی 15 ولت 14 متر برد آشکار سازی 140 درجه زاویه آشکار سازی passive infrared دارای قابلیت تنظیم میزان حساسیت قابلیت تنظیم LED بصورت ON/OFF مجهز به ورودی Tamper دارای انتخاب NC خروجی آلارم الکترونیکی		26,000,000
20	SM-D433WS1	چشمی دزدگیر حرکتی بیسیم به همراه باطری passive infrared (Nicera500 BP Sensor type) فرکانس کاری 433 مگاهرتز 14 متر برد آشکار سازی 140 درجه زاویه آشکار سازی قابلیت تنظیم زون , قابلیت کد دهی , دارای آنتن جهت افزایش برد ماژول - دارای کلید تست		29,000,000
21	SM-MD203S	چشمی دزدگیر حرکتی باسیم HLI 968 Sensor type D203S Sensor type ولتاژ کاری 9 الی 15 ولت 20 متر برد آشکار سازی 130 درجه زاویه آشکار سازی passive infrared دارای انتخاب NC-NE جهت تنظیم میزان حساسیت قابلیت تنظیم LED بصورت ON/OFF مجهز به ورودی Tamper خروجی آلارم الکترونیکی		18,100,000

کلیه محصولات لیست با گارانتی شرکت سیماران می باشند

simaran_camera

cctv_simaran