

Product data sheet

Specifications



circuit breaker Masterpact NW25H1 - 2500 A - 4 poles - drawout - w/o trip unit

48306

Main

| | |
|---------------------------|-------------------------------|
| Range of product | Masterpact NW |
| Product or component type | Basic frame |
| Device short name | Masterpact NW25 |
| Circuit breaker name | Masterpact NW25H1 |
| Poles description | 4P |
| Neutral position | Left |
| Network type | AC |
| Breaking capacity code | H1 |
| Suitability for isolation | Yes conforming to IEC 60947-2 |
| Utilisation category | Category B |

Complementary

| | |
|---|--|
| Network frequency | 50/60 Hz |
| Control type | Push-button |
| Mounting mode | Drawout |
| [In] rated current | 2500 A at 40 °C |
| [Ui] rated insulation voltage | 1000 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Uimp] rated impulse withstand voltage | 12 kV conforming to IEC 60947-2 |
| [Icm] rated short-circuit making capacity | 143 kA 525 V AC at 50/60 Hz 143 kA 690 V AC at 50/60 Hz |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Circuit breaker CT rating | 2500 A |
| Breaking capacity | 65 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 65 kA Icu at 690 V AC 50/60 Hz conforming to IEC 60947-2 65 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 65 kA Icu at 220...240 V AC 50/60 Hz conforming to IEC 60947-2 65 kA Icu at 380...415 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Ics] rated service breaking capacity | 65 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2 65 kA at 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Protection type | Without protection |
| Mechanical durability | 10000 cycles without maintenance conforming to IEC 60947-2 20000 cycles with maintenance conforming to IEC 60947-2 |

| | |
|---|---|
| Electrical durability | AC-3: 6000 cycles 440/690 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 2500 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 5000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 AC-23A: 2500 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 AC-23A: 5000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 |
| Connection pitch | 115 mm |
| [Icw] rated short-time withstand current | 65 kA 1 s conforming to IEC 60947-2 65 kA 3 s conforming to IEC 60947-2 |
| Maximum breaking time | 25 ms |
| Maximum closing response time | 70 ms |
| Height | 439 mm |
| Width | 556 mm |
| Depth | 394.5 mm |

Environment

| | |
|--|-----------------------------|
| Standards | IEC 60947-2 |
| Product certifications | ASTA |
| Pollution degree | 4 conforming to IEC 60664-1 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...85 °C |

Packing Units

| | |
|-------------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 49.501 kg |
| Package 1 Height | 30.5 cm |
| Package 1 width | 29.5 cm |
| Package 1 Length | 49.5 cm |

Offer Sustainability

| | |
|-----------------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| PVC free | Yes |
| California proposition 65 | WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

Contractual warranty

Warranty

18 months