

# Product data sheet

Specifications



## TeSys Deca contactor - 4P(4 NO) - AC-1 - $\leq 440$ V 32 A - 220 V AC 50/60 Hz coil

LC1DT32M7

### Main

<b>Range</b>	TeSys TeSys Deca
<b>Product name</b>	TeSys D TeSys Deca
<b>Product or component type</b>	Contacteur
<b>Device short name</b>	LC1D
<b>Contacteur application</b>	Resistive load
<b>Utilisation category</b>	AC-1
<b>Poles description</b>	4P
<b>Power pole contact composition</b>	4 NO
<b>[Ue] rated operational voltage</b>	Power circuit: $\leq 690$ V AC 25...400 Hz Power circuit: $\leq 300$ V DC
<b>[Ie] rated operational current</b>	32 A (at $\leq 60$ °C) at $\leq 440$ V AC AC-1 for power circuit
<b>Control circuit type</b>	AC at 50/60 Hz
<b>[Uc] control circuit voltage</b>	220 V AC 50/60 Hz
<b>Auxiliary contact composition</b>	1 NO + 1 NC
<b>[Uimp] rated impulse withstand voltage</b>	6 kV conforming to IEC 60947
<b>Overvoltage category</b>	III
<b>[Ith] conventional free air thermal current</b>	10 A (at 60 °C) for signalling circuit 32 A (at 60 °C) for power circuit
<b>Irms rated making capacity</b>	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 300 A at 440 V for power circuit conforming to IEC 60947
<b>Rated breaking capacity</b>	300 A at 440 V for power circuit conforming to IEC 60947
<b>[Icw] rated short-time withstand current</b>	40 A 40 °C - 10 min for power circuit 84 A 40 °C - 1 min for power circuit 145 A 40 °C - 10 s for power circuit 240 A 40 °C - 1 s for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit
<b>Associated fuse rating</b>	10 A gG for signalling circuit conforming to IEC 60947-5-1 50 A gG at $\leq 690$ V coordination type 1 for power circuit 35 A gG at $\leq 690$ V coordination type 2 for power circuit
<b>Average impedance</b>	2.5 mOhm - Ith 32 A 50 Hz for power circuit
<b>[Ui] rated insulation voltage</b>	Power circuit: 600 V CSA certified Power circuit: 600 V UL certified

Signalling circuit: 690 V conforming to IEC 60947-1  
 Signalling circuit: 600 V CSA certified  
 Signalling circuit: 600 V UL certified  
 Power circuit: 690 V conforming to IEC 60947-4-1

<b>Electrical durability</b>	1 Mcycles 32 A AC-1 at $U_e \leq 440$ V
<b>Power dissipation per pole</b>	2.5 W AC-1
<b>Front cover</b>	With
<b>Mounting support</b>	Plate Rail
<b>Standards</b>	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508 IEC 60335-1
<b>Product certifications</b>	GL UL RINA CCC GOST CSA BV LROS (Lloyds register of shipping) DNV
<b>Connections - terminals</b>	Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> solid without cable end Control circuit: screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> solid without cable end Power circuit: connector 1 cable(s) 2.5...10 mm <sup>2</sup> flexible without cable end Power circuit: connector 2 cable(s) 2.5...10 mm <sup>2</sup> flexible without cable end Power circuit: connector 1 cable(s) 2.5...10 mm <sup>2</sup> flexible with cable end Power circuit: connector 2 cable(s) 2.5...10 mm <sup>2</sup> flexible with cable end Power circuit: connector 1 cable(s) 2.5...16 mm <sup>2</sup> solid without cable end Power circuit: connector 2 cable(s) 2.5...16 mm <sup>2</sup> solid without cable end
<b>Tightening torque</b>	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat $\varnothing$ 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 1.7 N.m - on connector - with screwdriver flat $\varnothing$ 6 mm Power circuit: 1.7 N.m - on connector - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2 Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver pozidriv No 2
<b>Operating time</b>	4...19 ms opening 12...22 ms closing
<b>Safety reliability level</b>	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
<b>Mechanical durability</b>	15 Mcycles
<b>Maximum operating rate</b>	3600 cyc/h 60 °C

## Complementary

<b>Coil technology</b>	Without built-in suppressor module
<b>Control circuit voltage limits</b>	0.3...0.6 $U_c$ (-40...70 °C):drop-out AC 50/60 Hz 0.8...1.1 $U_c$ (-40...60 °C):operational AC 50 Hz 0.85...1.1 $U_c$ (-40...60 °C):operational AC 60 Hz 1...1.1 $U_c$ (60...70 °C):operational AC 50/60 Hz
<b>Inrush power in VA</b>	70 VA 60 Hz cos phi 0.75 (at 20 °C) 70 VA 50 Hz cos phi 0.75 (at 20 °C)
<b>Hold-in power consumption in VA</b>	7.5 VA 60 Hz cos phi 0.3 (at 20 °C) 7 VA 50 Hz cos phi 0.3 (at 20 °C)
<b>Heat dissipation</b>	2...3 W at 50/60 Hz
<b>Auxiliary contacts type</b>	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1
<b>Signalling circuit frequency</b>	25...400 Hz
<b>Minimum switching current</b>	5 mA for signalling circuit
<b>Minimum switching voltage</b>	17 V for signalling circuit
<b>Non-overlap time</b>	1.5 ms on de-energisation between NC and NO contact

1.5 ms on energisation between NC and NO contact

**Insulation resistance** > 10 MOhm for signalling circuit

## Environment

**IP degree of protection** IP20 front face conforming to IEC 60529

**Protective treatment** TH conforming to IEC 60068-2-30

**Pollution degree** 3

**Ambient air temperature for operation** -40...60 °C  
60...70 °C with derating

**Ambient air temperature for storage** -60...80 °C

**Operating altitude** 0...3000 m

**Fire resistance** 850 °C conforming to IEC 60695-2-1

**Mechanical robustness** Vibrations contactor open: 2 Gn, 5...300 Hz  
Vibrations contactor closed: 4 Gn, 5...300 Hz  
Shocks contactor closed: 15 Gn for 11 ms  
Shocks contactor open: 8 Gn for 11 ms

**Height** 91 mm

**Width** 45 mm

**Depth** 99 mm

**Net weight** 0.425 kg

## Packing Units

**Unit Type of Package 1** PCE

**Number of Units in Package 1** 1

**Package 1 Weight** 424 g

**Package 1 Height** 4.9 cm

**Package 1 width** 11.1 cm

**Package 1 Length** 8.9 cm

**Unit Type of Package 2** S02

**Number of Units in Package 2** 15

**Package 2 Weight** 6.815 kg

**Package 2 Height** 15 cm

**Package 2 width** 30 cm

**Package 2 Length** 40 cm

**Unit Type of Package 3** P06

**Number of Units in Package 3** 240

**Package 3 Weight** 117.54 kg

**Package 3 Height** 77 cm

**Package 3 width** 80 cm

**Package 3 Length** 60 cm

## Offer Sustainability

**Sustainable offer status** Green Premium product

**REACH Regulation** [REACH Declaration](#)

**REACH free of SVHC** Yes

**EU RoHS Directive** Compliant

[EU RoHS Declaration](#)

<b>Toxic heavy metal free</b>	Yes
<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>
<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
<b>PVC free</b>	Yes
<b>California proposition 65</b>	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

**Contractual warranty**

<b>Warranty</b>	18 months
-----------------	-----------