

# Product data sheet

Specifications



## TeSys LRD,Deca thermal overload relays - 0.4...0.63 A - class 10A

LRD04

### Main

<b>Range</b>	TeSys TeSys Deca
<b>Product name</b>	TeSys LRD TeSys Deca
<b>Product or component type</b>	Differential thermal overload relay
<b>Device short name</b>	LRD
<b>Relay application</b>	Motor protection
<b>Product compatibility</b>	LC1D25 LC1D38 LC1D32 LC1D18 LC1D12 LC1D09
<b>Network type</b>	AC DC
<b>Thermal overload class</b>	Class 10A conforming to IEC 60947-4-1
<b>Thermal protection adjustment range</b>	0.4...0.63 A
<b>[Ui] rated insulation voltage</b>	Power circuit: 600 V conforming to CSA Power circuit: 600 V conforming to UL Power circuit: 690 V conforming to IEC 60947-4-1

### Complementary

<b>Network frequency</b>	0...400 Hz
<b>Mounting support</b>	Plate, with specific accessories Rail, with specific accessories Under contactor
<b>Tripping threshold</b>	1.14 +/- 0.06 I <sub>r</sub> conforming to IEC 60947-4-1
<b>Auxiliary contact composition</b>	1 NO + 1 NC
<b>[I<sub>th</sub>] conventional free air thermal current</b>	5 A for signalling circuit
<b>Permissible current</b>	3 A at 120 V AC-15 for signalling circuit 0.22 A at 125 V DC-13 for signalling circuit
<b>[U<sub>e</sub>] rated operational voltage</b>	690 V AC 0...400 Hz for power circuit conforming to IEC 60947-4-1
<b>Associated fuse rating</b>	4 A gG for signalling circuit 4 A BS for signalling circuit
<b>[U<sub>imp</sub>] rated impulse withstand voltage</b>	6 kV

<b>Phase failure sensitivity</b>	Tripping current 130 % of I <sub>r</sub> on two phase, the last one at 0
<b>Control type</b>	Red push-button: stop Blue push-button: reset
<b>Temperature compensation</b>	-20...60 °C
<b>Connections - terminals</b>	Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> solid without cable end Power circuit: screw clamp terminals 1 cable(s) 1.5...10 mm <sup>2</sup> flexible without cable end Power circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> flexible with cable end Power circuit: screw clamp terminals 1 cable(s) 1...6 mm <sup>2</sup> solid without cable end
<b>Tightening torque</b>	Control circuit: 1.7 N.m - on screw clamp terminals Power circuit: 1.7 N.m - on screw clamp terminals
<b>Height</b>	66 mm
<b>Width</b>	45 mm
<b>Depth</b>	70 mm
<b>Net weight</b>	0.124 kg

## Environment

<b>Protective treatment</b>	TH conforming to IEC 60068
<b>IP degree of protection</b>	IP20 conforming to IEC 60529
<b>Ambient air temperature for operation</b>	-20...60 °C without derating conforming to IEC 60947-4-1
<b>Ambient air temperature for storage</b>	-60...70 °C
<b>Flame retardance</b>	V1 conforming to UL 94
<b>Mechanical robustness</b>	Vibrations: 6 Gn conforming to IEC 60068-2-6 Shocks: 15 Gn for 11 ms conforming to IEC 60068-2-7
<b>Dielectric strength</b>	1.89 kV at 50 Hz conforming to IEC 60947-1
<b>Standards</b>	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4 GB/T 14048.5 EN 50495
<b>Product certifications</b>	IEC UL CSA CCC EAC BV RINA DNV-GL LROS (Lloyds register of shipping) ATEX INERIS UKCA

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Weight</b>	137 g
<b>Package 1 Height</b>	4.9 cm
<b>Package 1 width</b>	7.7 cm
<b>Package 1 Length</b>	8.8 cm
<b>Unit Type of Package 2</b>	S02
<b>Number of Units in Package 2</b>	24

Package 2 Weight	3.62 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P06
Number of Units in Package 3	384
Package 3 Weight	69.924 kg
Package 3 Height	77 cm
Package 3 width	60 cm
Package 3 Length	80 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

## Contractual warranty

Warranty	18 months
----------	-----------