

standard motor mechanism module MT400/630, ComPact NSX400/630, 220/240 VAC 50/60 Hz, 208/277 VAC 60 Hz

LV432641

Main

MT400/630
Motor mechanism
Automatic spring charging
ComPact NSX400 ComPact NSX630 Compact NSX400 DC Compact NSX630 DC PowerPact Multistandard EasyPact CVS400 EasyPact CVS630 PowerPact L
Standard
208277 V AC 60 Hz 220240 V AC 50/60 Hz
Fixed
400 A 630 A

Complementary

Control signal type	Impulse Maintained
Maximum operating frequency	4 per minute
Maximum power consumption in VA	500 VA closing 500 VA opening
Locking options description	Padlocking in OFF position 1 to 3 padlocks Ø 5 to Ø 8

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3.15 kg
Package 1 Height	19.8 cm
Package 1 width	17.5 cm
Package 1 Length	17.5 cm
Unit Type of Package 2	S04
Number of Units in Package 2	6

Package 2 Weight	19.654 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm
Unit Type of Package 3	P12
Number of Units in Package 3	24
Package 3 Weight	90.616 kg
Package 3 Height	50 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov	

Contractual warranty

Warranty	18 months	
----------	-----------	--