



MN undervoltage release, ComPact NS630b to NS3200 fixed, MasterPact NT/NW, rated voltage 48/60 VDC, 48 VAC 50/60 Hz

33669

M	a	ın

Device short name	MN
Product or component type	Voltage release
Device application	Control
Range compatibility	MasterPact NT Masterpact NW ComPact NS630b1600 ComPact NS1600b3200
Voltage release type	Undervoltage release
[Uc] control circuit voltage	48 V AC 50/60 Hz 4860 V DC

Complementary

Threshold tripping voltage	0.350.7 x Un opening 0.85 x Un closing
Supply holding power	4.5 W
Mounting mode	Fixed
Response time	40 ms (Masterpact NT) 90 ms (Masterpact NW) 90 ms (Compact NS630b1600) 90 ms (Compact NS1600b3200)
Accessory / separate part category	Spare parts for Masterpact NT Spare parts for Masterpact NW Spare parts for Compact NS1600b3200 Spare parts for Compact NS630b1600

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	151 g
Package 1 Height	3.4 cm
Package 1 width	6.2 cm
Package 1 Length	8.3 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	1.554 kg

Package 2 Height	13 cm
Package 2 width	9 cm
Package 2 Length	19 cm
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Weight	9.747 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	

Contractual warranty

Warranty	18 months
----------	-----------