

Product data sheet

Specifications



circuit breaker Masterpact NW63H2 - 6300 A - 3 poles - drawout - w/o trip unit

48349

Main

| | |
|---------------------------|-------------------------------|
| Range of product | Masterpact NW |
| Product or component type | Basic frame |
| Device short name | Masterpact NW63 |
| Circuit breaker name | Masterpact NW63H2 |
| Poles description | 3P |
| Network type | AC |
| Breaking capacity code | H2 |
| Suitability for isolation | Yes conforming to IEC 60947-2 |
| Utilisation category | Category B |

Complementary

| | |
|---|---|
| Network frequency | 50/60 Hz |
| Control type | Push-button |
| Mounting mode | Drawout |
| [In] rated current | 6300 A at 40 °C |
| [Ui] rated insulation voltage | 1000 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Uimp] rated impulse withstand voltage | 12 kV conforming to IEC 60947-2 |
| [Icm] rated short-circuit making capacity | 220 kA 690 V AC at 50/60 Hz 286 kA 525 V AC at 50/60 Hz |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Circuit breaker CT rating | 6300 A |
| Breaking capacity | 150 kA Icu at 220...240 V AC 50/60 Hz conforming to IEC 60947-2 150 kA Icu at 380...415 V AC 50/60 Hz conforming to IEC 60947-2 100 kA Icu at 690 V AC 50/60 Hz conforming to IEC 60947-2 130 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 150 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Ics] rated service breaking capacity | 100 kA at 690 V AC 50/60 Hz conforming to IEC 60947-2 130 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2 |
| Protection type | Without protection |
| Mechanical durability | 10000 cycles with maintenance conforming to IEC 60947-2 5000 cycles without maintenance conforming to IEC 60947-2 |
| Electrical durability | AC-3: 6000 cycles 440/690 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 1500 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 1500 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 |

AC-23A: 1500 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-2
AC-23A: 1500 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-2

| | |
|--|--|
| Connection pitch | 230 mm |
| [Icw] rated short-time withstand current | 100 kA 1 s conforming to IEC 60947-2 100 kA 3 s conforming to IEC 60947-2 |
| Integral instant protection | 243...297 kA |
| Maximum breaking time | 25 ms |
| Maximum closing response time | 80 ms |
| Height | 479 mm |
| Width | 786 mm |
| Depth | 394.5 mm |

Environment

| | |
|---------------------------------------|-----------------------------|
| Standards | IEC 60947-2 |
| Product certifications | ASEFA ASTA |
| Pollution degree | 4 conforming to IEC 60664-1 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...85 °C |

Packing Units

| | |
|------------------------------|------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 132.286 kg |
| Package 1 Height | 75 cm |
| Package 1 width | 75 cm |
| Package 1 Length | 120 cm |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| PVC free | Yes |
| California proposition 65 | WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

Contractual warranty

Warranty

18 months